

USG LEVELROCK® BRAND RH ACCELERATOR

DESCRIPTION

Set time accelerant for floor underlayments

- For use with USG Levelrock® Floor Underlayments
- Reduces set time on the first pour (lift) on radiant heat projects
- Applied by USG Levelrock authorized applicators

LIMITATIONS

1. Do not use in exterior applications.

MIXING

Always add USG Levelrock RH Accelerator into the water before adding sand or underlayment. The typical amount of USG RH Accelerator used is approximately 2 ounces (57 g) per 80 lb. (36.3 kg) bag of USG Levelrock Floor Underlayment. Because job conditions will impact the final set of USG Levelrock Floor Underlayment, it may be necessary to use more than 2 ounces (57 g)/80 lb. (36.3 kg) bag.

When needed, a maximum of 4 ounces (113 g) of USG Levelrock RH Accelerator per 80 lb. (36.3 kg) bag of floor underlayment may be used, but only where normal job sets are extremely long. Under some rare job conditions, less than 2 ounces (57 g) of USG Levelrock RH Accelerator per 80 lb. (36.3 kg) bag of floor underlayment may be necessary.

APPLICATION

It is usually more effective to accelerate the first pour as much as possible and reduce the wait time until the second pour can commence. However, if the first pour is not covered by the second pour within one hour, an application of USG Levelrock® Acrylic Concrete Primer must be used at a 4 parts water to 1 part primer (4:1) dilution rate to ensure the two pours bond together. Therefore, accelerating the first pour too much may not save time if a primer coat must be applied prior to pouring the second one.

The use of the accelerator must be carefully done to avoid serious problems. Excessive or improper use could cause the USG Levelrock Floor Underlayment to set up anywhere in the mixing-pumping stage, even with the pump operating. In addition, job factors such as water temperature, sand, air temperature, cleanliness of the pumping equipment and age of the underlayment will affect the efficiency of the USG Levelrock RH Accelerator.

STORAGE

Keep USG Levelrock RH Accelerator in a dry covered area in temperatures between 40 °F (4 °C) and 110 °F (43 °C). USG Levelrock RH Accelerator has a shelf life of 6 months from date of manufacture.

SUBMITTAL APPROVALS

Job Name	
Contractor	Date

PRODUCT INFORMATION

See usg.com for the most up-to-date product information.

CAUTION

Dust from mixing may cause irritation to eyes, skin, nose, throat and upper respiratory tract. Use only in a well-ventilated area, wear a NIOSH/MSHA-approved respirator. Wear eye protection. If eye contact occurs, flush thoroughly with water for 15 minutes. Remove contact lenses and continue rinsing. If on skin: Wash with plenty of water. If swallowed and/or irritation persists, call physician. Keep containers closed when not in use. For more information call Product Safety: 800-507-8899 or see the SDS at usg.com
KEEP OUT OF REACH OF CHILDREN.

TRADEMARKS

The trademarks USG, LEVELROCK, IT'S YOUR WORLD. BUILD IT., the USG logo, the design elements and colors and related marks are trademarks of USG Corporation or its affiliates.

NOTE

The information in this document is subject to change without notice. USG Corp. and/or its affiliates assume no responsibility for any errors that may inadvertently appear in this document. Consult your USG sales office or representative for information.

NOTICE

We shall not be liable for consequential, incidental or special damages, directly or indirectly sustained, nor for any loss caused by application of these goods not in accordance with current printed instructions or for other than the intended use. Our liability is expressly limited to the replacement of defective goods or a refund of the purchase price, at USG's option, and does not include costs of labor, floor-covering materials, or any other costs associated with material replacement. Any claim shall be deemed waived unless made in writing to us within thirty (30) days from date it was or reasonably should have been discovered. For all applicable warranty information, please refer to *USG Levelrock® Brand & USG Durock™ Brand Performance Flooring Products Two-Year Limited Warranty for USG Levelrock Applicators* (IG1727) located at usg.com. For all terms and conditions see usg.com/terms-and-conditions.

SAFETY FIRST!

Follow good safety/industrial hygiene practices during installation. Wear appropriate personal protective equipment. Read applicable SDSs and literature before specification and installation.

800 USG.4YOU
800 (874.4968)
usg.com

Manufactured for
United States Gypsum Company
550 West Adams Street
Chicago, IL 60661

IG1958-USA-ENG/rev. 12-24
© 2024 USG Corporation and/or
its affiliates. All rights reserved.
Printed in U.S.A.

