



USG LEVELROCK® BRAND

WOOD PRIMER

DESCRIPTION

USG Levelrock® Brand Wood Primer is designed and manufactured by USG to improve adhesion to wood subfloors including OSB, plywood and corrugated galvanized steel deck substrates. The surfaces of these floors must be sound and non-friable. For old and new concrete floors and existing floor coverings such as vinyl tile, ceramic tile, linoleum and varnished wood floors, use USG Levelrock® Acrylic Concrete Primer.

This low odor primer can be sprayed, broomed on or paint roller-applied to the subfloor by USG Levelrock applicators prior to installing USG Levelrock® Floor Underlayments in all types of commercial, institutional and residential flooring applications.

LIMITATIONS

1. Do not use in exterior applications.
2. Do not apply at temperatures below 50 °F (10 °C) or above 120 °F (49 °C).
3. Do not apply on excessively dusty or dirty subfloors.

APPLICATION

Floor to be primed must be sound, clean, free of alkali and dry. Remove dirt, wax, polish, paint and all foreign material that would interfere with a good bond.

A minimum building temperature of 50 °F (10 °C) must be maintained for all USG Levelrock Wood Primers during the drying period. Cooler temperatures and high humidity will prolong dry times.

For most applications, USG Levelrock Wood Primer will need to be diluted (1:1) by mixing one part primer to one part water. Allow a minimum of one hour before applying USG Levelrock Floor Underlayment. Up to 3 hours of drying can greatly enhance the bond strength between the subfloor and the poured underlayment.

For use over corrugated steel decks, apply USG Levelrock Wood Primer at full strength without diluting. Allow a minimum of 3 hours for adequate drying to a maximum of 24 hours before pouring USG Levelrock® CSD® Early Exposure™ Floor Underlayment.

CLEANUP

Clean tools with water before primer dries. Flush with large quantities of water. Dry primer can be cleaned with mineral spirits.

STORAGE

Protect from freezing, and do not store above 120 °F (49 °C). USG Levelrock Wood Primer has limited freeze thaw protection. If accidentally frozen, allow to thaw at room temperature. Stir to a homogenous state before using. Do not use material that is coagulated or has excessive settlement that cannot be readily remixed. Discard questionable material. Do not over-stir or use a high-speed mixer, as excessive air entrainment may result. USG Levelrock Wood Primer has a shelf life of 12 months from the manufacture date when stored under proper conditions in the original, unopened container.

EXTENDED WARRANTY

An extended warranty may apply when using USG Levelrock Wood Primer in a system application. Please contact USG for further details.

SUBMITTAL APPROVALS

Job Name	
Contractor	Date

PRODUCT INFORMATION

See usg.com for the most up-to-date product information.

WARNING

May cause an allergic skin reaction. Avoid breathing mist or vapor. Use only in a well-ventilated area, wear a NIOSH/MSHA-approved respirator. Wear protective gloves/protective clothing/eye protection. If on skin: Wash with plenty of water. If skin irritation or rash occurs, or if swallowed: Get medical attention. If eye contact occurs, flush thoroughly with water for 15 minutes. Contaminated work clothing should not be allowed out of the workplace. Wash contaminated clothing before reuse. Dispose of in accordance with local, state, and federal regulations. Keep containers closed when not in use. For more information call Product Safety: 1-800-507-8899 or see the SDS at usg.com. **KEEP OUT OF REACH OF CHILDREN.**

TRADEMARKS

The trademarks USG, CSD, EARLY EXPOSURE, LEVELROCK, IT'S YOUR WORLD. BUILD IT., the USG logo, the design elements and colors and related marks are trademarks of USG Corporation or its affiliates.

NOTE

The information in this document is subject to change without notice. USG Corp. and/or its affiliates assume no responsibility for any errors that may inadvertently appear in this document. Consult your USG sales office or representative for information.

NOTICE

We shall not be liable for consequential, incidental or special damages, directly or indirectly sustained, nor for any loss caused by application of these goods not in accordance with current printed instructions or for other than the intended use. Our liability is expressly limited to the replacement of defective goods or a refund of the purchase price, at USG's option, and does not include costs of labor, floor-covering materials, or any other costs associated with material replacement. Any claim shall be deemed waived unless made in writing to us within thirty (30) days from date it was or reasonably should have been discovered. For all applicable warranty information, please refer to *USG Levelrock® Brand & USG Durock™ Brand Performance Flooring Products Two-Year Limited Warranty for USG Levelrock Applicators (IG1727)* located at usg.com. For all terms and conditions see usg.com/terms-and-conditions.

SAFETY FIRST!

Follow good safety/industrial hygiene practices during installation. Wear appropriate personal protective equipment. Read applicable SDSs and literature before specification and installation.



800 USG.4YOU
800 (874.4968)
usg.com

Manufactured by
United States Gypsum Company
550 West Adams Street
Chicago, IL 60661

IG1505-USA-ENG/rev. 11-24
© 2024 USG Corporation and/or
its affiliates. All rights reserved.
Printed in U.S.A.

USG
IT'S YOUR WORLD. BUILD IT.®