

# USG MARS™ ACOUSTICAL PANELS

CLIMAPLUS™ PERFORMANCE

USG Mars™ Acoustical Panels with  
ClimaPlus™ Performance, and  
USG Donn® Brand Identitee® DXI™  
Acoustical Suspension System

TO ORDER SAMPLES, GO TO [USG.COM](http://USG.COM) OR [CGCINC.COM](http://CGCINC.COM)



Flat White  
050



Limited color options available.  
See Ceiling Solutions Color  
Program for details.

## FEATURES AND BENEFITS

- Excellent noise reduction. Up to NRC-0.75.
- High light-reflective finish (LR-0.90) reduces light fixtures and energy use.
- Washable, scrubbable finish, that is impact and scratch resistant.
- Available in Optimized Recycled Content formulations to help maximize LEED recycled content contribution.
- Nondirectional, monolithic visual reduces installation time and waste.
- ClimaPlus™ 30-year limited system warranty against visible sag, mold and mildew.
- GREENGUARD Gold Certified for low-emitting performance.
- Balanced Acoustics. High-NRC and High-CAC.
- USG Mars™ Acoustical Panels are part of the Ecoblueprint™ portfolio — meeting today's sustainability standards. For sustainability documentation go to [USG.com](http://USG.com) or [CGCInc.com](http://CGCInc.com).

## APPLICATIONS

- Offices and conference rooms
- Healthcare (HIPAA requirements)
- Classrooms
- Dining rooms and food-prep areas

## SUBSTRATE

- Wet-formed mineral fiber

Fine-Textured Panel

# USG MARS™ ACOUSTICAL PANELS

## CLIMAPLUS™ PERFORMANCE


ORDER SAMPLES/LITERATURE  
 USG: usg.com or samplitt@usg.com  
 CGC: contact Sales Representative

FOR MOST UP-TO-DATE  
 TECHNICAL INFORMATION  
 AND LEED REPORT TOOL  
 usgdesignstudio.com  
 cgcdesignstudio.com

TECHNICAL SERVICES  
 800.USG.4YOU (874-4968)



PRODUCT CERTIFIED  
 FOR LOW CHEMICAL  
 EMISSIONS:  
 ULCOM/CG  
 UL2818



### USG MARS™ PANELS

| Edge | Panel Size   | Fire Rating | Item No. | UL Classified |          | LR <sup>2</sup> | Color | Grid Options | VOC Emissions | Anti-Mold & Mildew/Sag Resistance | Recycled Content <sup>1</sup> | Panel Cost |
|------|--------------|-------------|----------|---------------|----------|-----------------|-------|--------------|---------------|-----------------------------------|-------------------------------|------------|
|      |              |             |          | NRC           | CAC Min. |                 |       |              |               |                                   |                               |            |
| SQ   | 2'x2'x3/4"   | Class A     | 86185    | 0.75          | 35       | 0.90            | White | A,B,C        | Low           | 69%                               | 69%                           | \$\$       |
|      | 2'x2'x3/4"   | Class A     | 86185HRC | 0.70          | 35       | 0.90            | White | A,B,C        | Low           | 81%                               | 81%                           | \$\$       |
|      | 2'x4'x3/4"   | Class A     | 88185    | 0.75          | 35       | 0.90            | White | A,B          | Low           | 69%                               | 69%                           | \$\$       |
|      | 2'x4'x3/4"   | Class A     | 88185HRC | 0.70          | 35       | 0.90            | White | A,B          | Low           | 81%                               | 81%                           | \$\$       |
| SLT  | 2'x2'x3/4"   | Class A     | 86785    | 0.75          | 35       | 0.90            | White | D            | Low           | 69%                               | 69%                           | \$\$       |
|      | 2'x2'x3/4"   | Class A     | 86785HRC | 0.70          | 35       | 0.90            | White | D            | Low           | 81%                               | 81%                           | \$\$       |
|      | 2'x4'x3/4"   | Class A     | 88785    | 0.75          | 35       | 0.90            | White | D            | Low           | 69%                               | 69%                           | \$\$       |
|      | 2'x4'x3/4"   | Class A     | 88785HRC | 0.70          | 35       | 0.90            | White | D            | Low           | 81%                               | 81%                           | \$\$       |
|      | 30"x30"x3/4" | Class A     | 86875    | 0.75          | 35       | 0.90            | White | D            | Low           | 69%                               | 69%                           | \$\$       |
| FLB  | 2'x2'x3/4"   | Class A     | 86985    | 0.75          | 35       | 0.90            | White | E,F,G,H      | Low           | 69%                               | 69%                           | \$\$       |
|      | 2'x2'x3/4"   | Class A     | 86985HRC | 0.70          | 35       | 0.90            | White | E,F,G,H      | Low           | 81%                               | 81%                           | \$\$       |
|      | 2'x4'x3/4"   | Class A     | 88985    | 0.75          | 35       | 0.90            | White | E,F,G,H      | Low           | 69%                               | 69%                           | \$\$       |
|      | 2'x4'x3/4"   | Class A     | 88985HRC | 0.70          | 35       | 0.90            | White | E,F,G,H      | Low           | 81%                               | 81%                           | \$\$       |
|      | 30"x30"x3/4" | Class A     | 86830    | 0.75          | 35       | 0.90            | White | E,F,G,H      | Low           | 69%                               | 69%                           | \$\$       |

**Low Emissions (VOC)**  
 Third party (GREENGUARD Gold) certified for low-emitting performance, meets California Department of Public Health's (CDPH) Standard Method v1.2 - 2017 (CA Section 01350). \*Certificates of Compliance\* for Low VOC Emissions are available on usg.com and at spot.ul.com.

**ClimaPlus™ Warranty Performance<sup>3</sup>**  
 Contains a broad-spectrum antimicrobial additive on the face and back of the panel that provides resistance against the growth of mold and mildew. Includes sag-resistance performance.

**High Recycled Content**  
 USG classifies High Recycled Content as greater than 50%. Total recycled content is based on product composition of postconsumer and preconsumer (postindustrial) recycled content per FTC guidelines.

### GRID PROFILE OPTIONS

| A<br>USG<br>DX* | B<br>USG<br>DXW™ | C <sup>4</sup><br>USG Centricitee™<br>DXT™ | D<br>USG<br>DX* | E<br>USG Centricitee™<br>DXT™ | F<br>USG Fineline®<br>DXF™ | G<br>USG Fineline®<br>1/8 DXFF™ | H<br>USG Identitee®<br>DXI™ |
|-----------------|------------------|--|-----------------|-------------------------------|----------------------------|---------------------------------|-----------------------------|
|                 |                  |  |                 |                               |                            |                                 |                             |

### PHYSICAL DATA/ FOOTNOTES

**Product literature**  
 Data sheet: SC1966

**ASTM E1264 classification**  
 ASTM E1264-22 Type IV, Form 1 & 2, Pattern E & G  
 ASTM E1264-23 Type A, Form A2.1, Pattern E & G

**ASTM E84 and CAN/ULC S102 surface-burning characteristics**  
 Class A  
 Flame spread: 25 or less  
 Smoke developed: 50 or less

**Weight**  
 1.01 lb./sq. ft.

**Online tools**  
 usgdesignstudio.com or cgcdesignstudio.com

**Thermal resistance**  
 R-2.2

**Maximum backloading**  
 See USG 30-Year Limited System Warranty Commercial Applications (SC2102).

**Maintenance**  
 Can be cleaned easily with a soft brush or vacuum. To clean panel, use a clean, white cloth with water or a mild detergent and wipe surface.

**Metric sizes available**  
 Contact sales for minimum quantities and lead times.

- Notes**
- For details, see USG Sustainability tool at usgdesignstudio.com or cgcdesignstudio.com.
  - LR values are shown as averages.
  - Panel face and back surfaces treated with a proprietary, broad-spectrum antimicrobial additive that inhibits and retards the growth of mold, mildew and bacteria. For details, see USG 30-Year Limited System Warranty Commercial Applications (SC2102).
  - Maximum 2'x2' with SQ edge panels.
  - Select custom color panels are available in limited sizes and edge profiles. Minimum order quantities apply. Please contact your local sales representative for availability, pricing, minimum order quantities and lead times.

### Notice

The information in this document is subject to change without notice. CGC Inc. or USG Corp. assumes no responsibility for any errors that may inadvertently appear in this document.

SC1966/rev. 8-23  
 © 2023 USG Corporation and/or its affiliates. All rights reserved. Printed in USA

Manufactured by USG Interiors, LLC  
 550 West Adams Street  
 Chicago, IL 60661

The trademarks USG, CGC, CE, CENTRICITEE, CLIMAPLUS, DONN, DX, DXF, DXFF, DXI, DXT, DXW, ECOBLUEPRINT, FINELINE, IDENTITEE, MARS, IT'S YOUR WORLD. BUILD IT., the USG/CGC logo, the design elements and colors, and related marks are trademarks of USG Corporation or its affiliates.

Safety First! Follow good safety/industrial hygiene practices during installation. Wear appropriate personal protective equipment. Read SDS and literature before specification and installation.

