

USG MICORE® SB

MINERAL FIBER BOARD

DESCRIPTION

USG Micore® SB Mineral Fiber Board is a mineral fiber board designed for use in stove board applications. It meets the requirements of Type 1 and Type 2 stove boards in accordance to UL1618.

USG Micore SB qualifies as a low VOC emitting material (meets CA 01350).

INTENDED FOR

- Use as a wall shield, floor protector and hearth extension around heat producing devices such as fireplaces, fireplace stoves and solid-fuel type room heaters

PRODUCT INFORMATION

See usg.com for the most up-to-date product information.

GREENGUARD INFORMATION

GREENGUARD Certified products are certified to GREENGUARD standards for low chemical emissions into indoor air during product usage. For more information, visit ul.com/gg.

LEED INFORMATION

For more information on LEED credit contribution please see the product page on usg.ecomedes.com.

DANGER

May cause cancer or damage to lungs from presence of respirable crystalline silica through prolonged or repeated exposure by inhalation. Do not handle until all safety precautions have been read and understood. Avoid breathing dust. Use only in a well-ventilated area, wear a NIOSH/MSHA-approved respirator. Cut and trim with a utility knife or hand saw to minimize dust levels. If a router is used, it must have a dust collection system. Wear protective gloves/protective clothing/eye protection. If exposed or concerned: Get medical attention. If eye contact occurs, flush thoroughly with water for 15 minutes. Remove contact lenses and continue rinsing. Dispose of in accordance with local, state, and federal regulations. For more information, call Product Safety: 1-800-507-8899 or see the SDS at usg.com.

KEEP OUT OF REACH OF CHILDREN.

TRADEMARKS

The trademarks USG, MICORE, IT'S YOUR WORLD. BUILD IT., the USG logo, the design elements and colors and related marks are trademarks of USG Corporation or its affiliates.

LEED is a registered trademark of U.S. Green Building Council.

NOTE

The information in this document is subject to change without notice. USG Corp. and/or its affiliates assume no responsibility for any errors that may inadvertently appear in this document. Consult your USG sales office or representative for information.

NOTICE

We shall not be liable for consequential, incidental or special damages, directly or indirectly sustained, nor for any loss caused by application of these goods not in accordance with current printed instructions or for other than the intended use. Our liability is expressly limited to the replacement of defective goods or a refund of the purchase price, at USG's option, and does not include costs of labor, floor-covering materials, or any other costs associated with material replacement. Any claim shall be deemed waived unless made in writing to us within thirty (30) days from date it was or reasonably should have been discovered.

SAFETY FIRST!

Follow good safety/industrial hygiene practices during installation. Wear appropriate personal protective equipment. Read applicable SDSs and literature before specification and installation.



PRODUCT DATA

Thickness ¹	1/2"
Size ²	4' x 4'
Boards per pallet	80
Weight	0.83 - 1.08 psf
Density	23 ± 3 pcf
Modulus of rupture ³	200 psi
Hardness (Janka ball test) ³	30 lbs.
Hygrometric expansion (50-70% RH)	0.10%
R-value ⁴	1.17
K Factor ⁴	0.43

Notes

1. Thickness tolerance ± 0.015"
2. Width and length tolerance ± 1/16"
3. Values shown are production averages
4. Determined per ASTM C518

NOTES/LIMITATIONS

1. Avoid exposure to excessive or continuous moisture. Installation and occupancy conditions should not exceed 85 °F/70% RH.
2. Not intended to be painted. Painting will impair the acoustical and fire performance and will void all manufacturer warranties.
3. Not intended for use with ceramic tile.
4. Do not stack higher than 3 pallets high.

STORAGE AND HANDLING

Store USG Micore SB Mineral Fiber Board in an enclosed shelter providing protection from damage and exposure to the elements. Do not stack higher than 3 pallets high. Shelf life is indefinite as long as material is protected against moisture and UV/sunlight.

800.USG.4YOU
800 (874.4968)
usg.com

Manufactured by
United States Gypsum Company
550 West Adams Street
Chicago, IL 60661

IG307474-USG-ENG/9-22
© 2022 USG Corporation and/or
its affiliates. All rights reserved.
Printed in U.S.A.