

USG ROCK FACE® ACOUSTICAL PANELS

CLIMAPLUS™ PERFORMANCE



USG Rock Face® Acoustical Panels
with ClimaPlus™ Performance/
USG Donn® Brand DX*/DXL™
Acoustical Suspension System

TO ORDER SAMPLES, GO TO USG.COM OR CGCINC.COM



Flat White
050

FEATURES AND BENEFITS

- Specially compounded textured surface with hard core.
- Perfect for increased abuse resistance and sag resistance.
- ClimaPlus™ 30-year limited system warranty against visible sag, mold and mildew.
- Firecode® product designed to meet life-safety codes.

APPLICATIONS

- Athletic areas and exercise rooms
- Schools
- Corridors
- Dormitory rooms

SUBSTRATE

- Wet-formed mineral fiber

Fine-Textured Panel

USG ROCK FACE® ACOUSTICAL PANELS

CLIMAPLUS™ PERFORMANCE

ORDER SAMPLES/LITERATURE
 USG: samplitt@usg.com
 fax: 888 874-2348 | usg.com
 CGC: contact Sales Representative

TECHNICAL SERVICES
 800 USG.4YOU (874-4968)

FOR MOST UP-TO-DATE TECHNICAL INFORMATION AND LEED REPORT TOOL
usgdesignstudio.com
cgcdesignstudio.com



PRODUCT CERTIFIED FOR LOW CHEMICAL EMISSIONS:
 ULCOM/GG
 UL 2818



USG ROCK FACE® PANELS

UL Classified													
Edge	Panel Size	Fire Rating ²	Item No.	NRC	CAC Min.	LR ³	Color	Grid Options	VOC Emissions	Anti-Mold & Mildew/Sag Resistance	Abuse Resistant	Recycled Content ¹	Panel Cost
SQ	2'x2'x5/8"		56335	0.55	35	0.86	White	A,B,C	Low			50%	\$\$
	2'x4'x5/8"		56380	0.55	35	0.86	White	A,B,C	Low			50%	\$\$
SLT	2'x2'x3/4"		55483	0.55	35	0.86	White	D,E,F	Low			50%	\$\$

Low Emissions (VOC)

Third party (GREENGUARD Gold) certified for low-emitting performance, meets California Department of Public Health's (CDPH) Standard Method v1.1 - 2010 (CA Section 01350). 'Certificates of Compliance' for Low VOC Emissions are available on usg.com and at productguide.ulenvironment.com.

ClimaPlus™ Warranty Performance⁴

Contains a broad-spectrum antimicrobial additive on the face and back of the panel that provides resistance against the growth of mold and mildew. Includes sag-resistance performance.

High Recycled Content

Classified as containing greater than 50% total recycled content. Total recycled content is based on product composition of postconsumer and preconsumer (postindustrial) recycled content per FTC guidelines.

Firecode[®]


Abuse Resistant

GRID PROFILE OPTIONS

A USG DX™/DXL™	B USG DXLA™	C USG ZXLA™	D USG DX™/DXL™	E USG DXLA™	F USG ZXLA™

PANEL RETENTION CLIP 20428

Attaches to 1-1/2" main tees and cross tees behind lay-in ceilings. The retention clips help prevent panel displacement from incidental contact. Recommended with USG Rock Face® ceiling panels for impact-resistant systems.



See this clip and other accessories in the Accessory Guide AC2396.

PHYSICAL DATA/ FOOTNOTES

Product literature
 Data sheet: SC1840

ASTM E1264 classification
 Type III, Form 2, Pattern CE

ASTM E84 and CAN/ULC S102 surface-burning characteristics
 Class A
 Flame spread: 25 or less
 Smoke developed: 50 or less

UL Type
 FR-83

Weight
 1.0-1.3 lb./sq. ft.

Online tools
usgdesignstudio.com or cgcdesignstudio.com

Thermal resistance
 R-1.6 (5/8" panels)
 R-1.9 (3/4" panels)

Maximum backloading
 See *USG 30-Year Limited System Warranty Commercial Applications* (SC2102).

Maintenance
 Can be cleaned easily with a soft brush or vacuum.

Durability tests
 ASTM D1037: Tested to 45 lbf. for a 1/4" depression by a Janka ball.
 ASTM D5420: Tested to 3.5 in./lbf. for impact.

Metric sizes available
 Contact sales for minimum quantities and lead times.

Notes

- For details, see LEED report tool at usgdesignstudio.com or cgcdesignstudio.com.
- Fire-rated items: see UL design details.
- LR values are shown as averages.
- For details, see *USG 30-Year Limited System Warranty Commercial Applications* (SC2102) and *ClimaPlus™ Ceilings Certification of Performance* (SC2451).

Notice

The information in this document is subject to change without notice. CGC Inc. or USG Corp. assumes no responsibility for any errors that may inadvertently appear in this document.

SC1840/rev. 11-16

© 2016 USG Corporation and/or its affiliates. All rights reserved. Printed in U.S.A.

Manufactured by
 USG Interiors, LLC
 550 West Adams Street
 Chicago, IL 60661

The trademarks USG, CGC, CLIMAPLUS, DONN, DX, DXL, DXLA, FIRECODE, ROCK FACE, ZXLA, IT'S YOUR WORLD. BUILD IT., the USG/CGC logo, the design elements and colors, and related marks are trademarks of USG Corporation or its affiliates.

Safety First! Follow good safety/industrial hygiene practices during installation. Wear appropriate personal protective equipment. Read SDS and literature before specification and installation.

