


USG SHEETROCK® BRAND ECOSMART PANELS FIRECODE® X



Highly sustainable and ultralightweight 5/8 in. Type X wall and ceiling gypsum panels for interior applications

- Meet Architecture 2030 Challenge for Products
 - Up to 25% less global warming potential (GWP)¹
 - Up to 25% less water used in the manufacturing process¹
 - Up to 22% less weight reduces transportation fuel energy by up to 20%¹
- Living Building Challenge™ Red List Free
- Contains 100% USDA certified biobased content
- Up to 94.6% recycled content (regionally available)
- Achieved GREENGUARD Gold Certification and qualifies as a low VOC emitting material (meets CA 01350)
- USGBC® LEED® v4.0—may assist in achieving 1-1/2 additional credits (up to 10 total credits)
- Underwriters Laboratories Inc. (UL) Classification as to fire resistance, surface-burning characteristics and noncombustibility
- Comply with ASTM C1396 specification for 5/8 in. Type X gypsum wallboard
- Offer comparable sound, strength, sag and impact resistance to standard 5/8 in. Type X
- Listed by UL in the most widely specified wall, column, floor-ceiling and roof-ceiling assemblies (refer to specific UL designs for complete details)

Note:

1. Compared to standard 5/8 in. Type X gypsum panels as presented in the Gypsum Association's *5/8 in. Type X Environmental Product Declaration (FPI/GA/01/2014)* with fresh water usage updated to be in accordance with ISO 14046.

DESCRIPTION

USG Sheetrock® Brand EcoSmart Panels Firecode® X represent a revolution in wallboard manufacturing, significantly reducing the need for natural resources and impact on the environment. These 5/8 in. Type X lightweight gypsum panels have been formulated to achieve all of the strength and performance characteristics as standard 5/8 in. USG Sheetrock® Brand Firecode® X Panels at a significantly lower environmental impact and reduced weight. They feature an innovative noncombustible gypsum core encased in 100% recycled face and back papers that form a high strength-to-weight ratio composite design. The natural finish face paper is folded around the long edges to reinforce and protect the core, and the ends are cut square and even. The long edges of the panels are tapered, allowing joints to be reinforced and concealed with USG Sheetrock® Brand joint treatment systems. The panels are UL Classified for fire resistance and can be used in any UL design in which UltraLight Innovation Type X (ULIX™) panels are listed. On the face along the long edge of each panel, the UL Type Designation is printed for easy identification after installation.

INTENDED FOR

- Commercial or residential applications where 5/8 in. Type X panels are required
- New or repair and remodel construction
- Load-bearing and non-load-bearing wood- or steel-framed fire-rated walls
- Wall, column, floor-ceiling and roof-ceiling assemblies (refer to specific UL designs for complete details)

LIMITATIONS

1. Avoid exposure to sustained temperatures exceeding 125 °F (52 °C).
2. Avoid exposure to excessive, repetitive or continuous moisture before, during and after installation. Eliminate sources of moisture immediately.
3. Maximum frame spacing for walls is 24 in. OC.
4. UL Type ULIX™ requires the use of insulation for single-layer, steel-framed UL fire-rated assemblies.
5. Must be stored off the ground and under cover in accordance with Gypsum Association's *Handling and Storage of Gypsum Panel Products* (GA-801).

INTERIOR INSTALLATION, FINISHING AND DECORATING INSTALLATION

USG Sheetrock® Brand EcoSmart Panels Firecode® X install and finish just like standard 5/8 in. USG Sheetrock® Brand Firecode® X Panels. Fastener type and spacing requirements are the same as for standard 5/8 in. Type X.

Maximum Frame Spacing Drywall Construction

Direct Application	Panel Thickness	Location	Application Method ²	Maximum Frame Spacing OC
Single-layer	5/8 in. (15.9 mm)	Ceilings	Perpendicular	24 in. (610 mm)
		Sidewalls	Parallel or perpendicular	24 in. (610 mm)
Double-layer	5/8 in. (15.9 mm)	Ceilings	Parallel or perpendicular	24 in. (610 mm) ³
		Sidewalls	Perpendicular	24 in. (610 mm) ³

Notes:

2. Long edge position relative to framing.
3. Maximum 16 in. OC if fire rating required.

FINISHING AND DECORATING

For high-quality finishing results, USG recommends USG Sheetrock® Brand finishing products.

Painting products and systems should be used that comply with recommendations and requirements in Appendices of ASTM C840. For priming and decorating with paint, texture or wall covering, follow manufacturer's directions for materials used. Gypsum Association's *Recommended Specification for Levels of Gypsum Board Finish* (GA-214) should be referred to in order to determine the level of finishing needed to ensure a surface properly prepared to accept the final decoration.

All surfaces, including applied joint compound, must be thoroughly dry, dust-free and not glossy. Prime with USG Sheetrock® Brand First Coat™ Primer or with an undiluted, interior latex flat paint with high-solids content. Allow to dry before decorating.

To improve fastener concealment where gypsum panel walls and ceilings will be subjected to critical artificial or natural lighting, or will be decorated with a gloss paint (eggshell, semigloss or gloss), the gypsum panel should be skim coated with joint compound. This equalizes suction and texture differences between the drywall face paper and the finished joint compound before painting. When a Level 5 finish is required, use USG Sheetrock® Brand Tuff-Hide™ Primer-Surfacer. See *USG Sheetrock® Brand Tuff-Hide™ Primer-Surfacer Submittal Sheet* (J1613) for limitations and application instructions.

For more information, refer to USG literature *Finishing & Decorating Gypsum Panels White Paper* (J2010).

TEST DATA

Property		ASTM Test Method	ASTM C1396 Specification 5/8 in. Wallboard	UL Type ULIX™
Noncombustibility		E136	Pass	Pass
Surface-burning characteristics	Flame Spread	E84	Flame Spread Index, not greater than 25	5
	Smoke Developed	E84	Smoke Developed Index, not greater than 450	5
	Classification	E84	—	Class A
Core hardness (lbf)	Field	C473 (B)	Not less than 11	Meets or exceeds
	End	C473 (B)	Not less than 11	Meets or exceeds
	Edge	C473 (B)	Not less than 11	Meets or exceeds
Flexural strength (lbf)	Parallel	C473 (B)	Not less than 46	Meets or exceeds
	Perpendicular	C473 (B)	Not less than 147	Meets or exceeds
Humidified deflection (in.)		C473	Not greater than 5/8 in.	Less than
Nail pull resistance (lbf)		C473 (B)	Not less than 87	Meets or exceeds

Note: For more information on sound performance, see USG literature *USG Sheetrock® Brand EcoSmart Panels Sound Performance Selector Guide* (WB2880).

PRODUCT DATA

	UL Type ULIX™
Thickness	5/8 in. (15.9 mm)
Lengths	8-16 ft. (2438-4877 mm)
Width ⁴	4 ft. (1219 mm), 54 in. x 12 ft. (1372 mm x 3658 mm)
Weight ⁵ , nominal	1.8 lb./sq. ft. (8.8 kg/sq. m.)
Edges	Tapered
Packaging	Two panels per bundle

Notes:

- Other sizes available by special order. Check with your local USG representative for availability.
- Represents approximate weight for design and shipping purposes. For specific product weight in your area, contact your local USG representative or call the Customer Service Center at 800 950-3839.

COMPLIANCE

PRODUCT INFORMATION

See usg.com for the most up-to-date product information.

GREENGUARD Certified products are certified to GREENGUARD standards for low chemical emissions into indoor air during product usage. For more information, visit ul.com/gg.

CAUTION

Dust may cause irritation to eyes, skin, nose, throat and upper respiratory tract. Cut and trim with a utility knife or hand saw to minimize dust levels. Power tools must be equipped with a dust collection system. Wear eye, skin and respiratory protection if necessary. If eye contact occurs, flush thoroughly with water for 15 minutes. If irritation persists, call a physician. Do not swallow. If swallowed, call a physician.

For more information call Product Safety: 800 507-8899 or see the SDS at usg.com.

KEEP OUT OF REACH OF CHILDREN

TRADEMARKS

The trademarks USG, FIRECODE, FIRST COAT, SHEETROCK, TUFF-HIDE, ULIX, IT'S YOUR WORLD, BUILD IT., the USG logo, the design elements and colors, and related marks are trademarks of USG Corporation or its affiliates.

The trademarks IBC and INTERNATIONAL BUILDING CODE are trademarks of International Code Council, Inc. The trademarks LEED and USGBC are trademarks of U.S. Green Building Council. The trademark ARCHITECTURE 2030 is a trademark of Architecture 2030 Corporation. The trademarks DECLARE and LIVING BUILDING CHALLENGE are trademarks of INTERNATIONAL LIVING FUTURE INSTITUTE. USDA BIOPREFERRED is a trademark of United States Department of Agriculture.

NOTE

Products described here may not be available in all geographic markets. Consult your USG Company sales office or representative for information. The information in this document is subject to change without notice. USG Corporation assumes no responsibility for any errors that may inadvertently appear in this document.

NOTICE

We shall not be liable for incidental and consequential damages, directly or indirectly sustained, nor for any loss caused by application of these goods not in accordance with current printed instructions or for other than the intended use. Our liability is expressly limited to replacement of defective goods. Any claim shall be deemed waived unless made in writing to us within thirty (30) days from date it was or reasonably should have been discovered.

SAFETY FIRST!

Follow good safety and industrial hygiene practices during handling and installation of all products and systems. Take necessary precautions and wear the appropriate personal protective equipment as needed. Read Safety Data Sheets and related literature on products before specification and/or installation.

- Meet or exceed ASTM C1396 Section 5 for 5/8 in. gypsum wallboard, Type X
- Classified as a Class A Interior Finish Material per Section 803.1 of the International Building Code® (IBC®)
- UL Classification as to fire resistance, surface-burning characteristics and core combustibility
- Meet Architecture 2030 Challenge Criteria for Products
- Living Building Challenge™ Red List Free
- USDA Certified Biobased Product
- Achieved GREENGUARD Gold Certification and qualifies as a low VOC emitting material (meets CA 01350)

SUBMITTAL APPROVALS

Job Name	
Contractor	Date



800 USG.4YOU
800 (874-4968)
usg.com

Manufactured by
United States Gypsum Company
550 West Adams Street
Chicago, IL 60661

WB2859-USA-ENG/rev. 5-19
© 2019 USG Corporation and/or
its affiliates. All rights reserved.
Printed in U.S.A.

