



**Superior
strength**



**Superior
workability**



**Ultrafast drying,
paint same day**

PRODUCT INFORMATION

See usg.com for the most up-to-date product information.

TRADEMARKS

The trademarks USG, First Coat, SHEETROCK, TUFF-COVER+, IT'S YOUR WORLD. BUILD IT., the USG logo, the design elements and colors, and related marks are trademarks of USG Corporation or its affiliates.

NOTE

Products described here may not be available in all geographic markets. Consult your U.S. Gypsum Company sales office or representative for information.

NOTE

We shall not be liable for incidental and consequential damages, directly or indirectly sustained, nor for any loss caused by application of these products not in accord with current instructions or for other than the intended use. Our liability is expressly limited to replacement of defective products except where provided otherwise in a product specific warranty.

CAUTION: Dust from sanding may cause irritation to eyes, skin, nose, throat and upper respiratory tract. Use only in a well-ventilated area, wear a NIOSH/MSHA-approved respirator. Use a sander with vacuum attachment or wet-sanding to reduce dust. Wear eye protection. If eye contact occurs, flush thoroughly with water for 15 minutes. If on skin: Wash with plenty of water. If swallowed or irritation persists, call physician. Keep containers closed when not in use. For more information call Product Safety: 800-507-8899 or see the SDS at usg.com

KEEP OUT OF REACH OF CHILDREN.

Manufactured for
United States Gypsum Company
550 West Adams Street, Chicago, IL 60661

J5452-USA-ENG/2-21

© 2021 USG Corporation and/or its affiliates.
All rights reserved. Printed in U.S.A.

USG SHEETROCK® BRAND TUFF-COVER +™ SPACKLING COMPOUND

PRODUCT OVERVIEW

USG Sheetrock® Brand Tuff-Cover +™ Spackling Compound is a lightweight patch and repair compound that delivers professional grade performance for interior or exterior repairs. USG Sheetrock® Brand Tuff-Cover +™ provides superior strength (vs. competitive lightweight spackling compounds), excellent workability and ultra-fast drying. In as little as one-coat, this easy-to-use solution won't shrink or crack, and delivers a strong, durable bond on almost any surface.

LIMITATIONS

1. Protect container from freezing, extreme heat and exposure to direct sunlight.
2. Do not mix with any other material.
3. **Do not use as a skim coat.**
4. Do not use if material is discolored or has an unpleasant odor.

PREPARATION

Before applying, store at room temperature 55-95°F (13-35°C) in a dry location for 24-hours. Do not thin down with water as it may delay drying, cause abnormal shrinkage or other negative effects. Surface should be clean, dry and dust-free.

RECOMMENDED REPAIRS

Formulated to fill defects on drywall, wood, stone, brick, or metal (for metal surfaces prime with a high-quality primer prior to patching).

APPLICATION

Using a 1-4" clean putty knife, apply USG Sheetrock® Brand Tuff-Cover +™ Spackling Compound on the area requiring repair. For small repairs, one coat is typically sufficient. For repairs deeper than 1/8" apply additional coats until flush with the surface. Maintain minimum air, compound and surface temperature of 55°F (13°C) until repair is completely dry before painting or re-coating.

Do Not Use as a Skim Coat.

Applied product should be dry within 30 min to 3-hours. Dry time will depend on repair depth and environmental conditions. After compound dries, sand with a wet sponge to eliminate dust. A 150-grit or finer sandpaper or 220-grit of finer abrasive mesh cloth may also be used for sanding. If scratch marks are present, use a finer sandpaper or mesh cloth. After use, wash tools and skin with clean water.

FINISHING

For priming and decorating with paint, texture, or wallcovering, follow manufacturer's directions for materials used. All surfaces must be dry, dust-free, and not glossy. A prime coat of USG Sheetrock® Brand First Coat™ or a good-quality interior latex flat wall paint should be applied undiluted and allowed to dry before decorating.

For exterior applications, always topcoat with a high-quality exterior paint within 24-hours of application. Do not apply if rain is expected.

PRODUCT DATA

Storage: Store at 55-95°F (13-35°C) in a dry location.

Shelf Life: Up to 12 months from date of manufacture under proper storage conditions.

Packaging: Pint (16 fl. oz.), Quart (32 fl. oz.) and 1-Gallon (128 fl. oz.) pails.

Cleanup: Wash tools and skin with warm, soapy water. Wipe tools dry to prevent rusting.

FROZEN MATERIAL GUIDELINES

1. In the event the material is frozen, allow it to thaw completely.
2. Do not apply any form of heat to container.
3. Open the container carefully to prevent spilling any separated liquid. Remix separated liquid back into compound until creamy.
4. Do not use if the material is not smooth or lump free after remixing.