



USG STRUCTURAL PANEL CONCRETE SUBFLOOR

MEZZANINE APPLICATION

- Three easy steps: lay, fasten, finish
- No pouring, no setting, no curing
- An alternative to poured concrete for noncombustible mezzanines meeting latest active ASTM standard E136
- A complete dry application
- Mold-, moisture- and termite-resistant
- Easily transported into building/fits in an elevator
- Fast installation/dimensionally stable

TYPICAL APPLICATIONS

• Industrial-Mechanical Rooms ^(1,2)	• Interior Balconies	(1) Floor Finish: In some instances, uses such as highly corrosive or hazardous environments must be designed accordingly. Follow the contract documents and the floor finish manufacturer's recommendations for the application of finished flooring. Note that most floor finishes will require an underlayment. Before the application of floor finish materials, ensure that all panels are properly fastened, with the fastener head driven flush or slightly below the surface of the panels.
• Storage Rooms ⁽²⁾	• Architectural Platforms	
• Lofts	• Performance Stages ⁽²⁾	(2) Storage, traffic and equipment might be limited based on the concentrated load limitation of USG Structural Panel Concrete Subfloor. A qualified architect or engineer should review and approve calculations, framing and fastener spacing for all projects.
• Repair Platforms for Equipment Such As Boom Cranes ⁽²⁾	• Corporate Training Rooms ⁽²⁾	
• Restaurants		

TEST DATA

Physical and Mechanical Properties	Test Standard	Approximate Values Standard (Metric)
Concentrated load	ASTM E661	550 lb. (2.45 kN) static 0.108 in. (2.7 mm) max. deflection @ 200 lb. (0.89 kN)
Mold resistance	ASTM D3273, ASTM G21	10, 0
Weight (3/4 in. [19 mm] thickness)	ASTM D1037	5.3 lb./ft. ² (26 kg/m ²)
Water absorption ^a	ASTM C1185, Sec. 5.2.3.1	<15%
Noncombustibility	ASTM E136 (unmodified) CAN/ULC-S114	Passed Passed
Surface-burning characteristics (flame spread/smoke developed)	ASTM E84, CAN/ULC-S102	0/0
Termite resistance	AWPA Standard E1-13	9.8
Low VOC emissions	CDPH/EHLB/Standard Method V1.1-2010 ^b	Compliant

(a) Absorption measured from equilibrium conditioning followed by immersion in water for 48 hours.

(b) Reference Standard: California Department of Public Health CDPH/EHLB/Standard Method Version 1.1, 2010 (Emission testing method for CA Specification 01350).

SYSTEM PERFORMANCE

Description	Reference
Code Reports	ICC ESR-1792; PER-13067 ^b
City Code Approvals	Los Angeles: LARR #25682
UL 1-, 1.5-, 2-Hour Fire-Resistance Designs ^a	G535, G536, G556 , G557, G558, G562, G588, L521, L541, L550, L569, L570, M502, M506, M515, M521, M527
ULC 1-, 1.5-, 2-Hour Fire-Resistance Designs ^a	I526, I527, I528, I529, M520, M521

(a) For the most up-to-date UL/ULC Designations, visit www.USGStructuralUL.com.

(b) For the most up-to-date Product Evaluation Report, visit www.PER13067.com

LOAD TABLE

The following table represents the load-carrying capacity of USG Structural Panel. For the most up-to-date load tables, see the Progressive Engineering Inc. Product Evaluation Report [PER-13067](#). For technical questions, email usgstructural@usg.com. **A qualified architect or engineer should review and approve calculations, framing and fastener spacing for all projects.**

Ultimate Uniform Load for USG Structural Panel Concrete Subfloor			
Joist Spacing ² - inches (millimeters)	12" (305 mm)	16" (406 mm)	24" (610 mm)
Uniform Load ³ - psf (kPa)	1,320 psf (63.2 kPa)	744 psf (35.6 kPa)	330 psf (15.8 kPa)

For SI: 1 inch = 25.4 mm, 1 psf = 47.88 Pa.

(1) **Ultimate Load Values have no safety factor included.**

(2) Two framing spans minimum per panel piece.

(3) Ultimate Uniform Load Table for general reference only. For complete load capacities, consult Progressive Engineering Inc. Product Evaluation Report [PER-13067](#).

STRUCTURAL FASTENERS

Reference [USG Structural Panel Recommended Fasteners \(SCP95\)](#) for current fastener information. Visit www.usgscp95.com.

General Note: In accordance with [PER-13067](#) for subfloor, the minimum screw pattern is 6 in. (153 mm) o.c. along the perimeter of the panels and 12 in. (305 mm) o.c. in the field of the panels. Do not use a larger size screw unless specified by the structural engineer.

A qualified architect or engineer should review and approve calculations, framing and fastener spacing for all projects.

**MSRP based upon full truckload delivered to jobsite:
Subfloor: \$4.50/sf**

SCP30-USA-ENG/rev. 2-20
© 2020 USG Corporation and/or its affiliates.
All rights reserved. Printed in U.S.A.

Manufactured by or for
United States Gypsum Company
550 West Adams Street
Chicago, IL 60661

800 USG.4YOU (874-4968)
usg.com | usgdesignstudio.com

PRODUCT INFORMATION

See usg.com for the most up-to-date product information.

TRADEMARKS

The trademarks USG, IT'S YOUR WORLD. BUILD IT., the USG logo, the design elements and colors, and related marks are trademarks of USG Corporation or its affiliates.

NOTICE

We shall not be liable for incidental or consequential damages, directly or indirectly sustained, nor for any loss caused by application of these goods not in accordance with current printed instruction or for other than the intended use. Our liability is expressly limited to replacement of defective goods. Any claim shall be deemed waived

unless made in writing to us within thirty (30) days from date it was or reasonably should have been discovered.

SAFETY FIRST!

Follow good safety/industrial hygiene practices during installation. Wear appropriate personal protective equipment. Read SDS and literature before specification and installation.