

USG TOUCHSTONE™ ACOUSTICAL PANELS

CLIMAPLUS™ PERFORMANCE

USG Touchstone™ Acoustical Panels with ClimaPlus™ Performance, and USG Donn® Brand DX® Acoustical Suspension System

TO ORDER SAMPLES, GO TO USG.COM OR CGCINC.COM



Flat White
050

FEATURES AND BENEFITS

- Panels are scuff and abuse resistant and can withstand day-to-day activity in high traffic areas.
- ClimaPlus™ 30-year limited system warranty against visible sag, mold and mildew.
- Firecode® product designed to meet life-safety codes.

APPLICATIONS

- Schools
- General Offices
- Retail Stores

SUBSTRATE

- Wet-formed Mineral Fiber

Medium-Textured Panel

USG TOUCHSTONE™ ACOUSTICAL PANELS
CLIMAPLUS™ PERFORMANCE

ORDER SAMPLES/LITERATURE
USG: usg.com or samplitt@usg.com
CGC: contact Sales Representative

FOR MOST UP-TO-DATE
TECHNICAL INFORMATION
AND LEED REPORT TOOL
usgdesignstudio.com
cgcdesignstudio.com
usg.ecomedes.com






















TECHNICAL SERVICES
800 USG.4YOU (874-4968)



PRODUCT CERTIFIED
FOR LOW CHEMICAL
EMISSIONS:
ULCOM/GG
UL 2818

30 YEAR LIMITED SYSTEM
WARRANTY
• No Visible Sag
• Mold/Mildew Protection

USG TOUCHSTONE™
PANELS

UL Classified													
Edge	Panel Size	Fire Rating ²	Item No.	NRC	CAC Min.	LR ³	Color	Grid Options	VOC Emissions	Anti-Mold & Mildew/Sag Resistance	Abuse Resistant	Recycled Content ¹	Panel Cost
													
SQ	2'x2'x5/8"		5893	0.55	35	0.86	White	A,B	Low			65%	\$\$
	2'x4'x5/8"		5894	0.55	35	0.86	White	A	Low			65%	\$\$
SLT	2'x2'x5/8"		5896	0.55	35	0.86	White	C	Low			65%	\$\$
													

Low Emissions (VOC)
Third party (GREENGUARD Gold) certified for low-emitting performance, meets California Department of Public Health's (CDPH) Standard Method v1.2 - 2017 (CA Section 01350). 'Certificates of Compliance' for Low VOC Emissions are available on usg.ecomedes.com and at spot.ul.com.

ClimaPlus™ Warranty Performance⁴
Contains a broad-spectrum antimicrobial additive on the face and back of the panel that provides resistance against the growth of mold and mildew. Includes sag-resistance performance.

Firecode®
Abuse Resistant

GRID PROFILE OPTIONS

A USG DXL™	B ⁵ USG Centricitee™ DXLT™	C USG DXL™	

PHYSICAL DATA/
FOOTNOTES

Product literature
Data sheet: SC2214
ASTM E1264 classification
ASTM E1264-22 Type III, Form 2, Pattern C, E, & I
ASTM E1264-23 Type A, Form A1.2, Pattern C, E, & I
ASTM E84 and CAN/ULC S102 surface-burning characteristics
Class A
Flame spread: 25 or less
Smoke developed: 50 or less
UL Type
FR-83
Weight
1.09 lb./sq. ft.

Online tools
usgdesignstudio.com, cgcdesignstudio.com or usg.ecomedes.com
Thermal resistance
R-1.6
Maximum backloading
See USG 30-Year Limited System Warranty Commercial Applications (SC2102).
Maintenance
Can be cleaned easily with a soft brush or vacuum.
Metric sizes available
Contact sales for minimum quantities and lead times.

Notes
1. For details, see USG Sustainability tool at usgdesignstudio.com or cgcdesignstudio.com.
2. Firecode® products are approved for use in fire-resistance rated UL designs, where the designs allow for the UL Type Designation.
3. LR values are shown as averages.
4. For details, see USG 30-Year Limited System Warranty Commercial Applications (SC2102).
5. Maximum 2'x2' with SQ edge panels.

Notice
The information in this document is subject to change without notice. CGC Inc. or USG Corp. assumes no responsibility for any errors that may inadvertently appear in this document.

SC2214/rev. 8-24
© 2024 USG Corporation and/or its affiliates. All rights reserved. Printed in USA