



USG TRANSLUCENTS™ CANOPIES



USG Transluents™
Canopies

TO ORDER SAMPLES, GO TO USG.COM OR CGCINC.COM

DÉCORS



FEATURES AND BENEFITS

- Preformed curved panels.
- Available in a variety of decors that feature embedded fabrics and other materials as well as solid colors from the color gallery.
- Sculptural shape and elegant color for any project.
- Three easy-to-use elements: wave, vault or valley.
- Individual suspension or connected groupings for ribbons or larger spaces.
- Four simple connection/suspension points for fast, trouble-free installation.

APPLICATIONS

- Interior Applications
- Curved Ceilings
- Pods, Islands, and Clouds
- New Construction or Renovation
- Sloped Ceilings
- Backlit Ceilings

COLOR GALLERY



USG TRANSLUCENTS™ CANOPIES

ORDER SAMPLES/LITERATURE
 USG: usg.com or samplitt@usg.com
 CGC: contact Sales Representative

TECHNICAL SERVICES
 800 USG.4YOU (874-4968)

FOR MOST UP-TO-DATE TECHNICAL INFORMATION AND LEED REPORT TOOL
 usgdesignstudio.com
 cgcdesignstudio.com

PRODUCT INFORMATION


Shape	Typical Sizes		System Weight
	Nominal	Actual (in plan)	
Wave	2'x6'	23-3/8"x65-3/8"	Approximately 2 lb./sq. ft.
Vault	2'x6'	23-3/8"x68-1/2"	Approximately 2 lb./sq. ft.
Valley	2'x6'	23-3/8"x68-1/2"	Approximately 2 lb./sq. ft.

Acoustics


This product does not offer any acoustical properties.

Elements

USG Translucents™ Canopies Panels can be suspended under lighting normally located in a suspended ceiling or can be lit from above with point-source lighting.



Perspective



PHYSICAL DATA

Product literature

Data sheet: IC596
 Installation Guide: IC564

Online tools

usgdesignstudio.com or cgcdesignstudio.com

Fire rating

USG Translucents™ Canopies meet the Class A acceptance criteria of 2021 IBC Section 803.1.1.1 for interior finishes as tested in accordance with NFPA 286.

USG Translucents™ Canopies meet the Class B requirements for flame spread and smoke developed as tested in accordance with CAN/ULC S102 surface-burning characteristics.

Seismic applications

For installations on projects designated seismic design category C-F, suspension wires that are a minimum of no. 12 gauge galvanized, soft-annealed, mild steel wire shall be used. Please refer to SC2494 for more information about the seismic guidelines for specialty and decorative ceilings. Because codes continue to evolve, check with a local official prior to designing and installing a ceiling system. Other restrictions and exemptions may apply.

Limitation

This product is produced to order and will vary from batch-to-batch — panels ordered at the same time will be produced together and will be identical. USG cannot guarantee batch-to-batch consistency.

Note: Rain (Acrylic) is class C

1. Custom colors available by mixing up to 3 films.

Notice

The information in this document is subject to change without notice. CGC Inc. or USG Corp. assumes no responsibility for any errors that may inadvertently appear in this document.

IC596/rev. 5-24

© 2024 USG Corporation and/or its affiliates. All rights reserved. Printed in U.S.A.

Manufactured by
 USG Interiors, LLC
 550 West Adams Street
 Chicago, IL 60661

The trademarks USG, CGC, TRANSLUCENTS, IT'S YOUR WORLD. BUILD IT., the USG/CGC logo, the design elements and colors, and related marks are trademarks of USG Corporation or its affiliates.

Safety First! Follow good safety/industrial hygiene practices during installation. Wear appropriate personal protective equipment. Read SDS and literature before specification and installation.

