

# USG UMBRAL™ DIRECT MOUNT PANELS



USG Umbral™ Direct Mount Panels  
Rendering  
©USG Corporation 2023.  
All rights reserved.

TO ORDER SAMPLES, GO TO [USG.COM](https://www.usg.com) OR [CGCINC.COM](https://www.cgcinc.com)

#### STANDARD COLORS



#### CUSTOM COLOR



panels  
can be  
field  
painted

#### FEATURES AND BENEFITS

- Acoustically absorbent panels that blend in or stand out as desired.
- Easy to install directly to deck using hat channel and fasteners.
- Can be installed in addition to other specialty ceilings as a backdrop or alone as an acoustic treatment for open plenum design.
- ClimaPlus™ 30-year limited system warranty against visible sag, mold and mildew.

#### APPLICATIONS

- Offices and Conference Rooms
- Education
- Auditoriums
- Retrofits
- Restaurants and Hospitality
- Retail Spaces

#### SUBSTRATE

- Wet-formed Mineral Fiber

Fine-Textured Panel


# USG UMBRAL™ DIRECT MOUNT PANELS

CLIMAPLUS™ PERFORMANCE

ORDER SAMPLES/LITERATURE  
USG: usg.com or samplitt@usg.com  
CGC: contact Sales Representative

TECHNICAL SERVICES  
800.USG.4YOU (874-4968)

FOR MOST UP-TO-DATE  
TECHNICAL INFORMATION  
AND LEED REPORT TOOL  
usgdesignstudio.com  
cgcdesignstudio.com  
usg.ecomedes.com




Edge	Panel Size	Mounting	Fire Rating	Item No.	NRC <sup>4,6</sup>	LR <sup>2</sup>	Color	Anti-Mold & Mildew/Sag Resistance	Recycled Content <sup>1</sup>
SQ	2'x4'x3/4"	HC	Class A	22566.50	0.75	0.90	Flat White		69%
	2'x4'x3/4"	HC	Class A	22566.205	0.75	—	Flat Black		69%
	2'x4'x3/4"	HC	Class A	22566.99	0.75	—	Field Finish		69%

**ClimaPlus™ Warranty Performance<sup>3</sup>**  
Contains a broad-spectrum antimicrobial additive on the face and back of the panel that provides resistance against the growth of mold and mildew. Includes sag-resistance performance.

**High Recycled Content**  
USG classifies High Recycled Content as greater than 50%. Total recycled content is based on product composition of pre-consumer (post-industrial) and post-consumer recycled content per FTC guidelines.

## MOUNTING METHOD<sup>5</sup>

### Hat Channel (HC)



## PHYSICAL DATA

### Additional Documents and Resources

Data Sheet: IC307174

### ASTM E1264 Classification

ASTM E1264-22 Type IV, Form 1 & 2, Pattern E & G;  
ASTM E1264-23 Type A, Form A2.1, Pattern E & G

### Fire Classification

ASTM E84 and CAN/ULC S102 surface-burning characteristics Class A  
Flame spread: 25 or less  
Smoke developed: 50 or less

### Weight

1.0 lb/sq. ft.

### Online Tools

usgdesignstudio.com, cgcdesignstudio.com or usg.ecomedes.com

### Thermal Resistance

R-2.2

### Maintenance

Can be cleaned easily with a soft brush or vacuum. To clean panel, use a clean, white cloth with water or a mild detergent and wipe surface.

### Field Painting

Field painting is acceptable with Umbral™. For more detail, please see *USG Umbral™ Installation and Maintenance Guide* (IC307180)

### Installation Considerations

Ensure panels are mechanically fastened to approved surface/substrate. Panels may be installed in any configuration, abutting or spaced, in rows, columns or alone. Use caution and wear appropriate hand and eye protection when installing USG Umbral™ panels. Refer to *USG Umbral™ Installation and Maintenance Guide* (IC307180) for more details. Umbral™ panels are not suitable for pools or exterior applications.

### Notes

- For details, see USG Sustainability tool at usgdesignstudio.com or cgcdesignstudio.com
- LR values are shown as averages. LR values reflect factory painted Flat White. Painting panels other colors will reduce LR values.
- Panel face and back surfaces treated with a proprietary, broad-spectrum antimicrobial additive that inhibits and retards the growth of mold, mildew, and bacteria. For details, see *USG 30-Year Limited System Warranty Commercial Applications* (SC2102).
- Field painting may affect acoustic performance. See *Installation and Maintenance Guide* (IC307180) for more information and guidance.
- Fasteners available with 1/2" face, #2 square drive in Flat White and Flat Black to match factory finish, and in unpainted metal
- NRC values apply to a Type D20 mounting per ASTM E795.

### Notice

The information in this document is subject to change without notice. CGC Inc. or USG Corp. assumes no responsibility for any errors that may inadvertently appear in this document.

IC307174/rev. 7-24  
© 2024 USG Corporation and/or its affiliates. All rights reserved. Printed in USA

Manufactured by USG Interiors, LLC  
550 West Adams Street  
Chicago, IL 60661

The trademarks USG, CGC, CLIMAPLUS, UMBRAL, IT'S YOUR WORLD. BUILD IT., the USG/CGC logo, the design elements and colors, and related marks are trademarks of USG Corporation or its affiliates.

Safety First! Follow good safety/industrial hygiene practices during installation. Wear appropriate personal protective equipment. Read SDS and literature before specification and installation.

