



SAFETY DATA SHEET

1. Identification

Product identifier USG Durock™ Brand EW2™ Primer - Part B

Other means of identification

SDS Number 1400000027

Synonyms Flooring resin.

Recommended use Interior use.

Recommended restrictions Use in accordance with manufacturer's recommendations.

Manufacturer/Importer/Supplier/Distributor information

Company name United States Gypsum Company

Address 550 West Adams Street
Chicago, Illinois 60661-3637

Telephone 1-800-874-4968

Website www.usg.com

Emergency phone number 1-800-424-9300

2. Hazard(s) identification

Physical hazards Not classified.

Health hazards

Acute toxicity, oral	Category 4
Acute toxicity, dermal	Category 4
Skin corrosion/irritation	Category 1B
Serious eye damage/eye irritation	Category 1
Sensitization, skin	Category 1
Reproductive toxicity	Category 2
Specific target organ toxicity, single exposure	Category 3 respiratory tract irritation

Environmental hazards

Hazardous to the aquatic environment, acute hazard	Category 1
Hazardous to the aquatic environment, long-term hazard	Category 1

OSHA defined hazards Not classified.

Label elements



Signal word Danger

Hazard statement Harmful if swallowed or if inhaled. Causes severe skin burns and eye damage. May cause an allergic skin reaction. May cause respiratory irritation. Suspected of damaging fertility or the unborn child. Very toxic to aquatic life with long lasting effects.

Precautionary statement

Prevention Obtain special instructions before use. Do not handle until all safety precautions have been read and understood. Do not breathe mist or vapor. Do not eat, drink or smoke when using this product. Wash thoroughly after handling. Use only outdoors or in a well-ventilated area. Contaminated work clothing must not be allowed out of the workplace. Avoid release to the environment. Wear protective gloves/protective clothing/eye protection/face protection.

Response	If swallowed: Rinse mouth. Do NOT induce vomiting. Call a poison center/doctor if you feel unwell. If on skin (or hair): Take off immediately all contaminated clothing. Rinse skin with water/shower. If inhaled: Remove person to fresh air and keep comfortable for breathing. If in eyes: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. Immediately call a poison center/doctor. If skin irritation or rash occurs: Get medical advice/attention. Wash contaminated clothing before reuse. Collect spillage.
Storage	Store in a well-ventilated place. Keep container tightly closed. Store locked up.
Disposal	Dispose of contents/container in accordance with local/regional/national/international regulations.
Hazard(s) not otherwise classified (HNOC)	None known.
Supplemental information	None.

3. Composition/information on ingredients

Mixtures

Chemical name	CAS number	%
Benzene-1,3-dimethaneamine	1477-55-0	15 - 40
Dolomitic lime	1317-65-3	15 - 40
Nonylphenol	25154-52-3	15 - 40
Titanium dioxide	13463-67-7	10 - 30
2,2'-Iminodi(ethylamine) (deta)	111-40-0	1 - 5

Composition comments All concentrations are in percent by weight unless ingredient is a gas. Gas concentrations are in percent by volume.

4. First-aid measures

Inhalation

Remove victim to fresh air and keep at rest in a position comfortable for breathing. Oxygen or artificial respiration if needed. Induce artificial respiration with the aid of a pocket mask equipped with a one-way valve or other proper respiratory medical device. Call a POISON CENTER or doctor/physician if you feel unwell.

Skin contact

Remove contaminated clothing immediately and wash skin with soap and water. Call a physician or poison control center immediately. Chemical burns must be treated by a physician. Wash contaminated clothing before reuse.

Eye contact

Immediately flush eyes with plenty of water for at least 15 minutes. Remove contact lenses, if present and easy to do. Continue rinsing. Call a physician or poison control center immediately.

Ingestion

Give 3 - 4 glasses of water or milk if person is conscious. Do not induce vomiting. If vomiting occurs, keep head low so that stomach content doesn't get into the lungs.

Most important symptoms/effects, acute and delayed

Burning pain and severe corrosive skin damage. Causes serious eye damage. Symptoms may include stinging, tearing, redness, swelling, and blurred vision. Permanent eye damage including blindness could result. May cause respiratory irritation. May cause an allergic skin reaction. Dermatitis. Rash.

Indication of immediate medical attention and special treatment needed

Provide general supportive measures and treat symptomatically. Chemical burns: Flush with water immediately. While flushing, remove clothes which do not adhere to affected area. Call an ambulance. Continue flushing during transport to hospital. Keep victim under observation. Symptoms may be delayed.

General information

IF exposed or concerned: Get medical advice/attention. If you feel unwell, seek medical advice (show the label where possible). Ensure that medical personnel are aware of the material(s) involved, and take precautions to protect themselves. Show this safety data sheet to the doctor in attendance. Wash contaminated clothing before reuse.

5. Fire-fighting measures

Suitable extinguishing media

Water fog. Dry chemical. Alcohol resistant foam. Carbon dioxide (CO2).

Unsuitable extinguishing media

Do not use water jet as an extinguisher, as this will spread the fire.

Specific hazards arising from the chemical

May generate toxic or irritating combustion products. Sudden reaction and fire may result if product is mixed with an oxidizing agent. During fire, gases hazardous to health may be formed such as: Carbon oxides. Ammonia. Nitrogen oxides. Nitrogen oxides can react with water vapors to form corrosive nitric acid.

Special protective equipment and precautions for firefighters

Self-contained breathing apparatus and full protective clothing must be worn in case of fire.

Fire fighting equipment/instructions

Move containers from fire area if you can do so without risk.

Specific methods

Use standard firefighting procedures and consider the hazards of other involved materials.

General fire hazards

No additional fire or explosion hazards noted.

6. Accidental release measures**Personal precautions, protective equipment and emergency procedures**

Keep unnecessary personnel away. Keep people away from and upwind of spill/leak. Wear appropriate protective equipment and clothing during clean-up. Do not breathe mist or vapor. Do not touch damaged containers or spilled material unless wearing appropriate protective clothing. Ensure adequate ventilation. Local authorities should be advised if significant spillages cannot be contained. For personal protection, see section 8 of the SDS.

Methods and materials for containment and cleaning up

Prevent product from entering drains.

Large Spills: Stop the flow of material, if this is without risk. Dike the spilled material, where this is possible. Absorb in vermiculite, dry sand or earth and place into containers. Following product recovery, flush area with water.

Small Spills: Wipe up with absorbent material (e.g. cloth, fleece). Clean surface thoroughly to remove residual contamination.

Never return spills to original containers for re-use. For waste disposal, see section 13 of the SDS.

Environmental precautions

Avoid release to the environment. Inform appropriate managerial or supervisory personnel of all environmental releases. Prevent further leakage or spillage if safe to do so. Avoid discharge into drains, water courses or onto the ground.

7. Handling and storage**Precautions for safe handling**

Obtain special instructions before use. Do not handle until all safety precautions have been read and understood. Do not breathe mist or vapor. Do not get in eyes, on skin, or on clothing. Avoid prolonged exposure. Pregnant or breastfeeding women must not handle this product. Should be handled in closed systems, if possible. Provide adequate ventilation. Wear appropriate personal protective equipment. Avoid release to the environment. Observe good industrial hygiene practices.

Conditions for safe storage, including any incompatibilities

Store in a cool, dry place with adequate ventilation. Keep away from incompatible materials, open flames, and high temperatures. Store locked up. Store in original tightly closed container. Keep away from acids.

8. Exposure controls/personal protection**Occupational exposure limits****US. OSHA Table Z-1 Limits for Air Contaminants (29 CFR 1910.1000)**

Components	Type	Value	Form
Dolomitic lime (CAS 1317-65-3)	PEL	5 mg/m ³	Respirable fraction.
		15 mg/m ³	Total dust.
Titanium dioxide (CAS 13463-67-7)	PEL	15 mg/m ³	Total dust.

US. ACGIH Threshold Limit Values

Components	Type	Value
2,2'-Iminodi(ethylamine) (deta) (CAS 111-40-0)	TWA	1 ppm
Benzene-1,3-dimethaneamine (CAS 1477-55-0)	Ceiling	0.1 mg/m ³
Titanium dioxide (CAS 13463-67-7)	TWA	10 mg/m ³

US. NIOSH: Pocket Guide to Chemical Hazards

Components	Type	Value	Form
2,2'-Iminodi(ethylamine) (deta) (CAS 111-40-0)	TWA	4 mg/m ³	
		1 ppm	
Benzene-1,3-dimethaneamine (CAS 1477-55-0)	Ceiling	0.1 mg/m ³	

US. NIOSH: Pocket Guide to Chemical Hazards

Components	Type	Value	Form
Dolomitic lime (CAS 1317-65-3)	TWA	5 mg/m ³	Respirable.
		10 mg/m ³	Total

Biological limit values No biological exposure limits noted for the ingredient(s).

Exposure guidelines

US - California OELs: Skin designation

2,2'-Iminodi(ethylamine) (deta) (CAS 111-40-0) Can be absorbed through the skin.
Benzene-1,3-dimethaneamine (CAS 1477-55-0) Can be absorbed through the skin.

US - Minnesota Haz Subs: Skin designation applies

2,2'-Iminodi(ethylamine) (deta) (CAS 111-40-0) Skin designation applies.

US - Tennessee OELs: Skin designation

Benzene-1,3-dimethaneamine (CAS 1477-55-0) Can be absorbed through the skin.

US ACGIH Threshold Limit Values: Skin designation

2,2'-Iminodi(ethylamine) (deta) (CAS 111-40-0) Can be absorbed through the skin.
Benzene-1,3-dimethaneamine (CAS 1477-55-0) Can be absorbed through the skin.

US. NIOSH: Pocket Guide to Chemical Hazards

2,2'-Iminodi(ethylamine) (deta) (CAS 111-40-0) Can be absorbed through the skin.
Benzene-1,3-dimethaneamine (CAS 1477-55-0) Can be absorbed through the skin.

Appropriate engineering controls

Good general ventilation (typically 10 air changes per hour) should be used. Ventilation rates should be matched to conditions. If applicable, use process enclosures, local exhaust ventilation, or other engineering controls to maintain airborne levels below recommended exposure limits. If exposure limits have not been established, maintain airborne levels to an acceptable level. Eye wash facilities and emergency shower must be available when handling this product.

Individual protection measures, such as personal protective equipment

Eye/face protection Wear safety glasses with side shields (or goggles).

Skin protection

Hand protection Nitrile rubber gloves are recommended.

Other Wear appropriate chemical resistant clothing. Use of an impervious apron is recommended.

Respiratory protection Chemical respirator with organic vapor cartridge and full facepiece.

Thermal hazards Wear appropriate thermal protective clothing, when necessary.

General hygiene considerations

Observe any medical surveillance requirements. Always observe good personal hygiene measures, such as washing after handling the material and before eating, drinking, and/or smoking. Routinely wash work clothing and protective equipment to remove contaminants. Contaminated work clothing should not be allowed out of the workplace.

9. Physical and chemical properties

Appearance

Physical state Liquid.

Form Liquid.

Color White.

Odor Ammoniacal.

Odor threshold Not determined.

pH Not established. (alkaline)

Melting point/freezing point 32 °F (0 °C)

Initial boiling point and boiling range 500 °F (260 °C)

Flash point 249.8 °F (121.0 °C) Pensky-Martens Closed Cup

Evaporation rate Not determined.

Flammability (solid, gas) Not applicable.

Upper/lower flammability or explosive limits

Flammability limit - lower (%) Not established.

Flammability limit - upper (%)	Not established.
Explosive limit - lower (%)	Not established.
Explosive limit - upper (%)	Not established.
Vapor pressure	Not determined.
Vapor density	Not determined.
Relative density	1.5 - 1.6
Solubility(ies)	
Solubility (water)	< 1 %
Partition coefficient (n-octanol/water)	1.34
Auto-ignition temperature	Not applicable.
Decomposition temperature	Not applicable.
Viscosity	Not applicable.
Other information	% Solids: 100%
Critical temperature	Not applicable.
Explosive properties	Not explosive.
Oxidizing properties	Not oxidizing.
Partition coefficient (oil/water)	Not determined.
VOC	0 % v/v

10. Stability and reactivity

Reactivity	The product is stable and non-reactive under normal conditions of use, storage and transport.
Chemical stability	Material is stable under normal conditions.
Possibility of hazardous reactions	Hazardous polymerization does not occur.
Conditions to avoid	Contact with incompatible materials. Heat, sparks, flames, elevated temperatures.
Incompatible materials	Oxidizing agents. Acids.
Hazardous decomposition products	No hazardous decomposition products are known.

11. Toxicological information

Information on likely routes of exposure

Inhalation	Harmful if inhaled.
Skin contact	Causes severe skin burns. May cause an allergic skin reaction.
Eye contact	Causes serious eye damage.
Ingestion	Causes digestive tract burns. Harmful if swallowed.

Symptoms related to the physical, chemical and toxicological characteristics Burning pain and severe corrosive skin damage. Causes serious eye damage. Symptoms may include stinging, tearing, redness, swelling, and blurred vision. Permanent eye damage including blindness could result. May cause respiratory irritation. May cause sensitization by skin contact. Dermatitis. Rash.

Information on toxicological effects

Acute toxicity Harmful by inhalation and if swallowed.

Components	Species	Test Results
2,2'-Iminodi(ethylamine) (deta) (CAS 111-40-0)		
Acute		
<i>Dermal</i>		
LD50	Rabbit	550 mg/kg
<i>Oral</i>		
LD50	Rat	1080 mg/kg

Components	Species	Test Results
Benzene-1,3-dimethaneamine (CAS 1477-55-0)		
Acute		
<i>Dermal</i>		
LD50	Rabbit	2000 mg/kg
<i>Inhalation</i>		
LC50	Rat	3.75 mg/l, 1 Hours
<i>Oral</i>		
LD50	Rat	930 mg/kg
Nonylphenol (CAS 25154-52-3)		
Acute		
<i>Dermal</i>		
LD50	Rabbit	2140 mg/kg
<i>Oral</i>		
LD50	Rat	1600 mg/kg
Titanium dioxide (CAS 13463-67-7)		
Acute		
<i>Inhalation</i>		
LC50	Rat	> 2.28 mg/l, 4 Hours
<i>Oral</i>		
LD50	Rat	> 11000 mg/kg

* Estimates for product may be based on additional component data not shown.

Skin corrosion/irritation	Causes severe skin burns and eye damage.
Serious eye damage/eye irritation	Causes serious eye damage.
Respiratory or skin sensitization	
Respiratory sensitization	Not a respiratory sensitizer.
Skin sensitization	May cause an allergic skin reaction.
Germ cell mutagenicity	No data available to indicate product or any components present at greater than 0.1% are mutagenic or genotoxic.
Carcinogenicity	Titanium Dioxide is listed by IARC as possibly carcinogenic to humans (Group 2B). This listing is based on inadequate evidence of carcinogenicity in humans and sufficient evidence in experimental animals.
IARC Monographs. Overall Evaluation of Carcinogenicity	
Not listed.	
NTP Report on Carcinogens	
Not listed.	
OSHA Specifically Regulated Substances (29 CFR 1910.1001-1050)	
Not regulated.	
Reproductive toxicity	Suspected of damaging fertility or the unborn child.
Specific target organ toxicity - single exposure	May cause respiratory irritation.
Specific target organ toxicity - repeated exposure	Not classified.
Aspiration hazard	Not an aspiration hazard.
Chronic effects	Prolonged inhalation may be harmful. Prolonged exposure may cause chronic effects.

12. Ecological information

Ecotoxicity Very toxic to aquatic life with long lasting effects.

Components	Species		Test Results
Nonylphenol (CAS 25154-52-3)			
Aquatic			
Crustacea	EC50	Water flea (Daphnia magna)	0.076 - 0.0946 mg/l, 48 hours
Fish	LC50	Fathead minnow (Pimephales promelas)	0.098 - 0.187 mg/l, 96 hours

* Estimates for product may be based on additional component data not shown.

Persistence and degradability No data is available on the degradability of this product.

Bioaccumulative potential

Partition coefficient n-octanol / water (log Kow)

USG Durock™ Brand EW2™ Primer - Part B 1.34

Mobility in soil No data available.

Other adverse effects No other adverse environmental effects (e.g. ozone depletion, photochemical ozone creation potential, endocrine disruption, global warming potential) are expected from this component.

13. Disposal considerations

Disposal instructions Dispose in accordance with applicable federal, state, and local regulations. Recycle responsibly.

Local disposal regulations Dispose of in accordance with local regulations.

Hazardous waste code Not regulated.

Waste from residues / unused products Dispose of in accordance with local regulations.

Contaminated packaging Dispose of in accordance with local regulations.

14. Transport information

DOT

UN number UN2735
UN proper shipping name Amines, liquid, corrosive, n.o.s (benzene-1,3-dimethaneamine)
Transport hazard class(es)
Class 8
Subsidiary risk -
Label(s) 8
Packing group II
Environmental hazards
Marine pollutant Yes
Special precautions for user Read safety instructions, SDS and emergency procedures before handling.
Special provisions B2, IB2, T11, TP1, TP27
Packaging exceptions 154
Packaging non bulk 202
Packaging bulk 242

IATA

UN number UN2735
UN proper shipping name Amines, liquid, corrosive, n.o.s. (benzene-1,3-dimethaneamine)
Transport hazard class(es)
Class 8
Subsidiary risk -
Packing group II
Environmental hazards No.
ERG Code 8L
Special precautions for user Read safety instructions, SDS and emergency procedures before handling.

IMDG

UN number UN2735
UN proper shipping name AMINES, LIQUID, CORROSIVE, N.O.S. (BENZENE-1,3-DIMETHANEAMINE)
Transport hazard class(es)
Class 8
Subsidiary risk -
Packing group II
Environmental hazards
Marine pollutant Yes

EmS F-A, S-B

Special precautions for user Read safety instructions, SDS and emergency procedures before handling.

Nonylphenol

Transport in bulk according to Annex II of MARPOL 73/78 and the IBC Code Not established.

15. Regulatory information

US federal regulations This product is a "Hazardous Chemical" as defined by the OSHA Hazard Communication Standard, 29 CFR 1910.1200.

All components of this product are in compliance with the listing Requirements of the U.S. Toxic Substances Control Act (TSCA) Chemical Substance Inventory.

TSCA Section 12(b) Export Notification (40 CFR 707, Subpt. D)

Nonylphenol (CAS 25154-52-3) 1.0 % One-Time Export Notification only.

OSHA Specifically Regulated Substances (29 CFR 1910.1001-1050)

Not regulated.

CERCLA Hazardous Substance List (40 CFR 302.4)

Not listed.

Superfund Amendments and Reauthorization Act of 1986 (SARA)

Hazard categories Immediate Hazard - Yes
Delayed Hazard - Yes
Fire Hazard - No
Pressure Hazard - No
Reactivity Hazard - No

SARA 302 Extremely hazardous substance

Not listed.

SARA 311/312 Hazardous chemical Yes

SARA 313 (TRI reporting)

Chemical name	CAS number	% by wt.
Nonylphenol	25154-52-3	15 - 40

Other federal regulations

Clean Air Act (CAA) Section 112 Hazardous Air Pollutants (HAPs) List

Not regulated.

Clean Air Act (CAA) Section 112(r) Accidental Release Prevention (40 CFR 68.130)

Not regulated.

Safe Drinking Water Act (SDWA) Not regulated.

US state regulations

US. Massachusetts RTK - Substance List

2,2'-Iminodi(ethylamine) (deta) (CAS 111-40-0)
Benzene-1,3-dimethaneamine (CAS 1477-55-0)
Dolomitic lime (CAS 1317-65-3)
Nonylphenol (CAS 25154-52-3)
Titanium dioxide (CAS 13463-67-7)

US. New Jersey Worker and Community Right-to-Know Act

2,2'-Iminodi(ethylamine) (deta) (CAS 111-40-0)
Benzene-1,3-dimethaneamine (CAS 1477-55-0)
Dolomitic lime (CAS 1317-65-3)
Titanium dioxide (CAS 13463-67-7)

US. Pennsylvania Worker and Community Right-to-Know Law

2,2'-Iminodi(ethylamine) (deta) (CAS 111-40-0)
Benzene-1,3-dimethaneamine (CAS 1477-55-0)
Dolomitic lime (CAS 1317-65-3)
Nonylphenol (CAS 25154-52-3)
Titanium dioxide (CAS 13463-67-7)

US. Rhode Island RTK

Not regulated.


US. California Proposition 65

WARNING: This product contains a chemical known to the State of California to cause cancer.

US - California Proposition 65 - Carcinogens & Reproductive Toxicity (CRT): Listed substance

Titanium dioxide (CAS 13463-67-7)

16. Other information, including date of preparation or last revision

Issue date	14-July-2016
Revision date	-
Version #	01
Further information	<p>Titanium dioxide: Raw materials and/or coatings in this product contain small amounts of titanium dioxide. The International Agency for Research on Cancer (IARC) has determined that titanium dioxide is possibly carcinogenic to humans (Group 2B) based on inadequate evidence in humans and sufficient evidence in experimental animals. This conclusion relates to long-term inhalation exposure to high concentrations of pigmentary (powdered) or ultrafine titanium dioxide. However, no significant exposure to primary particles of titanium dioxide is thought to occur during the use of products in which titanium dioxide is bound to other materials, such as in paints. The available human studies do not suggest an association between occupational exposure to titanium dioxide and risk for cancer (1). The American Conference of Governmental Industrial Hygienists (ACGIH) has designated this chemical as not classifiable as a human carcinogen (A4). The US National Toxicology Program (NTP) has not listed this chemical in its report on carcinogens.</p> <p>NFPA Ratings: Health: 3 Flammability: 1 Physical hazard: 1 Hazard Scale: 0 = Minimal 1 = Slight 2 = Moderate 3 = Serious 4 = Severe</p>
NFPA ratings	
References	<p>1.) International Agency for Research on Cancer (IARC). Volume 93: Carbon Black, Titanium Dioxide, and Talc; (5. Summary of data reported). IARC, 2010. Available at: <http://monographs.iarc.fr/ENG/Monographs/vol93/mono93.pdf></p>
Disclaimer	<p>This information is provided without warranty. The information is believed to be correct. This information should be used to make an independent determination of the methods to safeguard workers and the environment.</p>