




# SAFETY DATA SHEET

## 1. Identification

<b>Product identifier</b>	<b>Hydro-Stone® Gypsum Cements</b>
<b>Other means of identification</b>	
<b>SDS number</b>	52000000012
<b>Additional Products</b>	Hydro-Stone® TB Gypsum Cement, Hydro-Stone® LF, Hydro-Stone® DL, Hydro-Stone® HD Cement, Hydro-Stone® SDCT, Hydro-Stone® Super Fast Set, Hydro-Stone® ME Special Gypsum Cement, Hydro-Stone® DL Plus Smoke
<b>Synonyms</b>	Statuary
<b>Recommended use</b>	Statuary or anchoring cement.
<b>Recommended restrictions</b>	Use in accordance with manufacturer's recommendations.
<b>Manufacturer/Importer/Supplier/Distributor information</b>	
<b>Company name</b>	United States Gypsum Company
<b>Address</b>	550 West Adams Street Chicago, Illinois 60661-3637
<b>Telephone</b>	1-800-874-4968
<b>Website</b>	www.usg.com
<b>Emergency phone number</b>	1-800-507-8899

## 2. Hazard(s) identification

<b>Physical hazards</b>	Not classified.	
<b>Health hazards</b>	Skin corrosion/irritation	Category 2
	Serious eye damage/eye irritation	Category 1
	Sensitization, skin	Category 1
	Carcinogenicity	Category 1A
<b>OSHA defined hazards</b>	Not classified.	
<b>Label elements</b>		

<b>Signal word</b>	Danger
<b>Hazard statement</b>	Causes skin irritation. May cause an allergic skin reaction. Causes serious eye damage. May cause cancer.
<b>Precautionary statement</b>	
<b>Prevention</b>	Obtain special instructions before use. Do not handle until all safety precautions have been read and understood. Avoid breathing dust. Wash thoroughly after handling. Contaminated work clothing must not be allowed out of the workplace. Wear protective gloves/protective clothing/eye protection/face protection.
<b>Response</b>	If on skin: Wash with plenty of water. If in eyes: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. Immediately call a poison center/doctor. If skin irritation or rash occurs: Get medical advice/attention. Take off contaminated clothing and wash before reuse.
<b>Storage</b>	Store locked up.
<b>Disposal</b>	Dispose of contents/container in accordance with local/regional/national/international regulations.
<b>Hazard(s) not otherwise classified (HNOC)</b>	None known.
<b>Supplemental information</b>	None.

### 3. Composition/information on ingredients

#### Mixtures

Chemical name	CAS number	%
Plaster of Paris (Calcium Sulfate Hemihydrate CAS 10034-76-1)	26499-65-0	> 95
Portland Cement	65997-15-1	< 5
Titanium dioxide	13463-67-7	< 0.5

#### Impurities

Chemical name	CAS number	%
Crystalline silica (Quartz)	14808-60-7	< 0.90

#### Composition comments

All concentrations are in percent by weight.

Raw materials in this product contain respirable crystalline silica as an impurity. The weight percent of respirable crystalline silica found in this product is < 0.90%. Exposures to respirable crystalline silica during the normal use of this product must be determined by workplace hygiene testing.

### 4. First-aid measures

#### Inhalation

Dust irritates the respiratory system, and may cause coughing and difficulties in breathing. Move injured person into fresh air and keep person calm under observation. Get medical attention if symptoms persist.

#### Skin contact

Contact with wet or dry product: Wash area with cold running water immediately. Open sores or cuts should be thoroughly flushed and covered with suitable dressings.

#### Eye contact

Dust in the eyes: Do not rub eyes. Flush thoroughly with water. If irritation occurs, get medical assistance.

#### Ingestion

Plaster of Paris hardens and if ingested may result in stomach and intestinal blockage. Drinking gelatin solutions or large volumes of water may delay setting.

#### Most important symptoms/effects, acute and delayed

Dust may irritate throat and respiratory system and cause coughing. May cause serious chemical burns to the skin. May cause chemical eye burns. Permanent eye damage including blindness could result.

#### Indication of immediate medical attention and special treatment needed

Provide general supportive measures and treat symptomatically.

#### General information

Ensure that medical personnel are aware of the material(s) involved.

### 5. Fire-fighting measures

#### Suitable extinguishing media

Use fire-extinguishing media appropriate for surrounding materials.

#### Unsuitable extinguishing media

Not applicable.

#### Specific hazards arising from the chemical

Not a fire hazard.

#### Special protective equipment and precautions for firefighters

Selection of respiratory protection for firefighting: follow the general fire precautions indicated in the workplace. Self-contained breathing apparatus and full protective clothing must be worn in case of fire.

#### Fire fighting equipment/instructions

Use standard firefighting procedures and consider the hazards of other involved materials.

#### Specific methods

Cool material exposed to heat with water spray and remove it if no risk is involved.

### 6. Accidental release measures

#### Personal precautions, protective equipment and emergency procedures

See Section 8 of the SDS for Personal Protective Equipment.

#### Methods and materials for containment and cleaning up

Vacuum up the spilled material. Vacuums used for this purpose should be equipped with HEPA filters. Containers must be labeled. Collect in approved containers and seal securely. For waste disposal, see Section 13 of the SDS.

#### Environmental precautions

Avoid discharge to drains, sewers, and other water systems.

## 7. Handling and storage

### Precautions for safe handling

Do not get in eyes and avoid contact with skin and clothing. Wear appropriate personal protective equipment (See Section 8). Avoid inhalation of dust. Minimize dust production when mixing, or opening and closing bags. Use with adequate dust control and local ventilation. Wear appropriate NIOSH respirator when ventilation is inadequate and occupational exposure limits are exceeded. Wash hands thoroughly after handling. Use a non-alkaline soap such as Neutralite Safety Solution or Mason's Hand Rinse.

### Conditions for safe storage, including any incompatibilities

Store in a cool, dry, well-ventilated place. Store away from incompatible materials. Avoid contact with acids, water, and moisture.

## 8. Exposure controls/personal protection

### Occupational exposure limits

#### US. OSHA Specifically Regulated Substances (29 CFR 1910.1001-1053)

Impurities	Type	Value
Crystalline silica (Quartz) (CAS 14808-60-7)	TWA	0.05 mg/m <sup>3</sup>

#### US. OSHA Table Z-1 Limits for Air Contaminants (29 CFR 1910.1000)

Components	Type	Value	Form
Plaster of Paris (Calcium Sulfate Hemihydrate CAS 10034-76-1) (CAS 26499-65-0)	PEL	5 mg/m <sup>3</sup>	Respirable fraction.
Portland Cement (CAS 65997-15-1)	PEL	15 mg/m <sup>3</sup>	Total dust.
		5 mg/m <sup>3</sup>	Respirable fraction.
Titanium dioxide (CAS 13463-67-7)	PEL	15 mg/m <sup>3</sup>	Total dust.
		15 mg/m <sup>3</sup>	Total dust.

#### US. OSHA Table Z-3 (29 CFR 1910.1000)

Components	Type	Value	Form
Portland Cement (CAS 65997-15-1)	TWA	50 mppcf	
Titanium dioxide (CAS 13463-67-7)	TWA	5 mg/m <sup>3</sup>	Respirable fraction.
		15 mg/m <sup>3</sup>	Total dust.
		50 mppcf	Total dust.
Impurities	Type	15 mppcf	Respirable fraction.
		0.1 mg/m <sup>3</sup>	Respirable.
		2.4 mppcf	Respirable.

#### US. ACGIH Threshold Limit Values

Components	Type	Value	Form
Plaster of Paris (Calcium Sulfate Hemihydrate CAS 10034-76-1) (CAS 26499-65-0)	TWA	10 mg/m <sup>3</sup>	Inhalable fraction.
Portland Cement (CAS 65997-15-1)	TWA	1 mg/m <sup>3</sup>	Respirable fraction.
Titanium dioxide (CAS 13463-67-7)	TWA	10 mg/m <sup>3</sup>	

Impurities	Type	Value	Form
Crystalline silica (Quartz) (CAS 14808-60-7)	TWA	0.025 mg/m <sup>3</sup>	Respirable fraction.

#### US. NIOSH: Pocket Guide to Chemical Hazards

Components	Type	Value	Form
Plaster of Paris (Calcium Sulfate Hemihydrate CAS 10034-76-1) (CAS 26499-65-0)	TWA	5 mg/m <sup>3</sup>	Respirable.

**US. NIOSH: Pocket Guide to Chemical Hazards**

Components	Type	Value	Form
Portland Cement (CAS 65997-15-1)	TWA	10 mg/m3 5 mg/m3	Total Respirable.
Impurities	Type	Value	Form
Crystalline silica (Quartz) (CAS 14808-60-7)	TWA	0.05 mg/m3	Respirable dust.

<b>Biological limit values</b>	No biological exposure limits noted for the ingredient(s).
<b>Appropriate engineering controls</b>	Provide sufficient ventilation for operations causing dust formation. Observe occupational exposure limits and minimize the risk of exposure.
<b>Individual protection measures, such as personal protective equipment</b>	
<b>Eye/face protection</b>	Wear approved safety goggles.
<b>Skin protection</b>	
<b>Hand protection</b>	Wear appropriate chemical resistant gloves.
<b>Skin protection</b>	
<b>Other</b>	Normal work clothing (long sleeved shirts and long pants) is recommended.
<b>Respiratory protection</b>	If engineering controls do not maintain airborne concentrations below recommended exposure limits (where applicable) or to an acceptable level (in countries where exposure limits have not been established), an approved respirator must be worn. Use a NIOSH/MSHA approved air purifying respirator as needed to control exposure. Consult with respirator manufacturer to determine respirator selection, use, and limitations. Use positive pressure, air-supplied respirator for uncontrolled releases or when air purifying respirator limitations may be exceeded. Follow respirator protection program requirements (OSHA 1910.134 and ANSI Z88.2) for all respirator use.
<b>Thermal hazards</b>	None.
<b>General hygiene considerations</b>	During work avoid kneeling in fresh mortar or concrete wherever possible. If kneeling is absolutely necessary, then appropriate waterproof personal protective equipment must be worn. Do not eat, drink or smoke when working with cement to avoid contact with skin or mouth. Immediately after working with cement or cement-containing materials, workers should wash or shower. Remove contaminated clothing, footwear, watches, etc, and clean thoroughly before re-use. Observe any medical surveillance requirements.

**9. Physical and chemical properties****Appearance**

<b>Physical state</b>	Solid.
<b>Form</b>	Powder.
<b>Color</b>	White to off-white.

**Odor** Low to no odor.

**Odor threshold** Not applicable.

**pH** 6 - 12

**Melting point/freezing point** Not applicable.  
Not applicable.

**Initial boiling point and boiling range** Not applicable.

**Flash point** Not applicable.

**Evaporation rate** Not applicable.

**Flammability (solid, gas)** Not applicable.

**Upper/lower flammability or explosive limits**

**Flammability limit - lower (%)** Not applicable.

**Flammability limit - upper (%)** Not applicable.

**Explosive limit - lower (%)** Not applicable.

**Explosive limit - upper (%)** Not applicable.

<b>Vapor pressure</b>	Not applicable.
<b>Vapor density</b>	Not applicable.
<b>Relative density</b>	2.96 (H <sub>2</sub> O=1)
<b>Solubility(ies)</b>	
<b>Solubility (water)</b>	0.15 - 0.4 g/100 g (H <sub>2</sub> O)
<b>Partition coefficient (n-octanol/water)</b>	Not applicable.
<b>Auto-ignition temperature</b>	Not applicable.
<b>Decomposition temperature</b>	2642 °F (1450 °C)
<b>Viscosity</b>	Not applicable.
<b>Other information</b>	
<b>Bulk density</b>	55 - 70 lb/ft <sup>3</sup>
<b>Particle size</b>	Varies.
<b>VOC</b>	0 %

## 10. Stability and reactivity

<b>Reactivity</b>	The product is stable and non-reactive under normal conditions of use, storage and transport.
<b>Chemical stability</b>	Material is stable under normal conditions.
<b>Possibility of hazardous reactions</b>	Hazardous polymerization does not occur.
<b>Conditions to avoid</b>	Contact with incompatible materials. Exposure to moisture. When mixed with water this product can become very hot. Encasing or making moulds of any body part can cause serious burns that may require surgical removal of affected tissue and even amputation of encased body part.
<b>Incompatible materials</b>	Acids. Exposure to water and acids must be supervised because the reactions are vigorous and produce large amounts of heat.
<b>Hazardous decomposition products</b>	Calcium oxides. Sulfur oxides.

## 11. Toxicological information

### Information on likely routes of exposure

<b>Inhalation</b>	Inhalation of dusts may cause respiratory irritation. Prolonged and repeated exposure to airborne respirable crystalline silica can cause silicosis and/or lung cancer.
<b>Skin contact</b>	Exposure to dry product may cause drying of the skin and mild irritation, or more significant effects from the aggravation of other conditions. Wet product is caustic (pH ≥ 12) and dermal exposure may cause more severe skin effects, including thickening, cracking or fissuring of the skin. Prolonged exposure can cause severe skin damage in the form of chemical (caustic) burns. Some individuals who are exposed to wet or dry product may exhibit an allergic response, which can result in symptoms ranging from mild rashes to severe skin ulcers.
<b>Eye contact</b>	Exposure to airborne dust may cause immediate or delayed irritation of the eyes. Depending on the level of exposure, effects may range from redness to chemical burns and blindness.
<b>Ingestion</b>	Ingestion may cause irritation and stomach discomfort.
<b>Symptoms related to the physical, chemical and toxicological characteristics</b>	Dust may irritate eyes and mucous membranes of the nose, throat and upper respiratory system causing sneezing and/or coughing. May cause serious chemical burns to the skin. May cause chemical eye burns. Permanent eye damage including blindness could result.

### Information on toxicological effects

**Acute toxicity** Not expected to be a hazard under normal conditions of intended use.

<b>Components</b>	<b>Species</b>	<b>Test Results</b>
Titanium dioxide (CAS 13463-67-7)		
<b>Acute</b>		
<b>Inhalation</b>		
LC50	Rat	3.43 mg/l, 4 Hours
<b>Oral</b>		
LD50	Rat	> 5000 mg/kg

\* Estimates for product may be based on additional component data not shown.

**Skin corrosion/irritation** Causes skin irritation.

<b>Serious eye damage/eye irritation</b>	Causes severe eye damage.
<b>Respiratory or skin sensitization</b>	
<b>Respiratory sensitization</b>	Not classified but possible due to skin sensitization effect.
<b>Skin sensitization</b>	Trace amounts of Cr(VI) compounds from Portland Cement may cause allergic skin reaction even after one exposure.
<b>Germ cell mutagenicity</b>	No data available to indicate product or any components present at greater than 0.1% are mutagenic or genotoxic.
<b>Carcinogenicity</b>	Repeated and prolonged exposures to high levels of respirable crystalline silica may cause cancer.

Titanium Dioxide is listed by IARC as possibly carcinogenic to humans (Group 2B). This listing is based on inadequate evidence of carcinogenicity in humans and sufficient evidence in experimental animals.

#### **IARC Monographs. Overall Evaluation of Carcinogenicity**

Crystalline silica (Quartz) (CAS 14808-60-7)	1 Carcinogenic to humans.
Titanium dioxide (CAS 13463-67-7)	2B Possibly carcinogenic to humans.

#### **NTP Report on Carcinogens**

Crystalline silica (Quartz) (CAS 14808-60-7)	Known To Be Human Carcinogen.
--	-------------------------------

#### **OSHA Specifically Regulated Substances (29 CFR 1910.1001-1053)**

Crystalline silica (Quartz) (CAS 14808-60-7)	Cancer
--	--------

<b>Reproductive toxicity</b>	Not expected to be a reproductive hazard.
<b>Specific target organ toxicity - single exposure</b>	No data available, but none expected.
<b>Specific target organ toxicity - repeated exposure</b>	No data available, but none expected.
<b>Aspiration hazard</b>	Due to the physical form of the product it is not an aspiration hazard.
<b>Chronic effects</b>	Some individuals may exhibit eczema upon exposure to wet cement. The response may appear in a variety of forms ranging from a mild rash to severe dermatitis.  Prolonged and routine inhalation of high levels of respirable crystalline silica particles can lead to the lung disease known as silicosis. Some studies show excess numbers of cases of scleroderma, connective tissue disorders, lupus, rheumatoid arthritis, chronic kidney diseases and end-stage kidney disease in workers exposed to respirable crystalline silica. Occupational exposure to respirable dust and respirable crystalline silica should be monitored and controlled.

## **12. Ecological information**

<b>Ecotoxicity</b>	This product is not expected to produce significant ecotoxicity upon exposure to aquatic organisms and aquatic systems. Large amounts of the product may affect the pH-factor in water with possible risk of harmful effects to aquatic organisms.
<b>Persistence and degradability</b>	Calcium sulfate dissolves in water forming calcium and sulfate ions.
<b>Bioaccumulative potential</b>	Bioaccumulation is not expected.
<b>Mobility in soil</b>	No data available.
<b>Other adverse effects</b>	None expected.

## **13. Disposal considerations**

<b>Disposal instructions</b>	Dispose in accordance with applicable federal, state, and local regulations. Recycle responsibly.
<b>Local disposal regulations</b>	Dispose of in accordance with local regulations.
<b>Hazardous waste code</b>	Not regulated.
<b>Waste from residues / unused products</b>	Dispose of in accordance with local regulations.
<b>Contaminated packaging</b>	Dispose of in accordance with local regulations.

## **14. Transport information**

<b>DOT</b>	Not regulated as dangerous goods.
<b>IATA</b>	Not regulated as dangerous goods.

## IMDG

Not regulated as dangerous goods.

**Transport in bulk according to Annex II of MARPOL 73/78 and the IBC Code** Not applicable. This product is a solid. Therefore, bulk transport is governed by IMSBC code.

## 15. Regulatory information

**US federal regulations** This product is a "Hazardous Chemical" as defined by the OSHA Hazard Communication Standard 29 CFR 1910.1200 (OSHA) and 8 CCR § 5194 (Cal/OSHA).

### TSCA Section 12(b) Export Notification (40 CFR 707, Subpt. D)

Not regulated.

### CERCLA Hazardous Substance List (40 CFR 302.4)

Not listed.

### SARA 304 Emergency release notification

Not regulated.

### OSHA Specifically Regulated Substances (29 CFR 1910.1001-1053)

Crystalline silica (Quartz) (CAS 14808-60-7)	Cancer lung effects immune system effects kidney effects
--	---

## Superfund Amendments and Reauthorization Act of 1986 (SARA)

### SARA 302 Extremely hazardous substance

Not listed.

**SARA 311/312 Hazardous chemical** Yes

### SARA 313 (TRI reporting)

Not regulated.

## Other federal regulations

### Clean Air Act (CAA) Section 112 Hazardous Air Pollutants (HAPs) List

Not regulated.

### Clean Air Act (CAA) Section 112(r) Accidental Release Prevention (40 CFR 68.130)

Not regulated.

**Safe Drinking Water Act (SDWA)** Not regulated.

**US state regulations** WARNING: This product contains a chemical known to the State of California to cause cancer.

### US. Massachusetts RTK - Substance List

Crystalline silica (Quartz) (CAS 14808-60-7)  
Plaster of Paris (Calcium Sulfate Hemihydrate CAS 10034-76-1) (CAS 26499-65-0)  
Portland Cement (CAS 65997-15-1)  
Titanium dioxide (CAS 13463-67-7)

### US. New Jersey Worker and Community Right-to-Know Act

Crystalline silica (Quartz) (CAS 14808-60-7)  
Plaster of Paris (Calcium Sulfate Hemihydrate CAS 10034-76-1) (CAS 26499-65-0)  
Portland Cement (CAS 65997-15-1)  
Titanium dioxide (CAS 13463-67-7)

### US. Pennsylvania Worker and Community Right-to-Know Law

Crystalline silica (Quartz) (CAS 14808-60-7)  
Plaster of Paris (Calcium Sulfate Hemihydrate CAS 10034-76-1) (CAS 26499-65-0)  
Portland Cement (CAS 65997-15-1)  
Titanium dioxide (CAS 13463-67-7)

### US. Rhode Island RTK

Crystalline silica (Quartz) (CAS 14808-60-7)  
Portland Cement (CAS 65997-15-1)  
Titanium dioxide (CAS 13463-67-7)

## California Proposition 65

### California Proposition 65 - CRT: Listed date/Carcinogenic substance

Crystalline silica (Quartz) (CAS 14808-60-7) Listed: October 1, 1988  
Titanium dioxide (CAS 13463-67-7) Listed: September 2, 2011

### US. California. Candidate Chemicals List. Safer Consumer Products Regulations (Cal. Code Regs, tit. 22, 69502.3, subd. (a))

Crystalline silica (Quartz) (CAS 14808-60-7)  
Titanium dioxide (CAS 13463-67-7)

## International Inventories

Country(s) or region	Inventory name	On inventory (yes/no)*
United States & Puerto Rico	Toxic Substances Control Act (TSCA) Inventory	Yes

\*A "Yes" indicates this product complies with the inventory requirements administered by the governing country(s).

A "No" indicates that one or more components of the product are not listed or exempt from listing on the inventory administered by the governing country(s).

## 16. Other information, including date of preparation or last revision

Issue date 16-November-2017

Revision date -

Version # 01

**Further information** Crystalline silica: Raw materials in this product may contain respirable crystalline silica. Exposures to respirable crystalline silica are not expected during the normal use of this product. However, actual levels must be determined by workplace hygiene testing. Prolonged and repeated exposure to airborne free respirable crystalline silica can result in lung disease (i.e., silicosis) and/or lung cancer.

Plaster of Paris: Is classified as a hazardous substance but is generally considered a safe material for routine use. When plaster of Paris is used responsibly it is not considered as a dangerous material. However, when mixed with water this product can become very hot. DO NOT attempt to make a cast enclosing any part of the body. Encasing any body part can cause serious burns and even amputation of the encased body part.

Titanium dioxide: This product may contain titanium dioxide. The International Agency for Research on Cancer (IARC) has determined that titanium dioxide is possibly carcinogenic to humans (Group 2B) based on inadequate evidence in humans and sufficient evidence in experimental animals. This conclusion relates to long-term inhalation exposure to high concentrations of pigmentary (powdered) or ultrafine titanium dioxide. However, no significant exposure to primary particles of titanium dioxide is thought to occur during the use of products in which titanium dioxide is bound to other materials, such as in paints. The available human studies do not suggest an association between occupational exposure to titanium dioxide and risk for cancer (1). The American Conference of Governmental Industrial Hygienists (ACGIH) has designated this chemical as not classifiable as a human carcinogen (A4). The US National Toxicology Program (NTP) has not listed this chemical in its report on carcinogens.

OSHA's "Preventing Skin Problems from Working with Portland Cement" provides excellent guidance and can be downloaded at: <https://www.osha.gov/dsg/guidance/cement-guidance.html>

NFPA Ratings:  
Health: 2  
Flammability: 0  
Physical hazard: 0

Hazard Scale: 0 = Minimal 1 = Slight 2 = Moderate 3 = Serious 4 = Severe

## NFPA ratings



## Disclaimer

This information is provided without warranty. The information is believed to be correct. This information should be used to make an independent determination of the methods to safeguard workers and the environment.