



SAFETY DATA SHEET

1. Identification

Product identifier	Industrial Ground Gypsum
Other means of identification	
SDS number	52000000106
Synonyms	Gypsum
Recommended use	General Purpose Filler.
Recommended restrictions	Use in accordance with manufacturer's recommendations.
Manufacturer/Importer/Supplier/Distributor information	
Company name	United States Gypsum Company
Address	550 West Adams Street Chicago, Illinois 60661-3637
Telephone	1-800-874-4968
Website	www.usg.com
Emergency phone number	1-800-507-8899

2. Hazard(s) identification

Physical hazards	Not classified.	
Health hazards	Carcinogenicity (inhalation)	Category 1A
OSHA defined hazards	Not classified.	
Label elements		



Signal word	Danger	
Hazard statement	May cause cancer by inhalation.	
Precautionary statement		
Prevention	Obtain special instructions before use. Do not handle until all safety precautions have been read and understood. Avoid breathing dust. Wear protective gloves/protective clothing/eye protection/face protection.	
Response	If exposed or concerned: Get medical advice/attention.	
Storage	Store locked up.	
Disposal	Dispose of contents/container in accordance with local/regional/national/international regulations.	
Hazard(s) not otherwise classified (HNOC)	None known.	
Supplemental information	None.	

3. Composition/information on ingredients

Mixtures

Chemical name	CAS number	%
Calcium sulfate dihydrate (alternative CAS 10101-41-4)	13397-24-5	> 95

Impurities

Chemical name	Common name and synonyms	CAS number	%
Crystalline silica (Quartz)		14808-60-7	< 1.0

Composition comments

All concentrations are in percent by weight.

Raw materials in this product contain respirable crystalline silica as an impurity. The weight percent of respirable crystalline silica found in this product is < 1.0%. Exposures to respirable crystalline silica during the normal use of this product must be determined by workplace hygiene testing.

4. First-aid measures

Inhalation

Dust irritates the respiratory system, and may cause coughing and difficulties in breathing. Move injured person into fresh air and keep person calm under observation. Get medical attention if symptoms persist.

Skin contact

Contact with dust: Rinse area with plenty of water. Get medical attention if irritation develops or persists.

Eye contact

Dust in the eyes: Do not rub eyes. Flush thoroughly with water. If irritation occurs, get medical assistance.

Ingestion

Rinse mouth. Get medical attention if symptoms occur.

Most important symptoms/effects, acute and delayed

Dust may irritate eyes and mucous membranes of the nose, throat and upper respiratory system causing sneezing and/or coughing. Prolonged exposure may cause chronic effects.

Indication of immediate medical attention and special treatment needed

Provide general supportive measures and treat symptomatically.

General information

Ensure that medical personnel are aware of the material(s) involved.

5. Fire-fighting measures

Suitable extinguishing media

Use fire-extinguishing media appropriate for surrounding materials.

Unsuitable extinguishing media

Not applicable.

Specific hazards arising from the chemical

Not a fire hazard.

Special protective equipment and precautions for firefighters

Selection of respiratory protection for firefighting: follow the general fire precautions indicated in the workplace. Self-contained breathing apparatus and full protective clothing must be worn in case of fire.

Fire fighting equipment/instructions

Use standard firefighting procedures and consider the hazards of other involved materials.

Specific methods

Cool material exposed to heat with water spray and remove it if no risk is involved.

General fire hazards

No unusual fire or explosion hazards noted.

6. Accidental release measures

Personal precautions, protective equipment and emergency procedures

See Section 8 of the SDS for Personal Protective Equipment. Use a NIOSH/MSHA approved respirator if there is a risk of exposure to dust/fume at levels exceeding the exposure limits.

Methods and materials for containment and cleaning up

Vacuum up the spilled material. Vacuums used for this purpose should be equipped with HEPA filters. Containers must be labeled. Collect in approved containers and seal securely. For waste disposal, see Section 13 of the SDS.

Environmental precautions

Avoid discharge to drains, sewers, and other water systems.

7. Handling and storage

Precautions for safe handling

Minimize dust production when mixing, or opening and closing bags. Avoid inhalation of dust. Wear appropriate personal protective equipment. Wash hands after handling. Observe good industrial hygiene practices and use appropriate lifting techniques.

Conditions for safe storage, including any incompatibilities

Store in a cool, dry, well-ventilated place. Store away from incompatible materials. Avoid contact with acids, water, and moisture.

8. Exposure controls/personal protection

Occupational exposure limits

US. OSHA Specifically Regulated Substances (29 CFR 1910.1001-1053)

Impurities	Type	Value
Crystalline silica (Quartz) (CAS 14808-60-7)	TWA	0.05 mg/m3

US. OSHA Table Z-1 Permissible Exposure Limits (PEL) for Air Contaminants (29 CFR 1910.1000)

Components	Type	Value	Form
Calcium sulfate dihydrate (alternative CAS 10101-41-4) (CAS 13397-24-5)	PEL	5 mg/m3	Respirable fraction.
		15 mg/m3	Total dust.

US. OSHA Table Z-3 Permissible Exposure Limits (PEL) for Mineral Dusts (29 CFR 1910.1000)

Components	Type	Value	Form
Calcium sulfate dihydrate (alternative CAS 10101-41-4) (CAS 13397-24-5)	TWA	5 mg/m3	Respirable fraction.
		15 mg/m3	Total dust.
		50 mppcf	Total dust.
		15 mppcf	Respirable fraction.

Impurities	Type	Value	Form
Crystalline silica (Quartz) (CAS 14808-60-7)	TWA	0.1 mg/m3	Respirable.
		2.4 mppcf	Respirable.

US. ACGIH Threshold Limit Values (TLV)

Components	Type	Value	Form
Calcium sulfate dihydrate (alternative CAS 10101-41-4) (CAS 13397-24-5)	TWA	10 mg/m3	Inhalable fraction.

Impurities	Type	Value	Form
Crystalline silica (Quartz) (CAS 14808-60-7)	TWA	0.025 mg/m3	Respirable fraction.

NIOSH. Immediately Dangerous to Life or Health (IDLH) Values, as amended

Impurities	Type	Value
Crystalline silica (Quartz) (CAS 14808-60-7)	IDLH	50 mg/m3

US. NIOSH: Pocket Guide to Chemical Hazards

Components	Type	Value	Form
Calcium sulfate dihydrate (alternative CAS 10101-41-4) (CAS 13397-24-5)	TWA	5 mg/m3	Respirable.
		10 mg/m3	Total
Impurities	Type	Value	Form
Crystalline silica (Quartz) (CAS 14808-60-7)	TWA	0.05 mg/m3	Respirable dust.

Biological limit values

No biological exposure limits noted for the ingredient(s).

Appropriate engineering controls

Provide sufficient ventilation for operations causing dust formation. Observe occupational exposure limits and minimize the risk of exposure.

Individual protection measures, such as personal protective equipment
Eye/face protection

Wear approved safety goggles.

Skin protection
Hand protection

It is a good industrial hygiene practice to minimize skin contact. For prolonged or repeated skin contact use suitable protective gloves.

Skin protection	
Other	Normal work clothing (long sleeved shirts and long pants) is recommended.
Respiratory protection	If engineering controls do not maintain airborne concentrations below recommended exposure limits (where applicable) or to an acceptable level (in countries where exposure limits have not been established), an approved respirator must be worn. Use a NIOSH/MSHA approved respirator if there is a risk of exposure to dust/fume at levels exceeding the exposure limits.
Thermal hazards	None.
General hygiene considerations	Always observe good personal hygiene measures, such as washing after handling the material and before eating, drinking, and/or smoking. Routinely wash work clothing and protective equipment separately from regular wash. Observe any medical surveillance requirements.

9. Physical and chemical properties

Appearance

Physical state	Solid.
Form	Powder.
Color	White to off-white.
Odor	Low to no odor.
Odor threshold	Not applicable.
pH	6 - 8
Melting point/freezing point	Not applicable. Not applicable.
Initial boiling point and boiling range	Not applicable.
Flash point	Not applicable.
Evaporation rate	Not applicable.
Flammability (solid, gas)	Not applicable.

Upper/lower flammability or explosive limits

Explosive limit - lower (%)	Not applicable.
Explosive limit - upper (%)	Not applicable.
Vapor pressure	Not applicable.
Vapor density	Not applicable.
Relative density	2.96 (H ₂ O=1)
Solubility(ies)	
Solubility (water)	0.15 - 0.4 g/100 g (H ₂ O)
Partition coefficient (n-octanol/water)	Not applicable.
Auto-ignition temperature	Not applicable.
Decomposition temperature	2642 °F (1450 °C)
Viscosity	Not applicable.
Other information	
Bulk density	55 - 70 lb/ft ³
Particle size	Varies.
VOC	0 %

10. Stability and reactivity

Reactivity	The product is stable and non-reactive under normal conditions of use, storage and transport.
Chemical stability	Material is stable under normal conditions.
Possibility of hazardous reactions	Hazardous polymerization does not occur.
Conditions to avoid	Contact with incompatible materials. Exposure to moisture.
Incompatible materials	Acids.
Hazardous decomposition products	Calcium oxides, carbon dioxide, and carbon monoxide.

11. Toxicological information

Information on likely routes of exposure

Inhalation	Inhalation of dusts may cause respiratory irritation. Prolonged and repeated exposure to airborne respirable crystalline silica can cause silicosis and/or lung cancer.
Skin contact	Under normal conditions of intended use, this product does not pose a skin hazard.
Eye contact	Direct contact with airborne particulates may cause temporary irritation.
Ingestion	May cause discomfort if swallowed.

Symptoms related to the physical, chemical and toxicological characteristics	Dust may irritate eyes and mucous membranes of the nose, throat and upper respiratory system causing sneezing and/or coughing. Prolonged exposure may cause chronic effects.
---	--

Information on toxicological effects

Acute toxicity	Not expected to be acutely toxic.
Skin corrosion/irritation	Not a skin irritant.
Serious eye damage/eye irritation	Direct contact with eyes may cause temporary irritation.

Respiratory or skin sensitization

Respiratory sensitization	Not a respiratory sensitizer.
Skin sensitization	Not a skin sensitizer.

Germ cell mutagenicity	Data does not suggest that this product or any components present at greater than 0.1% are mutagenic or genotoxic.
-------------------------------	--

Carcinogenicity	Repeated and prolonged exposures to high levels of respirable crystalline silica may cause cancer.
------------------------	--

IARC Monographs. Overall Evaluation of Carcinogenicity

Crystalline silica (Quartz) (CAS 14808-60-7)	1 Carcinogenic to humans.
--	---------------------------

NTP Report on Carcinogens

Crystalline silica (Quartz) (CAS 14808-60-7)	Known To Be Human Carcinogen.
--	-------------------------------

OSHA Specifically Regulated Substances (29 CFR 1910.1001-1053)

Crystalline silica (Quartz) (CAS 14808-60-7)	Cancer
--	--------

Reproductive toxicity	Not expected to be a reproductive hazard.
------------------------------	---

Specific target organ toxicity - single exposure	No data available, but none expected.
---	---------------------------------------

Specific target organ toxicity - repeated exposure	Not classified. For detailed information, see section 16.
---	---

Aspiration hazard	Due to the physical form of the product it is not an aspiration hazard.
--------------------------	---

Chronic effects	Prolonged and routine inhalation of high levels of respirable crystalline silica particles can lead to the lung disease known as silicosis. Some studies show excess numbers of cases of scleroderma, connective tissue disorders, lupus, rheumatoid arthritis, chronic kidney diseases and end-stage kidney disease in workers exposed to respirable crystalline silica. Pre-existing skin and respiratory conditions including dermatitis, asthma and chronic lung disease might be aggravated by exposure. Occupational exposure to respirable dust and respirable crystalline silica should be monitored and controlled.
------------------------	--

12. Ecological information

Ecotoxicity	The product components are not classified as environmentally hazardous. However, this does not exclude the possibility that large or frequent spills can have a harmful or damaging effect on the environment.
--------------------	--

Components	Species	Test Results
Calcium sulfate dihydrate (alternative CAS 10101-41-4) (CAS 13397-24-5)		
Aquatic		
Fish	LC50	Fathead minnow (Pimephales promelas) > 1970 mg/l, 96 hours
Persistence and degradability	Calcium sulfate dissolves in water forming calcium and sulfate ions.	
Bioaccumulative potential	Bioaccumulation is not expected.	
Mobility in soil	No data available.	
Other adverse effects	None expected.	

13. Disposal considerations

Disposal instructions	Dispose in accordance with applicable federal, state, and local regulations. Recycle responsibly.
Local disposal regulations	Dispose of in accordance with local regulations.
Hazardous waste code	The waste code should be assigned in discussion between the user, the producer and the waste disposal company.
Waste from residues / unused products	Dispose in accordance with local regulations.
Contaminated packaging	Dispose of in accordance with local regulations.

14. Transport information

DOT	Not regulated as dangerous goods.
IATA	Not regulated as dangerous goods.
IMDG	Not regulated as dangerous goods.
Transport in bulk according to Annex II of MARPOL 73/78 and the IBC Code	Not applicable.

15. Regulatory information

US federal regulations	This product is a "Hazardous Chemical" as defined by the OSHA Hazard Communication Standard 29 CFR 1910.1200 (OSHA) and 8 CCR § 5194 (Cal/OSHA).	
TSCA Section 12(b) Export Notification (40 CFR 707, Subpt. D)	Not regulated.	
CERCLA Hazardous Substance List (40 CFR 302.4)	Not listed.	
SARA 304 Emergency release notification	Not regulated.	
OSHA Specifically Regulated Substances (29 CFR 1910.1001-1053)	Crystalline silica (Quartz) (CAS 14808-60-7)	
		Cancer lung effects immune system effects kidney effects
Toxic Substances Control Act (TSCA)	All components of the mixture on the TSCA 8(b) inventory are designated "active".	
Superfund Amendments and Reauthorization Act of 1986 (SARA)		
SARA 302 Extremely hazardous substance	Not listed.	
SARA 311/312 Hazardous chemical	Yes	
Classified hazard categories	Carcinogenicity	
SARA 313 (TRI reporting)	Not regulated.	
Other federal regulations		
Clean Air Act (CAA) Section 112 Hazardous Air Pollutants (HAPs) List	Not regulated.	
Clean Air Act (CAA) Section 112(r) Accidental Release Prevention (40 CFR 68.130)	Not regulated.	
Safe Drinking Water Act (SDWA)	Not regulated.	
US state regulations		
US. Massachusetts RTK - Substance List	Calcium sulfate dihydrate (alternative CAS 10101-41-4) (CAS 13397-24-5) Crystalline silica (Quartz) (CAS 14808-60-7)	

US. New Jersey Worker and Community Right-to-Know Act

Calcium sulfate dihydrate (alternative CAS 10101-41-4) (CAS 13397-24-5)
 Crystalline silica (Quartz) (CAS 14808-60-7)

US. Pennsylvania Worker and Community Right-to-Know Law

Calcium sulfate dihydrate (alternative CAS 10101-41-4) (CAS 13397-24-5)
 Crystalline silica (Quartz) (CAS 14808-60-7)

US. Rhode Island RTK

Calcium sulfate dihydrate (alternative CAS 10101-41-4) (CAS 13397-24-5)
 Crystalline silica (Quartz) (CAS 14808-60-7)

California Proposition 65

WARNING: This product can expose you to Crystalline silica (Quartz), which is known to the State of California to cause cancer. For more information go to www.P65Warnings.ca.gov.

California Proposition 65 - CRT: Listed date/Carcinogenic substance

Crystalline silica (Quartz) (CAS 14808-60-7) Listed: October 1, 1988

International Inventories

Country(s) or region	Inventory name	On inventory (yes/no)*
Australia	Australian Inventory of Industrial Chemicals (AICIS)	Yes
Canada	Domestic Substances List (DSL)	Yes
Canada	Non-Domestic Substances List (NDSL)	No
China	Inventory of Existing Chemical Substances in China (IECSC)	Yes
Europe	European Inventory of Existing Commercial Chemical Substances (EINECS)	Yes
Europe	European List of Notified Chemical Substances (ELINCS)	No
Japan	Inventory of Existing and New Chemical Substances (ENCS)	Yes
Korea	Existing Chemicals List (ECL)	Yes
New Zealand	New Zealand Inventory	Yes
Philippines	Philippine Inventory of Chemicals and Chemical Substances (PICCS)	Yes
Taiwan	Taiwan Chemical Substance Inventory (TCSI)	Yes
United States & Puerto Rico	Toxic Substances Control Act (TSCA) Inventory	Yes

*A "Yes" indicates that all components of this product comply with the inventory requirements administered by the governing country(s)

A "No" indicates that one or more components of the product are not listed or exempt from listing on the inventory administered by the governing country(s).

16. Other information, including date of preparation or last revision

Issue date 23-May-2014

Revision date 17-July-2024

Version # 04

Further information Crystalline silica: Raw materials in this product contain respirable crystalline silica as an impurity. Exposures to respirable crystalline silica are not expected during the normal use of this product. However, actual levels must be determined by workplace hygiene testing. Prolonged and repeated exposure to airborne free respirable crystalline silica can result in lung disease (i.e., silicosis) and/or lung cancer.

NFPA Ratings:
 Health: 1
 Flammability: 0
 Physical hazard: 0

Hazard Scale: 0 = Minimal 1 = Slight 2 = Moderate 3 = Serious 4 = Severe

NFPA ratings**Disclaimer**

This information is provided without warranty. The information is believed to be correct. This information should be used to make an independent determination of the methods to safeguard workers and the environment.