



SAFETY DATA SHEET

1. Identification

Product identifier NORFOLK™ Veneer Finish Plaster

Other means of identification

SDS number 53000010016

Synonyms Construction Plaster.

Recommended use Interior use.

Recommended restrictions Use in accordance with manufacturer's recommendations.

Manufacturer/Importer/Supplier/Distributor information

Company name United States Gypsum Company

Address 550 West Adams Street
Chicago, Illinois 60661-3637

Telephone 1-800-874-4968

Website www.usg.com

Emergency phone number 1-800-507-8899

2. Hazard(s) identification

Physical hazards Not classified.

Health hazards Serious eye damage/eye irritation Category 1
Carcinogenicity (inhalation) Category 1A
Specific target organ toxicity, repeated exposure (inhalation) Category 2 (Lung)

OSHA defined hazards Not classified.

Label elements



Signal word Danger

Hazard statement Causes serious eye damage. May cause cancer by inhalation. May cause damage to organs (Lung) through prolonged or repeated exposure.

Precautionary statement

Prevention Obtain special instructions before use. Do not handle until all safety precautions have been read and understood. Do not breathe dust. Wear protective gloves/protective clothing/eye protection/face protection.

Response If exposed or concerned: Get medical advice/attention. If in eyes: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. Immediately call a poison center/doctor.

Storage Store locked up.

Disposal Dispose of contents/container in accordance with local/regional/national/international regulations.

Hazard(s) not otherwise classified (HNOC) None known.

Supplemental information None.

3. Composition/information on ingredients

Mixtures

Chemical name	CAS number	%
Plaster of Paris (Calcium Sulfate Hemihydrate CAS 10034-76-1)	26499-65-0	> 65
Quartz (Sand)	14808-60-7	< 35
Dolomitic hydroxide	39445-23-3	< 10

Impurities

Chemical name	CAS number	%
Crystalline silica (Quartz)	14808-60-7	< 2

Composition comments

All concentrations are in percent by weight.

Raw materials in this product contain respirable crystalline silica as an impurity. The weight percent of respirable crystalline silica found in this product is < 2%. Exposures to respirable crystalline silica during the normal use of this product must be determined by workplace hygiene testing.

4. First-aid measures

Inhalation

Dust irritates the respiratory system, and may cause coughing and difficulties in breathing. Move injured person into fresh air and keep person calm under observation. Get medical attention if symptoms persist.

Skin contact

Contact with dust: Rinse area with plenty of water. Get medical attention if irritation develops or persists.

Eye contact

Immediately flush eyes with plenty of water for at least 15 minutes. Remove contact lenses, if present and easy to do. Continue rinsing. Get medical attention immediately. Dust in the eyes: Do not rub eyes. Flush thoroughly with water. If irritation occurs, get medical attention immediately.

Ingestion

Plaster of Paris hardens and if ingested may result in stomach and intestinal blockage. Drinking gelatin solutions or large volumes of water may delay setting.

Most important symptoms/effects, acute and delayed

Severe eye irritation. Permanent eye damage including blindness could result. Dust may irritate throat and respiratory system and cause coughing. Skin irritation. Prolonged exposure may cause chronic effects.

Indication of immediate medical attention and special treatment needed

Provide general supportive measures and treat symptomatically.

General information

Ensure that medical personnel are aware of the material(s) involved.

5. Fire-fighting measures

Suitable extinguishing media

Use fire-extinguishing media appropriate for surrounding materials.

Unsuitable extinguishing media

Not applicable.

Specific hazards arising from the chemical

Not a fire hazard.

Special protective equipment and precautions for firefighters

Selection of respiratory protection for firefighting: follow the general fire precautions indicated in the workplace. Self-contained breathing apparatus and full protective clothing must be worn in case of fire.

Fire fighting equipment/instructions

Use standard firefighting procedures and consider the hazards of other involved materials.

Specific methods

Cool material exposed to heat with water spray and remove it if no risk is involved.

General fire hazards

No unusual fire or explosion hazards noted.

6. Accidental release measures

Personal precautions, protective equipment and emergency procedures

Avoid inhalation of dust and contact with skin and eyes. See Section 8 of the SDS for Personal Protective Equipment.

Methods and materials for containment and cleaning up

Vacuum up the spilled material. Vacuums used for this purpose should be equipped with HEPA filters. Containers must be labeled. Collect in approved containers and seal securely. For waste disposal, see Section 13 of the SDS.

Environmental precautions

Avoid discharge to drains, sewers, and other water systems.

7. Handling and storage

Precautions for safe handling

Minimize dust production when mixing, or opening and closing bags. Avoid inhalation of dust. Wear appropriate personal protective equipment. Wash hands after handling. Observe good industrial hygiene practices and use appropriate lifting techniques.

Conditions for safe storage, including any incompatibilities

Store in a cool, dry, well-ventilated place. Store away from incompatible materials. Avoid contact with acids, water, and moisture.

8. Exposure controls/personal protection

Occupational exposure limits

US. OSHA Specifically Regulated Substances (29 CFR 1910.1001-1053)

Impurities	Type	Value
Crystalline silica (Quartz) (CAS 14808-60-7)	TWA	0.05 mg/m ³

US. OSHA Table Z-1 Limits for Air Contaminants (29 CFR 1910.1000)

Components	Type	Value	Form
Plaster of Paris (Calcium Sulfate Hemihydrate CAS 10034-76-1) (CAS 26499-65-0)	PEL	5 mg/m ³	Respirable fraction.
		15 mg/m ³	Total dust.

US. OSHA Table Z-3 (29 CFR 1910.1000)

Impurities	Type	Value	Form
Crystalline silica (Quartz) (CAS 14808-60-7)	TWA	0.1 mg/m ³	Respirable.
		2.4 mppcf	Respirable.

US. ACGIH Threshold Limit Values

Components	Type	Value	Form
Plaster of Paris (Calcium Sulfate Hemihydrate CAS 10034-76-1) (CAS 26499-65-0)	TWA	10 mg/m ³	Inhalable fraction.

Impurities	Type	Value	Form
Crystalline silica (Quartz) (CAS 14808-60-7)	TWA	0.025 mg/m ³	Respirable fraction.

US. NIOSH: Pocket Guide to Chemical Hazards

Components	Type	Value	Form
Plaster of Paris (Calcium Sulfate Hemihydrate CAS 10034-76-1) (CAS 26499-65-0)	TWA	5 mg/m ³	Respirable.
		10 mg/m ³	Total

Impurities	Type	Value	Form
Crystalline silica (Quartz) (CAS 14808-60-7)	TWA	0.05 mg/m ³	Respirable dust.

Biological limit values

No biological exposure limits noted for the ingredient(s).

Appropriate engineering controls

Provide sufficient ventilation for operations causing dust formation. Observe occupational exposure limits and minimize the risk of exposure.

Individual protection measures, such as personal protective equipment

Eye/face protection Wear dust-resistant safety goggles.

Skin protection

Hand protection Wear protective gloves.

Skin protection

Other Normal work clothing (long sleeved shirts and long pants) is recommended.

Respiratory protection	If engineering controls do not maintain airborne concentrations below recommended exposure limits (where applicable) or to an acceptable level (in countries where exposure limits have not been established), an approved respirator must be worn. Use a NIOSH/MSHA approved respirator if there is a risk of exposure to dust/fume at levels exceeding the exposure limits.
Thermal hazards	None.
General hygiene considerations	Always observe good personal hygiene measures, such as washing after handling the material and before eating, drinking, and/or smoking. Routinely wash work clothing and protective equipment separately from regular wash. Observe any medical surveillance requirements.

9. Physical and chemical properties

Appearance

Physical state	Solid.
Form	Powder.
Color	White to off-white.
Odor	Low to no odor.
Odor threshold	Not applicable.
pH	6 - 8
Melting point/freezing point	Not applicable.
Initial boiling point and boiling range	Not applicable.
Flash point	Not applicable.
Evaporation rate	Not applicable.
Flammability (solid, gas)	Not applicable.

Upper/lower flammability or explosive limits

Flammability limit - lower (%)	Not applicable.
Flammability limit - upper (%)	Not applicable.
Explosive limit - lower (%)	Not applicable.
Explosive limit - upper (%)	Not applicable.

Vapor pressure	Not applicable.
Vapor density	Not applicable.
Relative density	2.4 - 2.8 (H ₂ O=1)

Solubility(ies)

Solubility (water)	0.15-0.40 g/100g (H ₂ O)
Partition coefficient (n-octanol/water)	Not applicable.

Auto-ignition temperature	Not applicable.
Decomposition temperature	2642 °F (1450 °C)
Viscosity	Not applicable.

Other information

Bulk density	45 - 55 lb/ft ³ (dry)
Explosive properties	Not explosive.
Oxidizing properties	Not oxidizing.
VOC	Not applicable.

10. Stability and reactivity

Reactivity	The product is stable and non reactive under normal conditions of storage and transport.
Chemical stability	Material is stable under normal conditions.
Possibility of hazardous reactions	Hazardous polymerization does not occur.
Conditions to avoid	Contact with incompatible materials. Exposure to moisture. When mixed with water this product can become very hot. Encasing or making moulds of any body part can cause serious burns that may require surgical removal of affected tissue and even amputation of encased body part.

Incompatible materials Acids. Crystalline silica in contact with powerful oxidizing agents, such as fluorine, chlorine trifluoride and oxygen difluoride, may cause fires. Crystalline silica will dissolve in hydrofluoric acid and produce a corrosive gas, silicon tetrafluoride.

Hazardous decomposition products Calcium oxides. Sulfur oxides. Magnesium oxides.

11. Toxicological information

Information on likely routes of exposure

Inhalation Inhalation of dusts may cause severe respiratory tract irritation. Prolonged and repeated exposure to airborne respirable crystalline silica can cause silicosis and/or lung cancer.

Skin contact Causes severe skin irritation and burning, especially in the presence of moisture.

Eye contact Causes severe irritation and burning of the eyes, may cause permanent damage.

Ingestion May cause burns to mouth, throat and stomach.

Symptoms related to the physical, chemical and toxicological characteristics Skin irritation. Severe eye irritation. Permanent eye damage including blindness could result. Dust may irritate throat and respiratory system and cause coughing. Prolonged exposure may cause chronic effects.

Information on toxicological effects

Acute toxicity Contact may cause serious skin and eye damage that can be permanent; ingestion can cause burns in mouth, esophagus and stomach.

Skin corrosion/irritation May be corrosive (causing chemical burns) to eyes and skin when in contact with water.

Serious eye damage/eye irritation Can cause severe eye damage that may be irreversible.

Respiratory or skin sensitization

Respiratory sensitization Not a respiratory sensitizer.

Skin sensitization Not a skin sensitizer. Plaster of Paris has displayed little sensitization potential.

Germ cell mutagenicity No data available to indicate product or any components present at greater than 0.1% are mutagenic or genotoxic.

Carcinogenicity Repeated and prolonged exposures to high levels of respirable crystalline silica may cause cancer.

IARC Monographs. Overall Evaluation of Carcinogenicity

Crystalline silica (Quartz) (CAS 14808-60-7) 1 Carcinogenic to humans.

NTP Report on Carcinogens

Crystalline silica (Quartz) (CAS 14808-60-7) Known To Be Human Carcinogen.

OSHA Specifically Regulated Substances (29 CFR 1910.1001-1053)

Crystalline silica (Quartz) (CAS 14808-60-7) Cancer

Reproductive toxicity Not expected to be a reproductive hazard.

Specific target organ toxicity - single exposure May cause respiratory irritation.

Specific target organ toxicity - repeated exposure May damage lung tissue through repeated and prolonged exposure to high levels of respirable crystalline silica particles.

Aspiration hazard Due to the physical form of the product it is not an aspiration hazard.

Chronic effects Prolonged and routine inhalation of high levels of respirable crystalline silica particles can lead to the lung disease known as silicosis. Some studies show excess numbers of cases of scleroderma, connective tissue disorders, lupus, rheumatoid arthritis, chronic kidney diseases and end-stage kidney disease in workers exposed to respirable crystalline silica. Pre-existing skin and respiratory conditions including dermatitis, asthma and chronic lung disease might be aggravated by exposure. Occupational exposure to respirable dust and respirable crystalline silica should be monitored and controlled.

12. Ecological information

Ecotoxicity The product components are not classified as environmentally hazardous. However, this does not exclude the possibility that large or frequent spills can have a harmful or damaging effect on the environment.

Plaster of Paris (Calcium Sulfate Hemihydrate CAS 10034-76-1) (CAS 26499-65-0)

Aquatic

Fish LC50 Fathead minnow (Pimephales promelas) > 1970 mg/l, 96 hours

Persistence and degradability Calcium sulfate dissolves in water forming calcium and sulfate ions.

Bioaccumulative potential Bioaccumulation is not expected.

Mobility in soil No data available.

Other adverse effects None expected.

13. Disposal considerations

Disposal instructions Dispose in accordance with applicable federal, state, and local regulations. Recycle responsibly.

Local disposal regulations Dispose of in accordance with local regulations.

Hazardous waste code The waste code should be assigned in discussion between the user, the producer and the waste disposal company.

Waste from residues / unused products Dispose of in accordance with local regulations.

Contaminated packaging Dispose of in accordance with local regulations.

14. Transport information

DOT

Not regulated as dangerous goods.

IATA

Not regulated as dangerous goods.

IMDG

Not regulated as dangerous goods.

Transport in bulk according to Annex II of MARPOL 73/78 and the IBC Code Not applicable.

15. Regulatory information

US federal regulations This product is a "Hazardous Chemical" as defined by the OSHA Hazard Communication Standard, 29 CFR 1910.1200.

TSCA Section 12(b) Export Notification (40 CFR 707, Subpt. D)

Not regulated.

CERCLA Hazardous Substance List (40 CFR 302.4)

Not listed.

SARA 304 Emergency release notification

Not regulated.

OSHA Specifically Regulated Substances (29 CFR 1910.1001-1053)

Crystalline silica (Quartz) (CAS 14808-60-7)	Cancer lung effects immune system effects kidney effects
--	---

Toxic Substances Control Act (TSCA) All components of the mixture on the TSCA 8(b) inventory are designated "active".

Superfund Amendments and Reauthorization Act of 1986 (SARA)

SARA 302 Extremely hazardous substance

Not listed.

SARA 311/312 Hazardous chemical Yes

Classified hazard categories Serious eye damage or eye irritation
Carcinogenicity
Specific target organ toxicity (single or repeated exposure)

SARA 313 (TRI reporting)

Not regulated.

Other federal regulations

Clean Air Act (CAA) Section 112 Hazardous Air Pollutants (HAPs) List

Not regulated.

Clean Air Act (CAA) Section 112(r) Accidental Release Prevention (40 CFR 68.130)

Not regulated.

Safe Drinking Water Act (SDWA)

Not regulated.

US state regulations

US. Massachusetts RTK - Substance List

Crystalline silica (Quartz) (CAS 14808-60-7)

Plaster of Paris (Calcium Sulfate Hemihydrate CAS 10034-76-1) (CAS 26499-65-0)

US. New Jersey Worker and Community Right-to-Know Act

Crystalline silica (Quartz) (CAS 14808-60-7)

Plaster of Paris (Calcium Sulfate Hemihydrate CAS 10034-76-1) (CAS 26499-65-0)

US. Pennsylvania Worker and Community Right-to-Know Law

Crystalline silica (Quartz) (CAS 14808-60-7)

Plaster of Paris (Calcium Sulfate Hemihydrate CAS 10034-76-1) (CAS 26499-65-0)

US. Rhode Island RTK

Crystalline silica (Quartz) (CAS 14808-60-7)

California Proposition 65



WARNING: This product can expose you to chemicals including Quartz, which is known to the State of California to cause cancer. For more information go to www.P65Warnings.ca.gov.

California Proposition 65 - CRT: Listed date/Carcinogenic substance

Crystalline silica (Quartz) (CAS 14808-60-7)

Listed: October 1, 1988

US. California. Candidate Chemicals List. Safer Consumer Products Regulations (Cal. Code Regs, tit. 22, 69502.3, subd. (a))

Crystalline silica (Quartz) (CAS 14808-60-7)

Dolomitic hydroxide (CAS 39445-23-3)

International Inventories

Country(s) or region	Inventory name	On inventory (yes/no)*
Australia	Australian Inventory of Chemical Substances (AICS)	No
Canada	Domestic Substances List (DSL)	No
Canada	Non-Domestic Substances List (NDSL)	Yes
China	Inventory of Existing Chemical Substances in China (IECSC)	Yes
Europe	European Inventory of Existing Commercial Chemical Substances (EINECS)	No
Europe	European List of Notified Chemical Substances (ELINCS)	No
Japan	Inventory of Existing and New Chemical Substances (ENCS)	No
Korea	Existing Chemicals List (ECL)	Yes
New Zealand	New Zealand Inventory	Yes
Philippines	Philippine Inventory of Chemicals and Chemical Substances (PICCS)	No
Taiwan	Taiwan Chemical Substance Inventory (TCSI)	No
United States & Puerto Rico	Toxic Substances Control Act (TSCA) Inventory	Yes

*A "Yes" indicates this product complies with the inventory requirements administered by the governing country(s).

A "No" indicates that one or more components of the product are not listed or exempt from listing on the inventory administered by the governing country(s).

16. Other information, including date of preparation or last revision

Issue date	18-June-2014
Revision date	31-August-2020
Version #	02

Further information

Crystalline silica: Raw materials in this product contain respirable crystalline silica as an impurity. Exposures to respirable crystalline silica are not expected during the normal use of this product. However, actual levels must be determined by workplace hygiene testing. Prolonged and repeated exposure to airborne free respirable crystalline silica can result in lung disease (i.e., silicosis) and/or lung cancer.

Plaster of Paris: Is classified as a hazardous substance but is generally considered a safe material for routine use. When plaster of Paris is used responsibly it is not considered as a dangerous material. However, when mixed with water this product can become very hot. DO NOT attempt to make a cast enclosing any part of the body. Encasing any body part can cause serious burns and even amputation of the encased body part.

NFPA Ratings:
Health: 2
Flammability: 0
Physical hazard: 0

Hazard Scale: 0 = Minimal 1 = Slight 2 = Moderate 3 = Serious 4 = Severe

NFPA ratings**Disclaimer**

This information is provided without warranty. The information is believed to be correct. This information should be used to make an independent determination of the methods to safeguard workers and the environment.