



SAFETY DATA SHEET

1. Identification

Product identifier SHEETROCK® Brand Tuff-Cover + Spackling Compound

Other means of identification

Product code 61111000007

Recommended use Interior use.

Recommended restrictions Use in accordance with manufacturer's recommendations.

Manufacturer/Importer/Supplier/Distributor information

Company name United States Gypsum Company

Address 550 West Adams Street
Chicago, Illinois 60661-3637

Telephone 1-800-874-4968

Website www.usg.com

Emergency phone number 1-800-507-8899

2. Hazard(s) identification

Physical hazards Not classified.

Health hazards Not classified.

OSHA defined hazards Not classified.

Label elements

Hazard symbol None.

Signal word None.

Hazard statement The mixture does not meet the criteria for classification.

Precautionary statement

Prevention Observe good industrial hygiene practices.

Response Wash hands after handling.

Storage Store away from incompatible materials.

Disposal Dispose of waste and residues in accordance with local authority requirements.

Hazard(s) not otherwise classified (HNOC) None known.

Supplemental information None.

3. Composition/information on ingredients

Mixtures

| Chemical name | CAS number | % |
|--|-------------|-------|
| Limestone | 1317-65-3 | < 40 |
| Kaolin | 1332-58-7 | < 10 |
| Soda lime borosilicate glass spheres | 65997-17-3 | < 10 |
| TRADE SECRET | Proprietary | < 5 |
| Titanium dioxide | 13463-67-7 | < 5 |
| 1,3,5-tris(2-hydroxyethyl)hexahydro-1,3,5-triazine | 4719-04-4 | < 0.2 |

Composition comments

All concentrations are in percent by weight.

Raw materials in this product contain respirable crystalline silica as an impurity. The weight percent of respirable crystalline silica found in this product is < 1.0%. Industrial hygiene testing of this product and its constituents suggests that under normal conditions the expected use of this product will not result in exposure to respirable crystalline silica that exceeds the OSHA PEL. However, actual exposures to respirable crystalline silica on a given jobsite must be determined by workplace hygiene testing.

4. First-aid measures

Inhalation

Move to fresh air. Call a physician if symptoms develop or persist.

Skin contact

Wash off with soap and water. Get medical attention if irritation develops and persists.

Eye contact

Do not rub eyes. Rinse with water. Get medical attention if irritation develops and persists.

Ingestion

Rinse mouth. Get medical attention if symptoms occur.

Most important symptoms/effects, acute and delayed

Dusts may irritate the respiratory tract, skin and eyes. Coughing.

Indication of immediate medical attention and special treatment needed

Treat symptomatically.

General information

Ensure that medical personnel are aware of the material(s) involved, and take precautions to protect themselves.

5. Fire-fighting measures

Suitable extinguishing media

Water fog. Foam. Dry chemical powder. Carbon dioxide (CO₂).

Unsuitable extinguishing media

Do not use water jet as an extinguisher, as this will spread the fire.

Specific hazards arising from the chemical

During fire, gases hazardous to health may be formed.

Special protective equipment and precautions for firefighters

Self-contained breathing apparatus and full protective clothing must be worn in case of fire.

Fire fighting equipment/instructions

Move containers from fire area if you can do so without risk.

Specific methods

Use standard firefighting procedures and consider the hazards of other involved materials.

General fire hazards

No unusual fire or explosion hazards noted.

6. Accidental release measures

Personal precautions, protective equipment and emergency procedures

Keep unnecessary personnel away. Wear appropriate protective equipment and clothing during clean-up. Use a NIOSH/MSHA approved respirator if there is a risk of exposure to dust/fume at levels exceeding the exposure limits. For personal protection, see section 8 of the SDS.

Methods and materials for containment and cleaning up

Stop the flow of material, if this is without risk.

Large Spills: Wet down with water and dike for later disposal. Absorb in vermiculite, dry sand or earth and place into containers. Shovel the material into waste container. Following product recovery, flush area with water.

Small Spills: Sweep up or vacuum up spillage and collect in suitable container for disposal. Wipe up with absorbent material (e.g. cloth, fleece). Clean surface thoroughly to remove residual contamination.

Never return spills to original containers for re-use. For waste disposal, see section 13 of the SDS. Avoid discharge into drains, water courses or onto the ground.

Environmental precautions

7. Handling and storage

Precautions for safe handling

Avoid prolonged exposure. Practice good housekeeping.

Conditions for safe storage, including any incompatibilities

Store in tightly closed container. Store in a well-ventilated place. Store away from incompatible materials (see Section 10 of the SDS).

8. Exposure controls/personal protection

Occupational exposure limits

US. OSHA Table Z-1 Limits for Air Contaminants (29 CFR 1910.1000)

| Components | Type | Value | Form |
|-----------------------------------|------|----------------------|----------------------|
| Kaolin (CAS 1332-58-7) | PEL | 5 mg/m ³ | Respirable fraction. |
| | | 15 mg/m ³ | Total dust. |
| Limestone (CAS 1317-65-3) | PEL | 5 mg/m ³ | Respirable fraction. |
| | | 15 mg/m ³ | Total dust. |
| Titanium dioxide (CAS 13463-67-7) | PEL | 15 mg/m ³ | Total dust. |
| TRADE SECRET | PEL | 5 mg/m ³ | Respirable fraction. |
| | | 15 mg/m ³ | Total dust. |

US. OSHA Table Z-3 (29 CFR 1910.1000)

| Components | Type | Value | Form |
|------------------------|------|----------------------|----------------------|
| Kaolin (CAS 1332-58-7) | TWA | 5 mg/m ³ | Respirable fraction. |
| | | 15 mg/m ³ | Total dust. |
| | | 50 mppcf | Total dust. |
| | | 15 mppcf | Respirable fraction. |

US. ACGIH Threshold Limit Values

| Components | Type | Value | Form |
|-----------------------------------|------|----------------------|----------------------|
| Kaolin (CAS 1332-58-7) | TWA | 2 mg/m ³ | Respirable fraction. |
| Titanium dioxide (CAS 13463-67-7) | TWA | 10 mg/m ³ | |

US. NIOSH: Pocket Guide to Chemical Hazards

| Components | Type | Value | Form |
|---------------------------|------|----------------------|-------------|
| Kaolin (CAS 1332-58-7) | TWA | 5 mg/m ³ | Respirable. |
| | | 10 mg/m ³ | Total |
| Limestone (CAS 1317-65-3) | TWA | 5 mg/m ³ | Respirable. |
| | | 10 mg/m ³ | Total |

Biological limit values

No biological exposure limits noted for the ingredient(s).

Appropriate engineering controls

Good general ventilation should be used. Ventilation rates should be matched to conditions. If applicable, use process enclosures, local exhaust ventilation, or other engineering controls to maintain airborne levels below recommended exposure limits. If exposure limits have not been established, maintain airborne levels to an acceptable level.

Individual protection measures, such as personal protective equipment

Eye/face protection Wear safety glasses with side shields (or goggles).

Skin protection

Hand protection Wear appropriate chemical resistant gloves.

Skin protection

Other Wear suitable protective clothing.

Respiratory protection

If engineering controls do not maintain airborne concentrations below recommended exposure limits (where applicable) or to an acceptable level (in countries where exposure limits have not been established), an approved respirator must be worn. Use a NIOSH/MSHA approved respirator if there is a risk of exposure to dust/fume at levels exceeding the exposure limits.

Thermal hazards

Wear appropriate thermal protective clothing, when necessary.

General hygiene considerations

Always observe good personal hygiene measures, such as washing after handling the material and before eating, drinking, and/or smoking. Routinely wash work clothing and protective equipment to remove contaminants.

9. Physical and chemical properties

Appearance

Physical state Liquid.

SHEETROCK® Brand Tuff-Cover + Spackling Compound

956361 Version #: 02 Revision date: 09-December-2020 Issue date: 13-November-2020

SDS US

3 / 8

| | |
|---|------------------------------------|
| Form | Semi-solid. |
| Color | White. |
| Odor | Acrylic. |
| Odor threshold | Not applicable. |
| pH | 9 - 10.5 |
| Melting point/freezing point | Not applicable. Not applicable. |
| Initial boiling point and boiling range | Not applicable. |
| Flash point | Not applicable. |
| Evaporation rate | Not applicable. |
| Flammability (solid, gas) | Not applicable. |
| Upper/lower flammability or explosive limits | |
| Flammability limit - lower (%) | Not applicable. |
| Flammability limit - upper (%) | Not applicable. |
| Explosive limit - lower (%) | Not applicable. |
| Explosive limit - upper (%) | Not applicable. |
| Vapor pressure | Not applicable. |
| Vapor density | Not applicable. |
| Relative density | Not applicable. |
| Solubility(ies) | |
| Solubility (water) | Not applicable. |
| Partition coefficient (n-octanol/water) | Not applicable. |
| Auto-ignition temperature | Not applicable. |
| Decomposition temperature | Not applicable. |
| Viscosity | 47400 - 86900 cps |
| Other information | |
| Bulk density | 40 - 50 lb/ft ³ |
| Explosive properties | Not explosive. |
| Oxidizing properties | Not oxidizing. |
| VOC | 16.63 g/L |

10. Stability and reactivity

| | |
|---|---|
| Reactivity | The product is stable and non-reactive under normal conditions of use, storage and transport. |
| Chemical stability | Material is stable under normal conditions. |
| Possibility of hazardous reactions | No dangerous reaction known under conditions of normal use. |
| Conditions to avoid | Contact with incompatible materials. |
| Incompatible materials | Strong oxidizing agents. |
| Hazardous decomposition products | No hazardous decomposition products are known. |

11. Toxicological information

Information on likely routes of exposure

| | |
|---------------------|--|
| Inhalation | Dust may irritate respiratory system. Prolonged inhalation may be harmful. |
| Skin contact | Dust or powder may irritate the skin. |
| Eye contact | Dust may irritate the eyes. |
| Ingestion | Expected to be a low ingestion hazard. |

Symptoms related to the physical, chemical and toxicological characteristics Dusts may irritate the respiratory tract, skin and eyes. Coughing.

Information on toxicological effects

Acute toxicity Not expected to be acutely toxic.

| Components | Species | Test Results |
|-----------------------------------|---------|-------------------|
| Kaolin (CAS 1332-58-7) | | |
| Acute | | |
| Dermal | | |
| LD50 | Rat | > 5000 mg/kg |
| Inhalation | | |
| LC50 | Rat | > 2 mg/l, 4 Hours |
| Oral | | |
| LD50 | Rat | > 5000 mg/kg |
| Titanium dioxide (CAS 13463-67-7) | | |
| Acute | | |
| Oral | | |
| LD50 | Rat | > 5000 mg/kg |
| TRADE SECRET (CAS Proprietary) | | |
| Acute | | |
| Dermal | | |
| LD50 | Rabbit | > 18700 mg/kg |
| Oral | | |
| LD50 | Rat | 27200 mg/kg |

Skin corrosion/irritation Prolonged skin contact may cause temporary irritation.

Serious eye damage/eye irritation Direct contact with eyes may cause temporary irritation.

Respiratory or skin sensitization

Respiratory sensitization Not a respiratory sensitizer.

Skin sensitization This product is not expected to cause skin sensitization.

Germ cell mutagenicity No data available to indicate product or any components present at greater than 0.1% are mutagenic or genotoxic.

Carcinogenicity Due to the form of the product, exposure to the potentially carcinogenic components is not expected. See Section 16 for further information.

IARC Monographs. Overall Evaluation of Carcinogenicity

Titanium dioxide (CAS 13463-67-7) 2B Possibly carcinogenic to humans.

NTP Report on Carcinogens

Not listed.

OSHA Specifically Regulated Substances (29 CFR 1910.1001-1053)

Not listed.

Reproductive toxicity This product is not expected to cause reproductive or developmental effects.

Specific target organ toxicity - single exposure Not classified.

Specific target organ toxicity - repeated exposure Not classified.

Aspiration hazard Not an aspiration hazard.

Chronic effects Prolonged inhalation may be harmful. Prolonged exposure may cause chronic effects.

12. Ecological information

Ecotoxicity The product is not classified as environmentally hazardous. However, this does not exclude the possibility that large or frequent spills can have a harmful or damaging effect on the environment.

| Components | Species | Test Results |
|-----------------------------------|---------|--------------------------------------|
| Kaolin (CAS 1332-58-7) | | |
| Aquatic | | |
| <i>Acute</i> | | |
| Crustacea | LC50 | Daphnia magna > 1.1 g/l, 48 Hours |
| Titanium dioxide (CAS 13463-67-7) | | |
| Aquatic | | |
| <i>Acute</i> | | |
| Crustacea | EC50 | Daphnia magna > 100 mg/l, 48 Hours |
| Fish | LL50 | Oryzias latipes > 100 mg/l, 96 Hours |
| TRADE SECRET (CAS Proprietary) | | |
| Aquatic | | |
| <i>Acute</i> | | |
| Crustacea | EC50 | Daphnia magna > 10000 mg/l, 24 Hours |

Persistence and degradability No data is available on the degradability of this product.

Bioaccumulative potential

Partition coefficient n-octanol / water (log Kow)

TRADE SECRET -1.76

Mobility in soil No data available.

Other adverse effects No other adverse environmental effects (e.g. ozone depletion, photochemical ozone creation potential, endocrine disruption, global warming potential) are expected from this component.

13. Disposal considerations

Disposal instructions Collect and reclaim or dispose in sealed containers at licensed waste disposal site.

Local disposal regulations Dispose in accordance with all applicable regulations.

Hazardous waste code The waste code should be assigned in discussion between the user, the producer and the waste disposal company.

Waste from residues / unused products Dispose of in accordance with local regulations. Empty containers or liners may retain some product residues. This material and its container must be disposed of in a safe manner (see: Disposal instructions).

Contaminated packaging Since emptied containers may retain product residue, follow label warnings even after container is emptied. Empty containers should be taken to an approved waste handling site for recycling or disposal.

14. Transport information

DOT

Not regulated as dangerous goods.

IATA

Not regulated as dangerous goods.

IMDG

Not regulated as dangerous goods.

Transport in bulk according to Annex II of MARPOL 73/78 and the IBC Code Not established.

15. Regulatory information

US federal regulations This product is not known to be a "Hazardous Chemical" as defined by the OSHA Hazard Communication Standard, 29 CFR 1910.1200.

TSCA Section 12(b) Export Notification (40 CFR 707, Subpt. D)

Not regulated.

CERCLA Hazardous Substance List (40 CFR 302.4)

Not listed.

SARA 304 Emergency release notification

Not regulated.

OSHA Specifically Regulated Substances (29 CFR 1910.1001-1053)

Crystalline silica (Quartz) (CAS 14808-60-7) Cancer

lung effects
immune system effects
kidney effects

Toxic Substances Control Act (TSCA)

All components of the mixture on the TSCA 8(b) inventory are designated "active".

Superfund Amendments and Reauthorization Act of 1986 (SARA)

SARA 302 Extremely hazardous substance

Not listed.

SARA 311/312 Hazardous chemical No

SARA 313 (TRI reporting)

Not regulated.

Other federal regulations

Clean Air Act (CAA) Section 112 Hazardous Air Pollutants (HAPs) List

Not regulated.

Clean Air Act (CAA) Section 112(r) Accidental Release Prevention (40 CFR 68.130)

Not regulated.

Safe Drinking Water Act (SDWA) Not regulated.

FEMA Priority Substances Respiratory Health and Safety in the Flavor Manufacturing Workplace

TRADE SECRET (CAS Proprietary)

Other Flavoring Substances with OSHA PEL's

US state regulations

US. Massachusetts RTK - Substance List

Crystalline silica (Quartz) (CAS 14808-60-7)

Kaolin (CAS 1332-58-7)

Limestone (CAS 1317-65-3)

Titanium dioxide (CAS 13463-67-7)

TRADE SECRET (CAS Proprietary)

US. New Jersey Worker and Community Right-to-Know Act

Crystalline silica (Quartz) (CAS 14808-60-7)

Kaolin (CAS 1332-58-7)

Limestone (CAS 1317-65-3)

Titanium dioxide (CAS 13463-67-7)

TRADE SECRET (CAS Proprietary)

US. Pennsylvania Worker and Community Right-to-Know Law

Crystalline silica (Quartz) (CAS 14808-60-7)

Kaolin (CAS 1332-58-7)

Limestone (CAS 1317-65-3)

Titanium dioxide (CAS 13463-67-7)

TRADE SECRET (CAS Proprietary)

US. Rhode Island RTK

Crystalline silica (Quartz) (CAS 14808-60-7)

Kaolin (CAS 1332-58-7)

Limestone (CAS 1317-65-3)

Titanium dioxide (CAS 13463-67-7)

TRADE SECRET (CAS Proprietary)

California Proposition 65



WARNING: This product can expose you to chemicals including Crystalline silica (Quartz), which is known to the State of California to cause cancer. For more information go to www.P65Warnings.ca.gov.

California Proposition 65 - CRT: Listed date/Carcinogenic substance

Crystalline silica (Quartz) (CAS 14808-60-7)

Listed: October 1, 1988

Titanium dioxide (CAS 13463-67-7)

Listed: September 2, 2011

US. California. Candidate Chemicals List. Safer Consumer Products Regulations (Cal. Code Regs, tit. 22, 69502.3, subd. (a))

Crystalline silica (Quartz) (CAS 14808-60-7)

Titanium dioxide (CAS 13463-67-7)

International Inventories

| Country(s) or region | Inventory name | On inventory (yes/no)* |
|-----------------------------|--|------------------------|
| Australia | Australian Inventory of Chemical Substances (AICS) | Yes |
| Canada | Domestic Substances List (DSL) | No |
| Canada | Non-Domestic Substances List (NDSL) | Yes |
| China | Inventory of Existing Chemical Substances in China (IECSC) | Yes |
| Europe | European Inventory of Existing Commercial Chemical Substances (EINECS) | No |
| Europe | European List of Notified Chemical Substances (ELINCS) | No |
| Japan | Inventory of Existing and New Chemical Substances (ENCS) | No |
| Korea | Existing Chemicals List (ECL) | Yes |
| New Zealand | New Zealand Inventory | Yes |
| Philippines | Philippine Inventory of Chemicals and Chemical Substances (PICCS) | Yes |
| Taiwan | Taiwan Chemical Substance Inventory (TCSI) | Yes |
| United States & Puerto Rico | Toxic Substances Control Act (TSCA) Inventory | Yes |

*A "Yes" indicates this product complies with the inventory requirements administered by the governing country(s).

A "No" indicates that one or more components of the product are not listed or exempt from listing on the inventory administered by the governing country(s).

16. Other information, including date of preparation or last revision

Issue date 13-November-2020

Revision date 09-December-2020

Version # 02

Further information Titanium dioxide: In lifetime inhalation studies of experimental rats, airborne nano-sized (15-40 nanometer particle size range) particles caused lung tissue overload, chronic inflammation and subsequent tumor formation. Because of these study results, titanium dioxide was classified by IARC as a 2B (possibly carcinogenic to humans). However, other laboratory animals such as mice and hamsters did not develop lung tumors under similar testing conditions. Furthermore, results of two major human epidemiology studies among titanium dioxide workers in the US and in Europe did not demonstrate an elevated lung cancer risk, and did not suggest an association between occupational exposure to titanium dioxide and risk for cancer.

Skin Sensitization Potential: This product contains an amount of Triazinetriethanol (THT) (CAS No. 4719-04-4) that is within the approved EPA regulated limits. THT can act as a sensitizer. Numerous human studies with concentrations up to 1% yielded negative (no sensitization) results. However, some results showed positive reactions in concentrations <0.5% mostly in persons with eczema.

NFPA Ratings:
Health: 1
Flammability: 0
Physical hazard: 0

Hazard Scale: 0 = Minimal 1 = Slight 2 = Moderate 3 = Serious 4 = Severe

NFPA ratings



Disclaimer

This information is provided without warranty. The information is believed to be correct. This information should be used to make an independent determination of the methods to safeguard workers and the environment.