



SAFETY DATA SHEET

1. Identification

Product identifier SHEETROCK® Brand MH Speed-Tex™ Ready-Mixed Spray Texture

Other means of identification

SDS number 48000010001

Synonyms Spray Texture

Recommended use Interior use.

Recommended restrictions Use in accordance with manufacturer's recommendations.

Manufacturer/Importer/Supplier/Distributor information

Company name United States Gypsum Company

Address 550 West Adams Street
Chicago, Illinois 60661-3637

Telephone 1-800-874-4968

Website www.usg.com

Emergency phone number 1-800-507-8899

2. Hazard(s) identification

Physical hazards Not classified.

Health hazards Carcinogenicity Category 1A

OSHA defined hazards Not classified.

Label elements



Signal word Danger

Hazard statement May cause cancer.

Precautionary statement

Prevention Obtain special instructions before use. Do not handle until all safety precautions have been read and understood. Wear protective gloves/protective clothing/eye protection/face protection.

Response If exposed or concerned: Get medical advice/attention.

Storage Store locked up.

Disposal Dispose of contents/container in accordance with local/regional/national/international regulations.

Hazard(s) not otherwise classified (HNOC) None known.

Supplemental information None.

3. Composition/information on ingredients

Mixtures

Chemical name	CAS number	%
Limestone	1317-65-3	< 60
Attapulgite	12174-11-7	< 5
1,3,5-tris(2-hydroxyethyl)hexahydro-1,3,5-triazine	4719-04-4	< 0.2

Impurities

Chemical name	CAS number	%
Crystalline silica (Quartz)	14808-60-7	< 1

Composition comments All concentrations are in percent by weight.

Raw materials in this product contain respirable crystalline silica as an impurity. The weight percent of respirable crystalline silica found in this product is < 1%. Exposures to respirable crystalline silica during the normal use of this product must be determined by workplace hygiene testing.

4. First-aid measures

Inhalation Dust irritates the respiratory system, and may cause coughing and difficulties in breathing. Move injured person into fresh air and keep person calm under observation. Get medical attention if symptoms persist.

Skin contact Contact with dust: Rinse area with plenty of water. Get medical attention if irritation develops or persists.

Eye contact Dust in the eyes: Do not rub eyes. Flush thoroughly with water. If irritation occurs, get medical assistance.

Ingestion Rinse mouth. Get medical attention if symptoms occur.

Most important symptoms/effects, acute and delayed Under normal conditions of intended use, this product is not expected to be a health risk. Dust may irritate throat and respiratory system and cause coughing. Prolonged exposure may cause chronic effects.

Indication of immediate medical attention and special treatment needed Provide general supportive measures and treat symptomatically.

General information Ensure that medical personnel are aware of the material(s) involved.

5. Fire-fighting measures

Suitable extinguishing media Use fire-extinguishing media appropriate for surrounding materials.

Unsuitable extinguishing media Not applicable.

Specific hazards arising from the chemical Not a fire hazard.

Special protective equipment and precautions for firefighters Selection of respiratory protection for firefighting: follow the general fire precautions indicated in the workplace. Self-contained breathing apparatus and full protective clothing must be worn in case of fire.

Fire fighting equipment/instructions Use standard firefighting procedures and consider the hazards of other involved materials.

Specific methods Cool material exposed to heat with water spray and remove it if no risk is involved.

General fire hazards No unusual fire or explosion hazards noted.

6. Accidental release measures

Personal precautions, protective equipment and emergency procedures Avoid inhalation of dust and contact with skin and eyes. See Section 8 of the SDS for Personal Protective Equipment.

Methods and materials for containment and cleaning up Large Spills: Scoop spilled materials and recover as much of the product as possible for use. If spillage is unrecoverable dispose according to local, state, and federal regulations.

Small Spills: Wipe up with absorbent material (e.g. cloth, fleece). Clean surface thoroughly to remove residual contamination.

Environmental precautions Avoid discharge to drains, sewers, and other water systems.

7. Handling and storage

Precautions for safe handling Avoid inhalation of dust and contact with skin and eyes. Minimize dust generation and accumulation. In case of insufficient ventilation, wear suitable respiratory equipment. Observe good industrial hygiene practices. Use proper lifting techniques.

Conditions for safe storage, including any incompatibilities Store in a cool, dry place. Store in a closed container away from incompatible materials. Protect from moisture. Keep away from heat. Do not use if material has spoiled, i.e., there is a moldy appearance or an unpleasant odor. Keep containers closed when not in use.

8. Exposure controls/personal protection

Occupational exposure limits

US. OSHA Specifically Regulated Substances (29 CFR 1910.1001-1053)

Impurities	Type	Value
Crystalline silica (Quartz) (CAS 14808-60-7)	TWA	0.05 mg/m ³

US. OSHA Table Z-1 Limits for Air Contaminants (29 CFR 1910.1000)

Components	Type	Value	Form
Limestone (CAS 1317-65-3)	PEL	5 mg/m ³	Respirable fraction.
		15 mg/m ³	Total dust.

US. OSHA Table Z-3 (29 CFR 1910.1000)

Impurities	Type	Value	Form
Crystalline silica (Quartz) (CAS 14808-60-7)	TWA	0.1 mg/m ³	Respirable.
		2.4 mppcf	Respirable.

US. ACGIH Threshold Limit Values

Impurities	Type	Value	Form
Crystalline silica (Quartz) (CAS 14808-60-7)	TWA	0.025 mg/m ³	Respirable fraction.

US. NIOSH: Pocket Guide to Chemical Hazards

Components	Type	Value	Form
Limestone (CAS 1317-65-3)	TWA	5 mg/m ³	Respirable.
		10 mg/m ³	Total

Impurities	Type	Value	Form
Crystalline silica (Quartz) (CAS 14808-60-7)	TWA	0.05 mg/m ³	Respirable dust.

Biological limit values

No biological exposure limits noted for the ingredient(s).

Exposure guidelines

Occupational exposure to nuisance dust (total and respirable) and respirable crystalline silica should be monitored and controlled.

Appropriate engineering controls

Provide sufficient ventilation for operations causing dust formation. Observe occupational exposure limits and minimize the risk of exposure.

Individual protection measures, such as personal protective equipment

Eye/face protection

Wear approved safety goggles.

Skin protection

Hand protection

It is a good industrial hygiene practice to minimize skin contact. For prolonged or repeated skin contact use suitable protective gloves.

Skin protection

Other

Normal work clothing (long sleeved shirts and long pants) is recommended.

Respiratory protection

If engineering controls do not maintain airborne concentrations below recommended exposure limits (where applicable) or to an acceptable level (in countries where exposure limits have not been established), an approved respirator must be worn. Use a NIOSH/MSHA approved air purifying respirator as needed to control exposure. Consult with respirator manufacturer to determine respirator selection, use, and limitations. Use positive pressure, air-supplied respirator for uncontrolled releases or when air purifying respirator limitations may be exceeded. Follow respirator protection program requirements (OSHA 1910.134 and ANSI Z88.2) for all respirator use.

Thermal hazards

None.

General hygiene considerations

Always observe good personal hygiene measures, such as washing after handling the material and before eating, drinking, and/or smoking. Routinely wash work clothing and protective equipment separately from regular wash. Observe any medical surveillance requirements.

9. Physical and chemical properties

Appearance

Physical state	Solid.
----------------	--------

Form	Paste.
Color	Off-white.
Odor	Low to no odor.
Odor threshold	Not applicable.
pH	8.5 - 10
Melting point/freezing point	32 °F (0 °C)
Initial boiling point and boiling range	212 °F (100 °C)
Flash point	Not applicable.
Evaporation rate	Not applicable.
Flammability (solid, gas)	Not applicable.
Upper/lower flammability or explosive limits	
Flammability limit - lower (%)	Not applicable.
Flammability limit - upper (%)	Not applicable.
Explosive limit - lower (%)	Not applicable.
Explosive limit - upper (%)	Not applicable.
Vapor pressure	Not applicable.
Vapor density	Not applicable.
Relative density	1.5 - 1.7 (H ₂ O=1)
Solubility(ies)	
Solubility (water)	Soluble in water.
Partition coefficient (n-octanol/water)	Not applicable.
Auto-ignition temperature	Not applicable.
Decomposition temperature	Not applicable.
Viscosity	300 - 840 Brabender units (20 °C)
Other information	
Bulk density	12.5 - 14.2 lb/gal
Explosive properties	Not explosive.
Oxidizing properties	Not oxidizing.
VOC	< 2 g/l (Calculated by EPA Method 24)

10. Stability and reactivity

Reactivity	The product is stable and non-reactive under normal conditions of use, storage and transport.
Chemical stability	Material is stable under normal conditions.
Possibility of hazardous reactions	No dangerous reaction known under conditions of normal use.
Conditions to avoid	None known.
Incompatible materials	None known.
Hazardous decomposition products	Above 1472°F (800°C) limestone (CaCO ₃) can decompose to lime (CaO) and release carbon dioxide (CO ₂).

11. Toxicological information

Information on likely routes of exposure

Inhalation	Inhalation of dusts may cause respiratory irritation. Prolonged and repeated exposure to airborne respirable crystalline silica can cause silicosis and/or lung cancer.
Skin contact	May cause allergic skin reactions especially in individuals with pre-existing skin disease such as eczema. (See Section 16).
Eye contact	Airborne dust may cause mechanical eye irritation.
Ingestion	May cause discomfort if swallowed.

Symptoms related to the physical, chemical and toxicological characteristics	Dust may irritate eyes and mucous membranes of the nose, throat and upper respiratory system causing sneezing and/or coughing. Prolonged exposure may cause chronic effects.
Information on toxicological effects	
Acute toxicity	Not expected to be acutely toxic.
Skin corrosion/irritation	Prolonged or repeated skin contact may cause drying, cracking, or irritation.
Serious eye damage/eye irritation	Direct contact with eyes may cause temporary irritation.
Respiratory or skin sensitization	
Respiratory sensitization	Not a respiratory sensitizer.
Skin sensitization	The product contains a small amount of sensitizing substance which may provoke an allergic reaction among sensitive individuals after repeated contact. For detailed information, see section 16.
Germ cell mutagenicity	No data available to indicate product or any components present at greater than 0.1% are mutagenic or genotoxic.
Carcinogenicity	Repeated and prolonged exposures to high levels of respirable crystalline silica may cause cancer.
IARC Monographs. Overall Evaluation of Carcinogenicity	
Attapulgit (CAS 12174-11-7)	2B Possibly carcinogenic to humans. 3 Not classifiable as to carcinogenicity to humans.
Crystalline silica (Quartz) (CAS 14808-60-7)	1 Carcinogenic to humans.
NTP Report on Carcinogens	
Crystalline silica (Quartz) (CAS 14808-60-7)	Known To Be Human Carcinogen.
OSHA Specifically Regulated Substances (29 CFR 1910.1001-1053)	
Crystalline silica (Quartz) (CAS 14808-60-7)	Cancer
Reproductive toxicity	Not expected to be a reproductive hazard.
Specific target organ toxicity - single exposure	No data available, but none expected.
Specific target organ toxicity - repeated exposure	Not classified. For detailed information, see section 16.
Aspiration hazard	Not an aspiration hazard.
Chronic effects	Prolonged and routine inhalation of high levels of respirable crystalline silica particles can lead to the lung disease known as silicosis. Some studies show excess numbers of cases of scleroderma, connective tissue disorders, lupus, rheumatoid arthritis, chronic kidney diseases and end-stage kidney disease in workers exposed to respirable crystalline silica. Pre-existing skin and respiratory conditions including dermatitis, asthma and chronic lung disease might be aggravated by exposure. Occupational exposure to respirable dust and respirable crystalline silica should be monitored and controlled.

12. Ecological information

Ecotoxicity	The product is not classified as environmentally hazardous. However, this does not exclude the possibility that large or frequent spills can have a harmful or damaging effect on the environment.
Persistence and degradability	No data available.
Bioaccumulative potential	Bioaccumulation is not expected.
Mobility in soil	No data available.
Other adverse effects	None expected.

13. Disposal considerations

Disposal instructions	Dispose in accordance with applicable federal, state, and local regulations. Recycle responsibly.
Local disposal regulations	Dispose of in accordance with local regulations.
Hazardous waste code	The waste code should be assigned in discussion between the user, the producer and the waste disposal company.
Waste from residues / unused products	Dispose of in accordance with local regulations.
Contaminated packaging	Dispose of in accordance with local regulations.

14. Transport information

DOT

Not regulated as dangerous goods.

IATA

Not regulated as dangerous goods.

IMDG

Not regulated as dangerous goods.

Transport in bulk according to Annex II of MARPOL 73/78 and the IBC Code Not applicable.

15. Regulatory information

US federal regulations This product is a "Hazardous Chemical" as defined by the OSHA Hazard Communication Standard, 29 CFR 1910.1200.

TSCA Section 12(b) Export Notification (40 CFR 707, Subpt. D)

Not regulated.

CERCLA Hazardous Substance List (40 CFR 302.4)

Not listed.

SARA 304 Emergency release notification

Not regulated.

OSHA Specifically Regulated Substances (29 CFR 1910.1001-1053)

Crystalline silica (Quartz) (CAS 14808-60-7)	Cancer lung effects immune system effects kidney effects
--	---

Toxic Substances Control Act (TSCA)

All components on the TSCA 8(b) inventory are designated "active" or are exempt from reporting under the Inventory Update Rule.

Superfund Amendments and Reauthorization Act of 1986 (SARA)

SARA 302 Extremely hazardous substance

Not listed.

SARA 311/312 Hazardous chemical Yes

Classified hazard categories Carcinogenicity

SARA 313 (TRI reporting)

Not regulated.

Other federal regulations

Clean Air Act (CAA) Section 112 Hazardous Air Pollutants (HAPs) List

Not regulated.

Clean Air Act (CAA) Section 112(r) Accidental Release Prevention (40 CFR 68.130)

Not regulated.

Safe Drinking Water Act (SDWA) Not regulated.

US state regulations

US. Massachusetts RTK - Substance List

Crystalline silica (Quartz) (CAS 14808-60-7)
Limestone (CAS 1317-65-3)

US. New Jersey Worker and Community Right-to-Know Act

Crystalline silica (Quartz) (CAS 14808-60-7)
Limestone (CAS 1317-65-3)

US. Pennsylvania Worker and Community Right-to-Know Law

Crystalline silica (Quartz) (CAS 14808-60-7)
Limestone (CAS 1317-65-3)

US. Rhode Island RTK

Crystalline silica (Quartz) (CAS 14808-60-7)
Limestone (CAS 1317-65-3)

California Proposition 65



WARNING: This product can expose you to chemicals including Attapulgite, which is known to the State of California to cause cancer. For more information go to www.P65Warnings.ca.gov.

California Proposition 65 - CRT: Listed date/Carcinogenic substance

Attapulgite (CAS 12174-11-7) Listed: December 28, 1999
Crystalline silica (Quartz) (CAS 14808-60-7) Listed: October 1, 1988

US. California. Candidate Chemicals List. Safer Consumer Products Regulations (Cal. Code Regs, tit. 22, 69502.3, subd. (a))

Attapulgite (CAS 12174-11-7)
Crystalline silica (Quartz) (CAS 14808-60-7)

International Inventories

Country(s) or region	Inventory name	On inventory (yes/no)*
United States & Puerto Rico	Toxic Substances Control Act (TSCA) Inventory	No

*A "Yes" indicates this product complies with the inventory requirements administered by the governing country(s).

A "No" indicates that one or more components of the product are not listed or exempt from listing on the inventory administered by the governing country(s).

16. Other information, including date of preparation or last revision

Issue date 31-January-2014

Revision date 21-January-2020

Version # 02

Further information Crystalline silica: Raw materials in this product contain respirable crystalline silica as an impurity. Exposures to respirable crystalline silica are not expected during the normal use of this product. However, actual levels must be determined by workplace hygiene testing. Prolonged and repeated exposure to airborne free respirable crystalline silica can result in lung disease (i.e., silicosis) and/or lung cancer.

Attapulgite: Carcinogenic to experimental animals via a route of exposure not relevant to human exposure per ACGIH.

Skin Sensitization Potential: This product contains an amount of Triazinetriethanol (THT) (CAS No. 4719-04-4) that is within the approved EPA regulated limits. THT can act as a sensitizer. Numerous human studies with concentrations up to 1% yielded negative (no sensitization) results. However, some results showed positive reactions in concentrations <0.5% mostly in persons with eczema.

NFPA Ratings:
Health: 1
Flammability: 0
Physical hazard: 0

Hazard Scale: 0 = Minimal 1 = Slight 2 = Moderate 3 = Serious 4 = Severe

NFPA ratings



Disclaimer

This information is provided without warranty. The information is believed to be correct. This information should be used to make an independent determination of the methods to safeguard workers and the environment.