SAFETY DATA SHEET

1. Identification

Product identifier USG Sof'n-Soil® Lawn & Garden Gypsum

Other means of identification

5200000135 SDS number **Synonyms** Gypsum

Recommended use Lawn and Garden Applications.

Recommended restrictions Use in accordance with manufacturer's recommendations.

Manufacturer/Importer/Supplier/Distributor information

Company name United States Gypsum Company

Address 550 West Adams Street

Chicago, Illinois 60661-3637

1-800-874-4968 Telephone Website www.usg.com **Emergency phone number** 1-800-507-8899

2. Hazard(s) identification

Not classified. **Physical hazards**

Health hazards Carcinogenicity (inhalation) Category 1A

OSHA defined hazards Not classified.

Label elements



Signal word

Hazard statement May cause cancer by inhalation.

Precautionary statement

Prevention Obtain special instructions before use. Do not handle until all safety precautions have been read

and understood. Avoid breathing dust. Wear protective gloves/protective clothing/eye

protection/face protection.

If exposed or concerned: Get medical advice/attention. Response

Storage Store locked up.

Dispose of contents/container in accordance with local/regional/national/international regulations. **Disposal**

Hazard(s) not otherwise

classified (HNOC)

None known.

Supplemental information None.

3. Composition/information on ingredients

Mixtures

Chemical name	CAS number	%
Calcium sulfate dihydrate (alternative CAS 10101-41-4)	13397-24-5	> 95

Impurities

Chemical name	Common name and synonyms	CAS number	%	
Crystalline silica (Quartz)		14808-60-7	< 0.60	

SDS US 1/8 920093 Version #: 02 Revision date: 29-July-2024 Issue date: 03-November-2017

Composition comments

All concentrations are in percent by weight. The exact concentrations of the above listed chemicals are being withheld as a trade secret.

Raw materials in this product contain respirable crystalline silica as an impurity. The weight percent of respirable crystalline silica found in this product is < 0.60%. Exposures to respirable crystalline silica during the normal use of this product must be determined by workplace hygiene testing.

4. First-aid measures

Inhalation

Move to fresh air. Call a physician if symptoms develop or persist.

Skin contact Eye contact

Wash off with soap and water. Get medical attention if irritation develops and persists. Do not rub eyes. Rinse with water. Get medical attention if irritation develops and persists.

Ingestion

Rinse mouth. Get medical attention if symptoms occur.

Most important

Dusts may irritate the respiratory tract, skin and eyes.

symptoms/effects, acute and delayed

Indication of immediate medical attention and special treatment needed

Provide general supportive measures and treat symptomatically. Keep victim under observation. Symptoms may be delayed.

General information

IF exposed or concerned: Get medical advice/attention. Ensure that medical personnel are aware of the material(s) involved, and take precautions to protect themselves.

5. Fire-fighting measures

Suitable extinguishing media

Unsuitable extinguishing media

Water fog. Foam. Dry chemical powder. Carbon dioxide (CO2). Do not use water jet as an extinguisher, as this will spread the fire.

Specific hazards arising from

the chemical

During fire, gases hazardous to health may be formed.

Special protective equipment and precautions for firefighters Self-contained breathing apparatus and full protective clothing must be worn in case of fire.

Fire fighting

Use water spray to cool unopened containers.

equipment/instructions Specific methods

Use standard firefighting procedures and consider the hazards of other involved materials.

General fire hazards

No unusual fire or explosion hazards noted.

6. Accidental release measures

Personal precautions, protective equipment and emergency procedures

Keep unnecessary personnel away. Keep people away from and upwind of spill/leak. Wear appropriate protective equipment and clothing during clean-up. Avoid inhalation of dust. Use a NIOSH/MSHA approved respirator if there is a risk of exposure to dust/fume at levels exceeding the exposure limits. Ensure adequate ventilation. Local authorities should be advised if significant spillages cannot be contained. For personal protection, see section 8 of the SDS.

Methods and materials for containment and cleaning up Avoid dispersal of dust in the air (i.e., clearing dust surfaces with compressed air). Collect dust using a vacuum cleaner equipped with HEPA filter. Stop the flow of material, if this is without risk.

Large Spills: Wet down with water and dike for later disposal. Shovel the material into waste container. Following product recovery, flush area with water.

Small Spills: Sweep up or vacuum up spillage and collect in suitable container for disposal.

Never return spills to original containers for re-use. Put material in suitable, covered, labeled containers. For waste disposal, see section 13 of the SDS.

Environmental precautions

Avoid discharge into drains, water courses or onto the ground.

7. Handling and storage

Precautions for safe handling

Obtain special instructions before use. Do not handle until all safety precautions have been read and understood. Minimize dust generation and accumulation. Provide appropriate exhaust ventilation at places where dust is formed. Avoid breathing dust. Avoid prolonged exposure. Should be handled in closed systems, if possible. Wear appropriate personal protective equipment. Observe good industrial hygiene practices.

Conditions for safe storage, including any incompatibilities Store locked up. Store in tightly closed container. Store in a well-ventilated place. Store away from incompatible materials (see Section 10 of the SDS).

USG Sof'n-Soil® Lawn & Garden Gypsum 2/8 920093 Version #: 02 Revision date: 29-July-2024 Issue date: 03-November-2017

8. Exposure controls/personal protection

Occupational exposure limits

JS. OSHA Specifically Regulated Substar mpurities	Type	Value	
Crystalline silica (Quartz) CAS 14808-60-7)	TWA	0.05 mg/m3	
JS. OSHA Table Z-1 Permissible Exposur Components	e Limits (PEL) for Air Contamina Type	ants (29 CFR 1910.10 Value	00) Form
Calcium sulfate dihydrate alternative CAS 10101-41-4) (CAS 13397-24-5)	PEL	5 mg/m3	Respirable fraction.
		15 mg/m3	Total dust.
IS. OSHA Table Z-3 Permissible Exposur Components	e Limits (PEL) for Mineral Dusts Type	(29 CFR 1910.1000) Value	Form
Calcium sulfate dihydrate alternative CAS 0101-41-4) (CAS 13397-24-5)	TWA	5 mg/m3	Respirable fraction.
,		15 mg/m3	Total dust.
		50 mppcf	Total dust.
		15 mppcf	Respirable fraction.
mpurities	Туре	Value	Form
Crystalline silica (Quartz) CAS 14808-60-7)	TWA	0.1 mg/m3	Respirable.
		2.4 mppcf	Respirable.
US. ACGIH Threshold Limit Values (TLV)			
Components	Туре	Value	Form
Calcium sulfate dihydrate (alternative CAS 10101-41-4) (CAS 13397-24-5)	TWA	10 mg/m3	Inhalable fraction.
mpurities	Туре	Value	Form
Crystalline silica (Quartz) CAS 14808-60-7)	TWA	0.025 mg/m3	Respirable fraction.
NIOSH. Immediately Dangerous to Life or impurities	Health (IDLH) Values, as amend Type	led Value	
•			
Crystalline silica (Quartz) CAS 14808-60-7)	IDLH .	50 mg/m3	
US. NIOSH: Pocket Guide to Chemical Ha Components	zards Type	Value	Form
Calcium sulfate dihydrate (alternative CAS 10101-41-4) (CAS 13397-24-5)	TWA	5 mg/m3	Respirable.
		10 mg/m3	Total
mpurities	Туре	Value	Form
Crystalline silica (Quartz) (CAS 14808-60-7)	TWA	0.05 mg/m3	Respirable dust.

Biological limit values No biological exposure limits noted for the ingredient(s).

USG Sof'n-Soil® Lawn & Garden Gypsum

SDS US

920093 Version #: 02 Revision date: 29-July-2024 Issue date: 03-November-2017

Appropriate engineering controls

Good general ventilation should be used. Ventilation rates should be matched to conditions. If applicable, use process enclosures, local exhaust ventilation, or other engineering controls to maintain airborne levels below recommended exposure limits. If exposure limits have not been established, maintain airborne levels to an acceptable level. If engineering measures are not sufficient to maintain concentrations of dust particulates below the Occupational Exposure Limit (OEL), suitable respiratory protection must be worn. If material is ground, cut, or used in any operation which may generate dusts, use appropriate local exhaust ventilation to keep exposures below the recommended exposure limits.

Individual protection measures, such as personal protective equipment

Wear safety glasses with side shields (or goggles). Eye/face protection

Skin protection

Hand protection Wear appropriate chemical resistant gloves.

Skin protection

Use of an impervious apron is recommended. Other

Use a NIOSH/MSHA approved respirator if there is a risk of exposure to dust/fume at levels Respiratory protection

exceeding the exposure limits. Chemical respirator with organic vapor cartridge, full facepiece,

dust and mist filter.

Thermal hazards Wear appropriate thermal protective clothing, when necessary.

General hygiene considerations

Observe any medical surveillance requirements. Always observe good personal hygiene measures, such as washing after handling the material and before eating, drinking, and/or smoking. Routinely wash work clothing and protective equipment to remove contaminants.

9. Physical and chemical properties

Appearance

Solid. **Physical state Form** Powder.

Color White to off-white. Odor Low to no odor. Odor threshold Not applicable.

6 - 8

Not applicable. Melting point/freezing point

Not applicable.

Initial boiling point and boiling

range

Not applicable.

Flash point Not applicable. **Evaporation rate** Not applicable. Flammability (solid, gas) Not available. Upper/lower flammability or explosive limits Explosive limit - lower (%) Not applicable.

Explosive limit - upper (%) Not applicable. Vapor pressure Not applicable. Vapor density Not applicable. 2.96 (H2O=1) Relative density

Solubility(ies)

0.15 - 0.4 g/100 g (H2O) Solubility (water)

Partition coefficient Not applicable.

(n-octanol/water)

Auto-ignition temperature Not applicable. 2642 °F (1450 °C) **Decomposition temperature** Not applicable. **Viscosity**

Other information

55 - 70 lb/ft3 **Bulk density** Not explosive. **Explosive properties** Oxidizing properties Not oxidizing.

USG Sof'n-Soil® Lawn & Garden Gypsum SDS US 920093 Version #: 02 Revision date: 29-July-2024

Particle size Varies. 0 % VOC

10. Stability and reactivity

Reactivity The product is stable and non-reactive under normal conditions of use, storage and transport.

Material is stable under normal conditions. Chemical stability

Possibility of hazardous

reactions

No dangerous reaction known under conditions of normal use.

Conditions to avoid Avoid temperatures exceeding the decomposition temperature. Contact with incompatible

materials. Exposure to moisture.

Incompatible materials Strong oxidizing agents. Acids.

Hazardous decomposition

products

Calcium oxides, carbon dioxide, and carbon monoxide.

11. Toxicological information

Information on likely routes of exposure

Inhalation May cause cancer by inhalation. Dust may irritate respiratory system.

Dust or powder may irritate the skin. Skin contact

Dust may irritate the eyes. Eye contact

Ingestion May cause discomfort if swallowed.

Symptoms related to the physical, chemical and toxicological characteristics Dusts may irritate the respiratory tract, skin and eyes. Prolonged exposure may cause chronic

effects.

Information on toxicological effects

Not expected to be acutely toxic. **Acute toxicity**

Skin corrosion/irritation Prolonged skin contact may cause temporary irritation. Serious eye damage/eye Direct contact with eyes may cause temporary irritation.

irritation

Respiratory or skin sensitization

Respiratory sensitization Not a respiratory sensitizer.

Skin sensitization This product is not expected to cause skin sensitization.

Germ cell mutagenicity No data available to indicate product or any components present at greater than 0.1% are

mutagenic or genotoxic.

Carcinogenicity May cause cancer.

IARC Monographs. Overall Evaluation of Carcinogenicity

Crystalline silica (Quartz) (CAS 14808-60-7) 1 Carcinogenic to humans.

NTP Report on Carcinogens

Crystalline silica (Quartz) (CAS 14808-60-7) Known To Be Human Carcinogen.

OSHA Specifically Regulated Substances (29 CFR 1910.1001-1053)

Crystalline silica (Quartz) (CAS 14808-60-7)

Reproductive toxicity This product is not expected to cause reproductive or developmental effects.

Specific target organ toxicity -

single exposure

Not classified.

Specific target organ toxicity -

repeated exposure

Not classified.

Aspiration hazard Not an aspiration hazard.

Chronic effects Prolonged inhalation may be harmful.

12. Ecological information

The product is not classified as environmentally hazardous. However, this does not exclude the **Ecotoxicity**

possibility that large or frequent spills can have a harmful or damaging effect on the environment.

920093 Version #: 02 Revision date: 29-July-2024 Issue date: 03-November-2017 Components **Test Results Species**

Calcium sulfate dihydrate (alternative CAS 10101-41-4) (CAS 13397-24-5)

Aquatic

Fish LC50 Fathead minnow (Pimephales promelas) > 1970 mg/l, 96 hours

Persistence and degradability Calcium sulfate dissolves in water forming calcium and sulfate ions.

Bioaccumulation is not expected. Bioaccumulative potential

Mobility in soil No data available. No data available. Other adverse effects

13. Disposal considerations

Disposal instructions Collect and reclaim or dispose in sealed containers at licensed waste disposal site. Dispose of

contents/container in accordance with local/regional/national/international regulations.

Local disposal regulations Dispose in accordance with all applicable regulations.

The waste code should be assigned in discussion between the user, the producer and the waste Hazardous waste code

disposal company.

Waste from residues / unused

Contaminated packaging

products

Dispose of in accordance with local regulations. Empty containers or liners may retain some product residues. This material and its container must be disposed of in a safe manner.

Since emptied containers may retain product residue, follow label warnings even after container is

emptied. Empty containers should be taken to an approved waste handling site for recycling or

disposal.

14. Transport information

DOT

Not regulated as dangerous goods.

IATA

Not regulated as dangerous goods.

IMDG

Not regulated as dangerous goods.

Not applicable. Transport in bulk according to

Annex II of MARPOL 73/78 and

the IBC Code

15. Regulatory information

This product is a "Hazardous Chemical" as defined by the OSHA Hazard Communication **US federal regulations**

Standard, 29 CFR 1910.1200.

TSCA Section 12(b) Export Notification (40 CFR 707, Subpt. D)

Not regulated.

CERCLA Hazardous Substance List (40 CFR 302.4)

Not listed.

SARA 304 Emergency release notification

Not regulated.

OSHA Specifically Regulated Substances (29 CFR 1910.1001-1053)

Crystalline silica (Quartz) (CAS 14808-60-7) Cancer

luna effects

immune system effects

kidney effects

Toxic Substances Control Act (TSCA) All components of the mixture on the TSCA 8(b) inventory are designated

"active".

Superfund Amendments and Reauthorization Act of 1986 (SARA)

SARA 302 Extremely hazardous substance

Not listed.

SARA 311/312 Hazardous

Yes

chemical

Classified hazard

categories

Carcinogenicity

SARA 313 (TRI reporting)

Not regulated.

Other federal regulations

Clean Air Act (CAA) Section 112 Hazardous Air Pollutants (HAPs) List

Not regulated.

Clean Air Act (CAA) Section 112(r) Accidental Release Prevention (40 CFR 68.130)

Not regulated.

Safe Drinking Water Act

Not regulated.

(SDWA)

US state regulations

US. Massachusetts RTK - Substance List

Calcium sulfate dihydrate (alternative CAS 10101-41-4) (CAS 13397-24-5)

Crystalline silica (Quartz) (CAS 14808-60-7)

US. New Jersey Worker and Community Right-to-Know Act

Calcium sulfate dihydrate (alternative CAS 10101-41-4) (CAS 13397-24-5)

Crystalline silica (Quartz) (CAS 14808-60-7)

US. Pennsylvania Worker and Community Right-to-Know Law

Calcium sulfate dihydrate (alternative CAS 10101-41-4) (CAS 13397-24-5)

Crystalline silica (Quartz) (CAS 14808-60-7)

US. Rhode Island RTK

Calcium sulfate dihydrate (alternative CAS 10101-41-4) (CAS 13397-24-5)

Crystalline silica (Quartz) (CAS 14808-60-7)

California Proposition 65



WARNING: This product can expose you to Crystalline silica (Quartz), which is known to the State of California

to cause cancer. For more information go to www.P65Warnings.ca.gov.

California Proposition 65 - CRT: Listed date/Carcinogenic substance

Crystalline silica (Quartz) (CAS 14808-60-7) Listed: October 1, 1988

International Inventories

Country(s) or region	Inventory name On inver	ntory (yes/no)*			
Australia	Australian Inventory of Industrial Chemicals (AICIS)	Yes			
Canada	Domestic Substances List (DSL)	Yes			
Canada	Non-Domestic Substances List (NDSL)	No			
China	Inventory of Existing Chemical Substances in China (IECSC)	Yes			
Europe	European Inventory of Existing Commercial Chemical Substances (EINECS)	Yes			
Europe	European List of Notified Chemical Substances (ELINCS)	No			
Japan	Inventory of Existing and New Chemical Substances (ENCS)	Yes			
Korea	Existing Chemicals List (ECL)	Yes			
New Zealand	New Zealand Inventory	Yes			
Philippines	Philippine Inventory of Chemicals and Chemical Substances (PICCS)	Yes			
Taiwan	Taiwan Chemical Substance Inventory (TCSI)	No			
United States & Puerto Rico	Toxic Substances Control Act (TSCA) Inventory	Yes			
*A "Yes" indicates that all components of this product comply with the inventory requirements administered by the governing country(s)					

16. Other information, including date of preparation or last revision

Issue date 03-November-2017 **Revision date** 29-July-2024

Version # 02

7/8 920093 Version #: 02 Revision date: 29-July-2024 Issue date: 03-November-2017

A "No" indicates that one or more components of the product are not listed or exempt from listing on the inventory administered by the governing

Further information

Crystalline silica: Raw materials in this product contain respirable crystalline silica as an impurity. Exposures to respirable crystalline silica are not expected during the normal use of this product. However, actual levels must be determined by workplace hygiene testing. Prolonged and repeated exposure to airborne free respirable crystalline silica can result in lung disease (i.e., silicosis) and/or lung cancer.

NFPA Ratings: Health: 1 Flammability: 0 Physical hazard: 0

Hazard Scale: 0 = Minimal 1 = Slight 2 = Moderate 3 = Serious 4 = Severe

NFPA ratings



Disclaimer

This information is provided without warranty. The information is believed to be correct. This information should be used to make an independent determination of the methods to safeguard workers and the environment.

USG Sof'n-Soil® Lawn & Garden Gypsum 920093 Version #: 02 Revision date: 29-July-2024 8/8 Issue date: 03-November-2017