# SAFETY DATA SHEET



#### 1. Identification

**Product identifier** STRUCTO-GAUGE® Gauging Plaster

Other means of identification

SDS number 53000010012 Synonyms Plaster Recommended use Interior use.

Use in accordance with manufacturer's recommendations. **Recommended restrictions** 

Manufacturer / Importer / Supplier / Distributor information

United States Gypsum Company Company name

550 West Adams Street **Address** 

Chicago, Illinois 60661-3637

**Telephone** 1-800-874-4968 Website www.usg.com 1-800-507-8899 **Emergency phone number** 

## 2. Hazard(s) identification

**Physical hazards** Not classified. **Health hazards** Not classified. Not classified. **OSHA** defined hazards

Label elements

None. **Hazard symbol** Signal word None. **Hazard statement** None.

**Precautionary statement** 

Prevention Observe good industrial hygiene practices. Response Get medical attention/advice if you feel unwell.

Storage Store as indicated in Section 7.

Dispose of in accordance with local, state, and federal regulations. Disposal

Hazard(s) not otherwise

classified (HNOC)

None known.

## 3. Composition/information on ingredients

# **Mixtures**

Chemical name	CAS number	%
Plaster of Paris (Calcium Sulfate Hemihydrate CAS 10034-76-1)	26499-65-0	> 90

**Composition comments** All concentrations are in percent by weight unless ingredient is a gas.

4. First-aid measures

Dust irritates the respiratory system, and may cause coughing and difficulties in breathing. Move Inhalation

injured person into fresh air and keep person calm under observation. Get medical attention if

symptoms persist.

Skin contact Contact with dust: Rinse area with plenty of water. Get medical attention if irritation develops or persists.

Dust in the eyes: Do not rub eyes. Flush thoroughly with water. If irritation occurs, get medical

Eye contact assistance.

Plaster of Paris hardens and if ingested may result in stomach and intestinal blockage. Drinking Ingestion

gelatin solutions or large volumes of water may delay setting.

Most important

symptoms/effects, acute and

delayed

Under normal conditions of intended use, this product is not expected to be a health risk. Dust may

irritate throat and respiratory system and cause coughing.

STRUCTO-GAUGE® Gauging Plaster 916483 Version #: 01 Revision date: -Issue date: 12-February-2014

1/6

Indication of immediate medical attention and special

treatment needed

**General information** Ensure that medical personnel are aware of the material(s) involved.

5. Fire-fighting measures

Suitable extinguishing media

Use fire-extinguishing media appropriate for surrounding materials.

Provide general supportive measures and treat symptomatically.

Unsuitable extinguishing

Not applicable.

Specific hazards arising from

the chemical

Not a fire hazard.

Special protective equipment and precautions for firefighters

Selection of respiratory protection for firefighting: follow the general fire precautions indicated in the workplace. Self-contained breathing apparatus and full protective clothing must be worn in

case of fire.

Fire-fighting

Specific methods

equipment/instructions

Use standard firefighting procedures and consider the hazards of other involved materials.

Cool material exposed to heat with water spray and remove it if no risk is involved.

6. Accidental release measures

Personal precautions, protective equipment and emergency procedures

See Section 8 of the SDS for Personal Protective Equipment.

Methods and materials for containment and cleaning up

Vacuum up the spilled material. Vacuums used for this purpose should be equipped with HEPA filters. Containers must be labeled. Collect in approved containers and seal securely. For waste

disposal, see Section 13 of the SDS.

**Environmental precautions** Avoid discharge to drains, sewers, and other water systems.

7. Handling and storage

Precautions for safe handling Minimize dust production when mixing, or opening and closing bags. Avoid inhalation of dust.

Wear appropriate personal protective equipment. Wash hands after handling. Observe good

industrial hygiene practices and use appropriate lifting techniques.

Conditions for safe storage, including any incompatibilities Store in a cool, dry, well-ventilated place. Store away from incompatible materials. Avoid contact

with acids, water, and moisture.

## 8. Exposure controls/personal protection

Occupational exposure limits

US. OSHA Table Z-1 Limits for Air Contaminants (29 CFR 1910.1000)

Components	Туре	Value	Form
Plaster of Paris (Calcium Sulfate Hemihydrate CAS 10034-76-1) (CAS 26499-65-0)	PEL	5 mg/m3	Respirable fraction.
		15 mg/m3	Total dust.

#### **US. ACGIH Threshold Limit Values**

Components	Туре	Value	Form
Plaster of Paris (Calcium	TWA	10 mg/m3	Inhalable fraction.
Sulfate Hemihydrate CAS			
10034-76-1) (CAS			

26499-65-0)

**US. NIOSH: Pocket Guide to Chemical Hazards** 

Components	Туре	Value	Form	
Plaster of Paris (Calcium Sulfate Hemihydrate CAS 10034-76-1) (CAS 26499-65-0)	TWA	5 mg/m3	Respirable.	
·		10 mg/m3	Total	

**Biological limit values** No biological exposure limits noted for the ingredient(s).

Appropriate engineering Provide sufficient ventilation for operations causing dust formation. Observe occupational

exposure limits and minimize the risk of exposure. controls

Individual protection measures, such as personal protective equipment

Eye/face protection Wear approved safety goggles.

STRUCTO-GAUGE® Gauging Plaster

Skin protection

Hand protection It is a good industrial hygiene practice to minimize skin contact. For prolonged or repeated skin

contact use suitable protective gloves.

Normal work clothing (long sleeved shirts and long pants) is recommended. Other

If engineering controls do not maintain airborne concentrations below recommended exposure Respiratory protection

limits (where applicable) or to an acceptable level (in countries where exposure limits have not been established), an approved respirator must be worn. Use a NIOSH/MSHA approved air purifying respirator as needed to control exposure. Consult with respirator manufacturer to determine respirator selection, use, and limitations. Use positive pressure, air-supplied respirator for uncontrolled releases or when air purifying respirator limitations may be exceeded. Follow respirator protection program requirements (OSHA 1910.134 and ANSI Z88.2) for all respirator

use.

Thermal hazards None.

**General hygiene** considerations

Always observe good personal hygiene measures, such as washing after handling the material and before eating, drinking, and/or smoking. Routinely wash work clothing and protective equipment separately from regular wash. Observe any medical surveillance requirements.

# 9. Physical and chemical properties

**Appearance** 

Solid. Physical state Powder. **Form** 

Color White to off-white. Odor Low to no odor. Not applicable. **Odor threshold** 

6 - 8 pН

Melting point/freezing point Not applicable.

Not applicable.

Initial boiling point and boiling

range

Not applicable.

Not applicable. Flash point **Evaporation rate** Not applicable. Flammability (solid, gas) Not applicable. Upper/lower flammability or explosive limits

Flammability limit - lower

Not applicable.

(%)

Flammability limit - upper

Not applicable.

(%)

Explosive limit - lower (%) Not applicable. Explosive limit - upper (%) Not applicable. Vapor pressure Not applicable. Vapor density Not applicable. Relative density 2.4 - 2.8 (H2O=1)

Solubility(ies)

Solubility (water) 0.15 - 0.4 g/100 g (H2O)

Partition coefficient Not applicable.

(n-octanol/water)

**Auto-ignition temperature** Not applicable. 2642 °F (1450 °C) **Decomposition temperature** 

**Viscosity** Not applicable.

Other information

45 - 55 lb/ft<sup>3</sup> **Bulk density** Particle size Varies. VOC (Weight %) 0 %

# 10. Stability and reactivity

Reactivity Not available.

Material is stable under normal conditions. Chemical stability Possibility of hazardous Hazardous polymerization does not occur.

reactions

Conditions to avoid When mixed with water this product can become very hot. Encasing or making moulds of any body

part can cause serious burns that may require surgical removal of affected tissue and even

amputation of encased body part.

Incompatible materials Acids. Exposure to water and acids must be supervised because the reactions are vigorous and

produce large amounts of heat.

Hazardous decomposition

products

Calcium oxides. Sulfur oxides.

# 11. Toxicological information

### Information on likely routes of exposure

Ingestion Ingestion may cause irritation and stomach discomfort.

Inhalation Airborne dust may irritate throat and upper respiratory system causing coughing. Skin contact Under normal conditions of intended use, this product does not pose a skin hazard.

Eye contact Direct contact with airborne particulates may cause temporary irritation.

Symptoms related to the physical, chemical and toxicological characteristics Dust may irritate eyes and mucous membranes of the nose, throat and upper respiratory system

causing sneezing and/or coughing.

#### Information on toxicological effects

**Acute toxicity** Not expected to be a hazard under normal conditions of intended use.

Skin corrosion/irritation Not a skin irritant.

Serious eye damage/eye

irritation

Direct contact with eyes may cause temporary irritation.

#### Respiratory or skin sensitization

Not expected to cause respiratory sensitization based on non-skin sensitization history. Respiratory sensitization

Skin sensitization Not a skin sensitizer. Plaster of Paris has displayed little sensitization potential.

No evidence of mutagenicty found in Ames bacterial tests. Germ cell mutagenicity

Carcinogenicity This material is not classified as a carcinogen by IARC, ACGIH, NTP or OSHA.

Not expected to be a reproductive hazard. Reproductive toxicity No data available, but none expected. Specific target organ toxicity -

single exposure

Specific target organ toxicity repeated exposure

No data available, but none expected.

**Aspiration hazard** Due to the physical form of the product it is not an aspiration hazard.

**Chronic effects** No other specific acute or chronic health impact noted.

# 12. Ecological information

**Ecotoxicity** The product components are not classified as environmentally hazardous. However, this does not

exclude the possibility that large or frequent spills can have a harmful or damaging effect on the

environment.

Components **Test Results Species** 

Plaster of Paris (Calcium Sulfate Hemihydrate CAS 10034-76-1) (CAS 26499-65-0)

Aquatic

Fish LC50 Fathead minnow (Pimephales promelas) > 1970 mg/l, 96 hours

Persistence and degradability Calcium sulfate dissolves in water forming calcium and sulfate ions.

Bioaccumulative potential Bioaccumulation is not expected. Mobility in soil No data available.

Other adverse effects None expected

#### 13. Disposal considerations

**Disposal instructions** Dispose in accordance with applicable federal, state, and local regulations. Recycle responsibly.

Local disposal regulations Dispose of in accordance with local regulations.

Not regulated. Hazardous waste code

Waste from residues / unused

products

Dispose of in accordance with local regulations.

Contaminated packaging Dispose of in accordance with local regulations.

STRUCTO-GAUGE® Gauging Plaster

SDS US

## 14. Transport information

DOT

Not regulated as dangerous goods.

**IATA** 

Not regulated as dangerous goods.

**IMDG** 

Not regulated as dangerous goods.

Transport in bulk according to Annex II of MARPOL 73/78 and Not applicable. This product is a solid. Therefore, bulk transport is governed by IMSBC code.

the IBC Code

### 15. Regulatory information

**US federal regulations** 

This product is a "Hazardous Chemical" as defined by the OSHA Hazard Communication Standard 29 CFR 1910.1200 (OSHA) and 8 CCR § 5194 (Cal/OSHA).

TSCA Section 12(b) Export Notification (40 CFR 707, Subpt. D)

Not regulated.

US. OSHA Specifically Regulated Substances (29 CFR 1910.1001-1050)

Not listed.

**CERCLA Hazardous Substance List (40 CFR 302.4)** 

Not listed.

Superfund Amendments and Reauthorization Act of 1986 (SARA)

Hazard categories Immediate Hazard - Yes

Delayed Hazard - No Fire Hazard - No Pressure Hazard - No Reactivity Hazard - No

SARA 302 Extremely hazardous substance

Not listed.

SARA 311/312 Hazardous Yes

chemical

SARA 313 (TRI reporting)

Not regulated.

# Other federal regulations

Clean Air Act (CAA) Section 112 Hazardous Air Pollutants (HAPs) List

Not regulated.

Clean Air Act (CAA) Section 112(r) Accidental Release Prevention (40 CFR 68.130)

Not regulated.

Safe Drinking Water Act

Not regulated.

(SDWA)

**US** state regulations

**US. Massachusetts RTK - Substance List** 

Plaster of Paris (Calcium Sulfate Hemihydrate CAS 10034-76-1) (CAS 26499-65-0)

US. New Jersey Worker and Community Right-to-Know Act

Plaster of Paris (Calcium Sulfate Hemihydrate CAS 10034-76-1) (CAS 26499-65-0)

US. Pennsylvania Worker and Community Right-to-Know Law

Plaster of Paris (Calcium Sulfate Hemihydrate CAS 10034-76-1) (CAS 26499-65-0)

**US. Rhode Island RTK** 

Not regulated.

**US.** California Proposition 65

This product does not contain a chemical known to the State of California to cause cancer, birth defects or other reproductive harm.

US - California Proposition 65 - Carcinogens & Reproductive Toxicity (CRT): Listed substance

Not listed.

#### **International Inventories**

Country(s) or region Inventory name

On inventory (yes/no)\*

United States & Puerto Rico Toxic Substances Control Act (TSCA) Inventory

Yes

\*A "Yes" indicates this product complies with the inventory requirements administered by the governing country(s).

A "No" indicates that one or more components of the product are not listed or exempt from listing on the inventory administered by the governing country(s).

# 16. Other information, including date of preparation or last revision

**Issue date** 12-February-2014

Revision date - Version # 01

Further information Plaster of Paris: Is classified as a hazardous substance but is generally considered a safe material

for routine use. When plaster of Paris is used responsibly it is not considered as a dangerous material. However, when mixed with water this product can become very hot. DO NOT attempt to make a cast enclosing any part of the body. Encasing any body part can cause serious burns and

even amputation of the encased body part.

NFPA Ratings: Health: 1 Flammability: 0 Physical hazard: 0

Hazard Scale: 0 = Minimal 1 = Slight 2 = Moderate 3 = Serious 4 = Severe

**NFPA Ratings** 



Disclaimer

This information is provided without warranty. The information is believed to be correct. This information should be used to make an independent determination of the methods to safeguard workers and the environment.