



SIMPLIFY YOUR JOBSITE BY ELIMINATING TYPE C PANELS

USG SHEETROCK® BRAND ECOSMART PANELS
FIRECODE® X (UL TYPE ULIX™)



Declare.



ONE GYPSUM PANEL SOLUTION FOR WALLS, COLUMNS AND CEILINGS

In addition to applications that require a Type X wallboard, USG Sheetrock® Brand EcoSmart Panels Firecode® X (UL Type ULIX™) can also be installed in the most widely-specified wall, column, and floor - and roof-ceiling UL fire-resistance rated designs as an alternative to Type C panels, significantly reducing jobsite stocking and hanging complexity while promoting greater worker safety and productivity.

Plus, they weigh up to 28% less than standard Type C and up to 22% less than standard Type X, significantly reducing overall project and ceiling installation time.

OTHER BENEFITS INCLUDE:

	USG Sheetrock® Brand EcoSmart Panels Firecode® X (UL Type ULIX™)	USG Sheetrock® Brand Firecode® X Panels (UL Type SCX)	USG Sheetrock® Brand Firecode® C Panels (UL Type C)
Weight	1.8 lb./sq. ft., or 72 lbs. per 4 x 10 panel	2.2 lb./sq. ft., or 88 lbs. per 4 x 10 panel	2.5 lb./sq. ft., or 100 lbs. per 4 x 10 panel
Thickness	5/8 in.	5/8 in.	5/8 in.
Width/Length	48 in. wide-8 ft. to 16 ft. long; 54 in. wide-12 ft. long	48 in. wide-8 ft. to 16 ft. long; 54 in. wide-12 ft. long	48 in. wide-8 ft. to 16 ft. long
UL Design Coverage (Walls, Columns, and Floor- and Roof-Ceiling Applications) ¹	Specified in more 400 UL fire-resistance-rated designs	Specified in 120 UL fire-resistance-rated designs	Specified in 237 UL fire-resistance-rated designs
Productivity Enhancements ²	<ul style="list-style-type: none"> Up to 10% savings in overall project installation time Up to 26% savings in ceiling installation time 	None	None
Sound Performance ³	Tested for use in designs that meet or exceed model building code acoustical requirements	Tested for use in designs that meet or exceed model building code acoustical requirements	Tested for use in designs that meet or exceed model building code acoustical requirements
Meet Architecture 2030 Challenge for Products	<ul style="list-style-type: none"> Up to 25% less global warming potential⁴ Up to 25% less water used in the manufacturing process⁴ 	No	No
Living Building Challenge™ Compliant Declare™ Label	Yes	No	No
Achieved GREENGUARD Gold Certification and qualify as a low VOC emitting material (meets CA 01350)	Yes	Yes	Yes
USDA Certified Biobased Product	Contains 100% USDA certified biobased content	No	No

Notes:

- For the most up-to-date fire-rated coverage, refer to the UL Online Certifications Directory.
- Installation savings are based on a 2016 time-motion study conducted by Ducker Worldwide.
- Acoustical performance is dependent upon the details of any given design. Refer to *USG Sheetrock® Brand EcoSmart Panels Sound Performance Selector Guide* (WB2880) for STC and IIC ratings of tested designs.
- Compared to standard 5/8 in. Type X gypsum panels as presented in the Gypsum Association's *5/8 in. Type X Environmental Product Declaration* (FPI/GA/01/2014) with fresh water usage updated to be in accordance with ISO 14046.

For a safer, more productive and environmentally-friendly jobsite, the choice is simple. Visit usg.com/eco for more information.

WB5178-USA-ENG/rev. 12-18

© 2018 USG Corporation and/or its affiliates.
All rights reserved. | Printed in USA

Manufactured by
United States Gypsum Company
550 West Adams Street
Chicago, IL 60661

800 USG.4YOU (874-4968) | usg.com

PRODUCT INFORMATION

See usg.com for the most up-to-date product information.

GREENGUARD Certified products are certified to GREENGUARD standards for low chemical emissions into indoor air during product usage. For more information, visit ul.com/gg.

TRADEMARKS

The trademarks USG, FIRECODE, SHEETROCK, ULIX, IT'S YOUR WORLD, BUILD IT., the USG logo, the design elements and colors, and related marks are trademarks of USG Corporation or its affiliates. The trademark USGBC is a trademark of U.S. Green Building Council. The trademark ARCHITECTURE 2030 is a trademark of Architecture 2030 Corporation. The trademark DECLARE is a trademark of International Living Future Institute. USDA BIOPREFERRED is a trademark of United States Department of Agriculture.

NOTICE

We shall not be liable for incidental and consequential damages, directly or indirectly sustained, nor for any loss caused by application of these goods not in accordance with current printed instructions or for other than the intended use. Our liability is expressly limited to replacement of defective goods. Any claim shall be deemed waived unless made in writing to us within thirty (30) days from date it was or reasonably should have been discovered.

NOTE

Products described here may not be available in all geographic markets. Consult your USG Company sales office or representative for information. The information in this document is subject to change without notice. USG Corporation assumes no responsibility for any errors that may inadvertently appear in this document.

SAFETY FIRST!

Follow good safety and industrial hygiene practices during handling and installation of all products and systems. Take necessary precautions and wear the appropriate personal protective equipment as needed. Read SDS and related literature on products before specification and/or installation.